



CEPC AHCAL Progress

Jianbei Liu

for the CEPC calorimeter working group

State Key Laboratory of Particle Detection and Electronics

University of Science and Technology of China

CEPC Day / Feb. 14, 2020

Outline



中国科学技术大学
University of Science and Technology of China



- Introduction
- Cell size optimization
- SiPM simulation
- Studies on AHCAL active cell: scintillator tile and SiPM
- Scintillator tile wrapping machine
- Summary

Introduction



中国科学技术大学
University of Science and Technology of China

- AHCAL is one HCAL option for CEPC
- Active medium: scintillator, absorber: steel
- SiPM-on-Tile configuration






- The AHCAL task in the MOST2 CEPC R&D project
 - to validate the CEPC AHCAL option by designing, building and testing a full AHCAL prototype

Optimization based on BMR



中国科学技术大学
University of Science and Technology of China

- 1/3 of Higgs events have 2jets : hadronic decays of bosons
- The requirement from benchmark physics processes on boson mass resolution(BMR) : 4%
- Calorimeter cell size and number of readout layers should be optimized in terms of BMR





$$\text{Accuracy} = \frac{\sqrt{S+B}}{S}$$

Simulation Setup



中国科学技术大学
University of Science and Technology of China

- CEPC V4 geometry
 - Tracker, Si-W ECAL, Sci-Fe HCAL
- Evaluate BMR with $\nu\nu H \rightarrow \text{gluon} + \text{gluon}$
 - K_L is the largest in number in neutral hadrons
 - K_L energy mostly below 30 GeV




Cell-size optimization



中国科学技术大学
University of Science and Technology of China

- A cell-size of 40 mm can meet the requirement of 4% BMR





SiPM Modeling



中国科学技术大学
University of Science and Technology of China

- A SiPM is composed of many pixels each functioning as an avalanche photodiode
- The photons produced in an avalanche occurring in a pixel can propagate to adjacent pixels triggering avalanche in more pixels.





SiPM Cross-talk



中国科学技术大学
University of Science and Technology of China

- Two cross-talk probabilities:
 - Pixel cross-talk probability: cross-talk probability between adjacent pixels
 - SiPM cross-talk probability: possibility that dark count signal is larger than 1.5p.e.
- Dark count signal distribution is determined by pixel cross-talk probability and SiPM amplitude resolution
- Number of pixels only affects dark count rate with no impact on dark count signal distribution.







- Dark Count rate of a single SiPM for over 10p.e. :
 - S12571-15: 0.7Hz
 - SiPM cross-talk probability: 22%
 - Dark count rate (≥ 1.5 p.e.) : 200K
 - NDL-15um: <0.043Hz
 - SiPM cross-talk probability: 11.5%
 - Dark count rate (≥ 1.5 p.e.): 425K for 1mm^2 active area
 - A single layer of AHCAL prototype with $0.7\text{m} \times 0.7\text{m}$ (324 NDL-SiPM / layer) : 14 Hz

Response of SiPM with different sizes



中国科学技术大学
University of Science and Technology of China

- NDL-15um: 1mm×1mm, 1.3mm×1.3mm *and* 2mm×2mm
 - PDE: 35%, Gain: 3.7×10^5
 - SiPM cross-talk probability: 11.5%
 - Number of pixels and light yield both proportional to SiPM size




Required dynamic range



中国科学技术大学
University of Science and Technology of China

- Physics requirement: 400MIP from 100GeV K_L , too much overestimated. Needs to be re-evaluated in a more sensible way.
- A larger SiPM implies a larger maximum input charge for readout electronics. This has to be considered when making a choice of SiPM.



Max Cell Energy for 100GeV KLong



Redesign of scintillator tile



中国科学技术大学
University of Science and Technology of China

- Given the optimized cell-size of 4cm*4cm, the AHCAL active cell needs to be redesigned to accommodate the change from 3cm*3cm to 4cm*4cm

the central cavity in the new design :
5mmx5mmx1.5mm



mean=19.0794

Max mean deviation value=3.7%

uniformity≤5.4%


The light yield decreases significantly for the size expansion. Need to get back the light yield loss → use larger SiPM

Large NDL-SiPM




中国科学技术大学
University of Science and Technology of China

NDL 22-1414B-S








Active area	4x1.3mmx1.3mm
Pixel size	10um
Breakdown	23.7V
PDE@420nm	35%



Light-yield test



中国科学技术大学
University of Science and Technology of China





- The SiPM behaved as expected.
- The combination feature of the SiPM also offers us flexibility in adjusting light yield.

Scintillator tile wrapping machine



中国科学技术大学
University of Science and Technology of China



- An auto-wrapping machine has been built and tested.
- Average wrapping time for a single tile: 45 s

Summary



中国科学技术大学
University of Science and Technology of China

- The cell size of the CEPC AHCAL has been optimized and the cell geometry has been redesigned following the optimization.
- Large SiPM is needed for the large cell size to compensate for the light yield loss due to the size expansion. One NLD SiPM is being tested as such a SiPM candidate.
- SiPM dark count seems not a big concern above a reasonable threshold.
- Tile wrapping machine is ready for tile batch production.
- Not mentioned in the talk : tile batch testing system is about to finish.