The 2020 International Workshop on the High Energy Circular Electron Positron Collider (Oct. 26-28, 2020)

Development of the CEPC Scintillatortungsten ECAL prototype

Yazhou Niu, USTC

On behalf of the CEPC-CALO working group


CEPC Workshop 2020, TDLI/SJTU, Shanghai


Outline

- Introduction
- CEPC Sc-ECAL prototype design and development
- Progress of the prototype commissioning
- Summary and future plan

Introduction

- A fine-grained Sci+W calorimeter concept has been adopted as one of the CEPC ECAL options.
- There is a R&D program dedicated to the CEPC Sci-ECAL option that was started in 2016.
- The R&D goal is to build and characterize a technological Sci-ECAL prototype to validate the CEPC Sci-ECAL design.
- Collaborating with the Sci-ECAL effort in Japan to fully explore the synergy between CEPC and ILC in detector R&D.





Joint Snowmass Lol on ScW-ECAL

Both for ILC and CEPC

Development of Highly Granular Scintillator Strip Electromagnetic Calorimeter

M. Dong^{ab}, J. Liu^{ac}, Y. Liu^{ab}, H. Ono^d, W. Ootani^e, Z. Shen^{ac}, T. Takeshita^f, Z. Wang^{ab}, Y. Zhang^{ac}

^aState Key Laboratory of Particle Detection and Electronics, China ^bInstitute of High Energy Physics, Chinese Academy of Sciences, China ^cUniversity of Science and Technology of China, China ^dNippon Dental University, Japan ^eICEPP, University of Tokyo, Japan ^fShinshu University, Japan

August 30, 2020

Abstract

Highly granular electromagnetic calorimeter based on scintillator strip with SiPM readout (Sc-ECAL) is under development in the framework of the CALICE collaboration for future electron-positron colliders such as ILC and CEPC. After the validation of the concept with the physics prototype, a technological prototype with full layers is being constructed to demonstrate the performance of Sc-ECAL with more realistic technical implementation. The status and prospects of the R&D of Sc-ECAL are briefly described.

SNOWMASS21-IF6 IF0 CALICE-058.pdf


4

3


Outline

- Introduction
- CEPC Sc-ECAL prototype design and development
- Progress of the prototype commissioning
- Summary and future plan

CEPC Sc-ECAL prototype design



- > 30 EBUs + 30 DIFs
- > 15 "super-layers"
- Sc-ECAL prototype




Ecal Basic Unit and absorber


SiPM coupling with scintillator strips

bottom-center embedded

Contributions from Japanese groups




Overview




EBU design and development

- 210 channels readout with 6 SP2E chips divided into 5 rows and 42 columns
- 24 layers of EBU with 10um SiPMs and 6 layers EBU with 15um SiPMs
- Total thickness is controlled under 6mm excluding DIF
- Electronics calibration and SiPM operation voltage adjustment realized
- LED calibration and temperature monitoring circuits under test.




Ecal Basic Unit mass produce












- Ecal Basic Unit mass produce
 - Scintillator strip and ESR machining
 - Scintillator strips wrapping
 - PCB soldering and testing
 - Ecal Basic Unit (EBU) assembly



Super-layer mounting






- One super-layer is an independent unit
- One super-layer consists of two EBU and inserted by two absorber layers

Super-layer mounting

• 16 super-layer in total




Outline

- Introduction
- CEPC Sc-ECAL prototype design and development
- Progress of the prototype commissioning
- Summary and future plan


Grouping combined test

- 5/4 super-layers grouped and combined test with DAQ system
 - Trigger with the coincidence of 2 EBU layers
 - Data acquisition and synchronize work properly
 - All 32 EBU layers have tested and functioned well




0






Cosmic ray test results




- EBUs properly synchronized for each group multi EBU layers
- Event reconstructed correctly
- Cosmic finding and track fitting algorithm are performed in preliminary
- More than 95% events hit more than 5 layers


Cosmic ray test results

• Distinct MIP signals in both SiPMs types, namely 15 um SiPMs and 10 um SiPMs




Assembly of prototype





• 16 super-layers fabricated into the mechanic structure

Assembly of prototype




- 17 super-layers hold most in the mechanic structure
- Two directions are reserved for cables connection(signal and power cables)

Assembly of prototype




- 17 super-layers hold most in the mechanic structure
- Two directions are reserved for cables connection(signal and power cables)
- Fans cooling system and light shield also integrated

Commission of prototype



Commission of prototype



-50

-100


100

50

X [mm]

Hodoscope commissioning

Wataru's group developed





• Hodoscopes setup completed

Hodoscope commissioning

Wataru's group developed

• Check the waveform of HG-OUT on EASIROC using the test charge





- Now working on some problems of EASIROC modules
- Joint with Sc-ECAL prototype CR test in preparation

Outline

- Introduction
- CEPC Sc-ECAL prototype design and development
- Progress of prototype commissioning
- Summary and future plan

Summary and future plan

- CEPC Sci-W ECAL technological prototype is commissioning
 - ✓ DAQ tested with multi-EBUs and the combined system work synchronized
 - ✓ 32 EBU layers have been tested and functional well
 - ✓ Prototype integrated with mechanic structure, fans cooling and light shield function well
 - ✓ The prototype system work properly and validated by preliminary cosmic ray test
- To do next
 - Beam test at IHEP E3 with low energy mixed beam in next two weeks
 - cosmic ray test of the full prototype and calibration for all channels
 - preparation for the test beam at DESY planned in February 2021

Additional

Sc-ECAL prototype

weight	W-Cu alloy	3750 g * 32	> 200 Kg
	Support structure	1220 g * 16	
	EBU	500 g * 32	
	Mechanic, power and cables	~ 50 Kg	
Connectors	HDMI	36	46
	Power (EBU & fans)	4+4	
	Trigger	2	
Cables	Power for EBU (inside + outside)	32+4	104
	HDMI	32*2	
	Fans and trigger	2+2	
Screws	HDMI connector	2*18*2	> 1290
	Fans and EBU power connector	4*6*2+4*4	
	Mechanic framework	(4+16+16+6)*2+(22+12)*2+18+16	
	Support for supper layer	16*8	
	Supper layer	(16+12+24)*16	