

ACTS meeting

Shuiting Xin

Dec 14.2020

Modify Resolution

- ❖ Introduction : resolution inside acts is not fully consistent with resolution in CDR

❖ CDR

#1 2.8um
#2 6um

CEPC baseline Tracker

note: sigma 1 and sigma 2 are the local resolutions, x-y for silicon detector


	Layer Index	R (mm)	half z (mm)	sigma 1 (um)	sigma 2 (um)	volume_id	layer_id
Beampipe		14.25	2470			2	2
VTX Barrel	#1	16	62.5	3	3	25	2
	#2	18	62.5	4	4	25	2
	#3	37	125	4	4	25	4
	#4	39	125	4	4	25	4
	#5	58	125	4	4	25	6
	#6	60	125	4	4	25	6
SIT Barrel	#1	160	371.3	7	9999	28	2
	#2	310	685	7	9999	31	2
SET Barrel	#1	1831	2350	7	9999	36	2
	Layer Index	Rmin (mm)	Rmax (mm)	Z (mm)	sigma 1 (um)	sigma 2 (um)	volume_id (positlayer_id)
FTD Endcap	#1	39	151.9	220	3	3	28,24
	#2	49.5	151.9	371	3	3	4
	#3	70.1	298.9	644.9	7	9999	29,19
	#4	79.1	309	846	7	9999	32,14
	#5	92.6	309	1057.5	7	9999	4
ETD	#1	419.2	1622.8	2420	7	9999	37,6
TPC	#1	400.1	1767.9	2340	r-phi (100um)	z (5000um)	34
							1-222

❖ Previous ACTs


- ◇ VTX : 3um,4um,4um
- ◇ SIT & FTD(expect first 2 layers): x:5um;y:250um

How it implemented

❖ recognize vtx layer1 and layer2 by Module ID











layer2



layer1

```
switch (hit.geometryId().volume()){
case 23:{
    if(hit.geometryId().layer() == 2) {
        if(hit.geometryId().sensitive()>85 || hit.geometryId().sensitive()<22 || hit.geometryId().sensitive()==63 ||
hit.geometryId().sensitive()==65){...}
    }
}
```









Without material: acts, requirement



current

previous

With material: acts, full simulation



current

previous