


环形正负电子对撞机 CEPC



娄辛丑 (高能物理研究所)
代表 CEPC 研究工作组

中科院大科学装置战略规划
国内专家组评审会议

目录

CEPC 简介

科学目标、科学意义和战略价值

拟解决关键科学问题

实验设计方案与技术指标

实验设施的附加技术创新价值

关键技术预研现状、技术成熟程度


核心人员队伍、依托单位已有条件及支持

项目预研、建设预算及时间进度安排



总结

CEPC 简介

- CEPC: 环形正负电子希格斯工厂，也可产生大量的 **H**、**W**、**Z** 玻色子、并在升级后产生 **top** 夸克。目标是发现超出标准模型的新物理。
 - 2012年希格斯玻色子发现后，同年中国科学家提出了**CEPC** 和**SppC**方案
 - CEPC 在 2018 年发布《概念设计报告》，是**首个环形正负电子希格斯工厂的概念设计报告**
 - 关键技术预研达到成熟水平，预计于2023 年初发表《技术设计报告》，包含多个**重要技术创新**
- 建议 2026 年左右开建，
2030s 年代可以开始取数



科学目标、科学意义和战略价值



CEPC/FCC-ee : 最佳设施?

- 可以以最低代价搜索新物理存在的迹象；一旦确认，能立即转入直接搜索模式

$$\mathcal{L} = \mathcal{L}_{SM} + \sum_i \frac{c_i}{M^2} \mathcal{O}_{6,i} \quad \delta \sim c_i \frac{v^2}{M^2}$$

到目前为止未能在 LHC 上发现新物理

直接搜索可达到能标: $M \sim 1 \text{ TeV}$

10% 精度对应的能标: $M \sim 1 \text{ TeV}$


在CEPC/FCC-ee上寻找新物理

精度可比 HL-LHC提高 1 一个量级 (1%)；对应的能标也提高1 个量级: $M \sim 10 \text{ TeV}$

新物理能标大概率 $< 10 \text{ TeV} \rightarrow$ 需要一个正负电子对撞机
如果未在这一能标发现新物理，预示着需要全新新的理论 $\rightarrow$
即使未看到新物理，1%精度的对撞机也非常有意义

精度达到 1%水平的希格斯工厂可以解决一系列紧迫性的科学问题

科学目标、科学意义和战略价值



Chinese Physics C Vol. 43, No. 4 (2019) 043002

Precision Higgs physics at the CEPC*

Fenfen An(安芬芬)^{4,23} Yu Bai(白羽)⁹ Chunhui Chen(陈春晖)²³ Xin Chen(陈新)⁵ Zhenxing Chen(陈振兴)³ Joao Guimaraes da Costa⁴ Zhenwei Cui(崔振威)³ Yaquan Fang(方亚泉)^{4,43,43} Chengdong Fu(付成栋)³ Jun Gao(高俊)¹⁰ Yanyan Gao(高艳彦)²² Yuanning Gao(高原宁)³ Shaofeng Ge(葛韶峰)^{13,29} Jiayin Gu(顾嘉音)^{13,29} Fangyi Guo(郭方毅)¹⁴ Jun Guo(郭军)¹⁰ Tao Han(韩涛)^{3,31} Shuang Han(韩爽)⁴ Hongjian He(何红建)^{11,10} Xianke He(何显柯)¹⁰ Xiaogang He(何小刚)^{11,10,20} Jifeng Hu(胡继峰)¹⁰ Shih-Chieh Hsu(徐士杰)³² Shan Jin(金山)⁸ Maoqiang Jing(荆茂强)^{4,7} Susmita Jyotishmati³ Ryuta Kinchi⁴ Chia-Ming Kuo(郭家铭)³¹ Peizhu Lai(赖培筑)³¹ Boyang Li(李博扬)³ Congqiao Li(李聪乔)³ Gang Li(李刚)^{4,34,3} Haifeng Li(李海峰)¹² Liang Li(李亮)¹⁰ Shu Li(李数)^{11,10} Tong Li(李通)³² Qiang Li(李强)³ Hao Liang(梁浩)^{4,6} Zhijun Liang(梁志均)³ Libo Liao(廖立波)³ Bo Liu(刘波)^{4,23} Jianbei Liu(刘建北)³ Tao Liu(刘涛)¹⁴ Zhen Liu(刘真)^{26,30,4} Xinchou Lou(娄辛丑)^{4,6,33,34} Lianliang Ma(马连良)¹² Bruce Mellado^{17,18} Xin Mo(莫欣)⁴ Mila Pandurovic¹⁶ Jianming Qian(钱剑明)^{24,5} Zhimou Qian(钱卓妮)¹⁹ Nikolaos Rompotis²² Manqi Ruan(阮曼奇)^{4,6} Alex Schuy³² Liangyou Shan(单连友)³ Jingyuan Shi(史静远)³ Xin Shi(史欣)⁴ Shufang Su(苏淑芳)³² Dayong Wang(王大勇)³ Jun Wang(王锦)³ Liantao Wang(王连涛)^{37,7} Yifang Wang(王贻芳)^{4,6} Yuqian Wei(魏或菁)³ Yue Xu(许悦)³ Haijun Yang(杨海军)^{10,31} Ying Yang(杨迎)⁴ Weiming Yao(姚为民)²⁸ Dan Yu(于丹)⁴ Kai Zhang(张凯)^{4,6,8} Zhaoru Zhang(张照茹)⁴ Minxian Zhao(赵明显)² Yueshan Zhao(赵悦山)⁴ Xing Zhao(赵兴)¹⁰

*University of Chinese Academy of Science (UCAS), Beijing 100049, China
School of Nuclear Science and Technology, University of South China, Hengyang 421001, China
Department of Physics, Nanjing University, Nanjing 210093, China
Department of Physics, Southeast University, Nanjing 210096, China
School of Physics and Astronomy, Shanghai Jiao Tong University, KLPPAC-MoE, SKLPPC, Shanghai 200240, China
Tsung-Dao Lee Institute, Shanghai 200240, China
Institute of Particle and Nuclear Physics and School of Physics, Tsinghua University, Beijing 100084, China

CEPC Higgs 物理白皮书

+ o(100) 期刊/ArXiv文章

Table 2.1: Precision of the main parameters of interests and observables at the CEPC, from Ref. [1] and the references therein, where the results of Higgs are estimated with a data sample of 20 ab⁻¹. The HL-LHC projections of 3000 fb⁻¹ data are used for comparison. [2]

Higgs			W, Z and top		
Observable	HL-LHC projections	CEPC precision	Observable	Current precision	CEPC precision
M_H	20 MeV	3 MeV	M_W	9 MeV	0.5 MeV
Γ_H	20%	1.7%	Γ_W	49 MeV	2 MeV
$\sigma(ZH)$	4.2%	0.26%	M_{top}	760 MeV	O(10) MeV
$B(H \rightarrow bb)$	4.4%	0.14%	M_Z	2.1 MeV	0.1 MeV
$B(H \rightarrow cc)$	-	2.0%	Γ_Z	2.3 MeV	0.025 MeV
$B(H \rightarrow gg)$	-	0.81%	R_b	3×10^{-3}	2×10^{-4}
$B(H \rightarrow WW^*)$	2.8%	0.53%	R_c	1.7×10^{-2}	1×10^{-3}
$B(H \rightarrow ZZ^*)$	2.9%	4.2%	R_μ	2×10^{-3}	1×10^{-4}
$B(H \rightarrow \tau^+\tau^-)$	2.9%	0.42%	R_τ	1.7×10^{-2}	1×10^{-4}
$B(H \rightarrow \gamma\gamma)$	2.6%	3.0%	A_μ	1.5×10^{-2}	3.5×10^{-5}
$B(H \rightarrow \mu^+\mu^-)$	8.2%	6.4%	A_τ	4.3×10^{-3}	7×10^{-5}
$B(H \rightarrow Z\gamma)$	20%	8.5%	A_b	2×10^{-2}	2×10^{-4}
$B_{upper}(H \rightarrow inv.)$	2.5%	0.07%	N_ν	2.5×10^{-3}	2×10^{-4}

通过系统全模拟研究、物理-唯像研究量化了CEPC物理潜力

- Higgs: 精度超过HL-LHC极限约一个量级
- 电弱物理: 精度在现有极限下提升 1-2 个量级
- 味物理: 可观测10TeV甚至更高能标的新物理
- 对多种新物理信号极为敏感
- ...

1.2、科学意义 & 2.1、关键具体科学问题

科学目标、科学意义和战略价值




Figure 2.1: Covered energy scales of new physics from CPEEC and HL-LHC, based on measurements of operators in the framework of the Standard Model Effective Field Theory (SMEFT). [1]

CEPC聚焦基础研究的重大突破，去拓展人类对物质世界的认识

科学目标、科学意义和战略价值

正负电子希格斯工厂的科学意义和战略价值非常明确

高能物理学界明确的共识

2013年第464次和2016年第572次香山会议认为“**CEPC 是我国基于加速器的高能物理发展的最佳途径和重大历史机遇**”。

An electron-positron Higgs factory is the highest-priority next collider. For the longer term, the European particle physics community has the ambition to operate a proton-proton collider at the highest achievable energy. Accomplishing these compelling goals will require innovation and cutting-edge technology:

欧洲粒子物理战略讨论：“**正负电子希格斯工厂是未来对撞机发展的最高优先级**”。

*In April 2022, the International Committee for Future Accelerators (ICFA) “reconfirmed the international consensus on the importance of **a Higgs factory as the highest priority for realizing the scientific goals of particle physics**”, and expressed support for the above-mentioned Higgs factory proposals. Recently, the United States also proposed a new linear collider concept based on the cool copper collider (C3) technology [31].*

ICFA：多次强调希格斯工厂项目的最高优先级和科学重要性



Given the **strong motivation** and existence of proven technology to build an **e^+e^- Higgs Factory in the next decade**, the **US should participate** in the construction of any facility that has firm commitment to go forward.

美国Snowmass讨论：“**美国需参与建设任一实质性推进的正负电子希格斯工厂项目**”





科学目标、科学意义和战略价值

- CEPC建成后将成为国际高能物理中心，将在高能物理领域中处于旗舰地位，带动全球科学研究。它可将中国提升至国际粒子物理研究的领导地位。
 - **科学** 将在基础科研和创新中发挥核心作用，对人类文明做出重大贡献。
 - **技术** 可大幅提升中国乃至世界的技术水平。
 - **国际合作** 将聚集几千名国际顶尖人才进行协同创新；加强国际交流，促进国际和平。
 - **教育及人才培养** 将培养大批具有国际水准的人才。
 - **经济带** 培育高科技企业、作为科技中心带动经济发展。


1.3 战略价值

关键科学和技术问题





- 正负电子对撞机被欧洲粒子物理战略等判断为未来对撞机发展的最高优先级。
- CEPC在所有已完成设计报告的正负电子对撞机中，优势明显：
 - **数据早**：预期于2030年代取数（领先FCC-ee约10年），**更大的隧道**（同时容纳pp和正负电子对撞机）
 - **更精确**：相对于直线对撞机有更高的W、Z粒子产额；同时有升级为**质子对撞机**的潜力。
 - **更经济**：造价约为FCC-ee的一半, 亮度指标与之相当。
- **CEPC被粒子物理学界广泛视作未来旗舰型项目的主要选择之一。**

关键科学和技术问题（路线）



实验设施设计方案与技术指标

- 环形对撞机: 较直线对撞机亮度更高
- 100km 周长: 优化后的取值、有助于SppC达到高能量
- 共享隧道: CEPC增强器、对撞环及未来SppC可共用同一隧道
- 能量灵活切换: Higgs, W/Z, top 多能量模式运行



D. Wang et al 2022 JINST 17 P10018

CEPC的加速器主要参数表

	Higgs	W	Z	ttbar
Number of IPs	2			
Circumference [km]	100.0			
SR power per beam [MW]	50			
Energy [GeV]	120	80	45.5	180
Bunch number	415	2161	19918	59
Emittance (ϵ_x/ϵ_y) [nm/pm]	0.64/1.3	0.87/1.7	0.27/1.4	1.4/4.7
Beam size at IP (σ_x/σ_y) [$\mu\text{m}/\text{nm}$]	15/36	13/42	6/35	39/113
Bunch length (SR/total) [mm]	2.3/3.9	2.5/4.9	2.5/8.7	2.2/2.9
Beam-beam parameters (ξ_x/ξ_y)	0.015/0.11	0.012/0.113	0.004/0.127	0.071/0.1
RF frequency [MHz]	650			
Luminosity per IP [$10^{34}/\text{cm}^2/\text{s}$]	8.3	27	192	0.83

实验设施设计方案与技术指标

创新性设计	➤ 100 km 完整/部分双环高亮度设计 ➤ 可灵活切换对撞能量: Higgs、W、Z ➤ 多种能量的不同注入/引出模式 ➤ 世界上首个超高能量、通量的γ同步光源设计
高水平技术	➤ 高效速调管 (瞄准全球最高能量转换效率) ➤ 高性能超导射频腔 (全球领先技术水平) ➤ 新型加速器磁铁: 极弱场二极磁铁, 双孔径二/四极磁铁 (全球首台样机)
探索革命性技术	➤ 束流驱动等离子体尾场加速 (新加速原理) ➤ 高场超导磁体 (国际首倡铁基高场磁体技术)

通过创新性设计和高水平关键技术研发达到 CEPC 的高亮度性能指标。

实验设施设计方案与技术指标

目标

高亮度正负电子环形Higgs工厂

灵活切换Higgs, W, Z, Top运行模式





亮度优化兼顾节能设计

设计




- 完整的加速器设计（包含最新的理念）
- 各能量模式下的lattice设计已完成
- 动力学孔径满足需求
- 充分考虑束束作用与集体效应

一个可工作的100公里包含不同能量模式的加速器设计—已完成

各能量模式的磁聚焦结构



动力学孔径优化（含误差）



3.1 设施设计方案

实验设施设计方案与技术指标

关键技术

- 高效速调管
- 高Q值超导加速腔
- 新型加速器磁铁
- 等离子体加速注入器
- 高场超导磁体

研究现状


- 能量转换效率 > 70%, 目标 80%
- 超过CEPC的设计需求
- 满足CEPC的设计需求
- 正电子加速、高能量(> 10GeV)
- 铁基高温超导磁体技术应用

代表性的先进加速器技术与国际领先实验室比较


设备	指标要求	IHEP 现状	CERN 现状	Fermi 现状	KEK 现状	LBNL 现状
1.3 GHz SRF cavity	$Q = 3 \times 10^{10}$ @ 24 MV/m	$Q = 4.3 \times 10^{10}$ @ 31 MV/m	初步进展	与 IHEP 相当	与 IHEP 相当	无
650MHz SRF cavity (2-cell)	$Q = 4 \times 10^{10}$ @ 22 MV/m	$Q = 6 \times 10^{10}$ @ 22 MV/m	无	与 IHEP 相当	无	无
高效速调管	效率 80%	效率约 70%	在研 80%	无	约 60%	无
高场磁体	20-24 T	已经达到 12.5 T, 正在建造内插高温超导线圈, 目标 16 T	14-16 T	14.5 T	10 T	14-16 T

全球领先的技术

束流驱动等离子体加速作为直线注入器的备选方案




铁基超导技术近年来的快速发展



3.2 设施技术指标

实验设施设计方案与技术指标

探测器



物理要求


玻色子质量分辨率
(BMR ~3%)



设计挑战

- 支持粒子流重建
- 高颗粒度
- 高精度的能量、径迹测量

全新的基于粒子流的
量能器设计. 目标是将
BMR从4% 提升至 3%



探测器	关键性能指标	世界水平	CEPC要求
基于粒子流的 电磁量能器	电磁 能量分辨率	$\sim 20\%/\sqrt{E}$	$< 3\%/\sqrt{E}$
基于粒子流的 强子量能器	单强子 能量分辨率	$\sim 50\%/\sqrt{E}$	$\sim 40\%/\sqrt{E}$

3.2 设施技术指标

实验设施设计方案与技术指标

CEPC创新性设计和关键技术预研处于国际领先水平

概念性创新	可升级	最先进技术	环保、节约	革命性原理	价值溢出
					

- 100km 环形对撞机
- 局部及全双环
- H/W/Z能量可切换
- CEPC对撞环、增能环及SppC共用隧道



- 高效速调管
- 超导射频加速腔
- 极弱场二极磁铁
- 双孔径磁铁
- 等离子体尾场加速注入器
- 铁基高温超导磁体
- 新型粒子流探测器



CEPC扩展升级空间及附加效益

单环束流同步辐射功率可升级至 **50 MW**: 获得更高的亮度 (8×10^{34} @ 240 GeV)

质心能量可升级至 **360 GeV**: 覆盖顶夸克的研究

可升级为高能质子对撞机 (SppC) 质心能量 **>100 TeV**

可扩展性: 提供高能量高通量同步辐射光 (能量可达300MeV), 对多学科的研究具有重要意义

带动多领域技术的发展:

快电子学, 机械, 真空, 束流, 高频, 低温, 新型磁铁, 高精度电源, 控制系统, 大数据, 自动化与智能化 等等

- CEPC升级方案: 设计和建设充分考虑了兼容性;
- CEPC进行多种升级、提升其发现能力, 预期其科学寿命将超过50年;
- **CEPC** 对于多领域、多学科的研究及应用具有显著的溢出效应。

4. 扩展功能、未来升级空间、溢出效应

CEPC 技术预研现状与成熟度


- 已得到科技部、中科院、国家自然科学基金等部门约2.6亿元的经费支持
- 多项关键技术已通过高能所负责的其它大型加速器得到验证: BEPCII, HEPS, ...

CEPC项目预研覆盖 ~ 50% 加速器部件（造价占比）	➤ 高效束调管 ➤ 650MHz 超导高频腔 ➤ 正电子源关键部件 ➤ 高性能直线加速器 ➤ 组合型静电分离器（电场磁场复合） ➤ 低温系统 ➤ 新型磁铁: 弱场二极铁, 双孔径磁铁 ➤ 超快注入引出磁铁 ➤ 真空盒技术 ➤ 大型加速器勘测与准直技术 ➤ 探测器与加速器接口
BEPCII / HEPS覆盖 ~ 40% 加速器部件	➤ 高精度磁铁 ➤ 高稳定磁铁电源 ➤ NEG镀膜真空盒 ➤ 束测与反馈系统 ➤ 传统功率源 ➤ 超导高频腔 ➤ 电子源与传统直线加速器 ➤ 勘测与准直技术 ➤ 高稳定机械系统 ➤ 辐射防护 ➤ 低温系统 ➤ 探测器与加速器接口

~10% 项目来自于未来加速器系统集成、参数联调等工作带来的挑战。
在开建前完成，也给国际合作留有空间。

5. 关键技术预研现状及技术成熟度

CEPC 技术预研现状与成熟度



✓ 样机指标已满足

☑ 样机研发中

Accelerator	Cost (billion CNY)	Ratio
✓ Magnets	4.47	27.3%
✓ Vacuum	3.00	18.3%
☑ RF power source	1.50	9.1%
✓ Mechanics	1.24	7.6%
✓ Magnet power supplies	1.14	7.0%
✓ SCRF	1.16	7.1%
✓ Cryogenics	1.06	6.5%
✓ Linac and sources	0.91	5.5%
✓ Instrumentation	0.87	5.3%
☑ Control	0.39	2.4%
☑ Survey and alignment	0.40	2.4%
✓ Radiation protection	0.17	1.0%
☑ SC magnets	0.07	0.4%
✓ Damping ring	0.04	0.2%

Table 5.1: Summary of key technologies under R&D essential for CEPC

Device	Accelerator	Quantity	CEPC specification	R&D status
1.3 GHz SRF cavity (9-cell)	Booster	96	$Q=3\times 10^{10}$ @ 24 MV/m	Specification met
650 MHz SRF cavity (2-cell)	Collider	240	$Q=4\times 10^{10}$ @22 MV/m	Specification met
650 MHz klystron	Collider	120	Efficiency: 80% Power: 800 kW	Prototype manufactured
C-band NC accelerating tube	Linac	292	Gradient: 45 MV/m	Prototype manufactured
S-band bunch compressor	Linac	35	Peak power gain: 7 dB	Prototype manufactured
Positron source flux concentrator	Linac	1	Central peak magnetic field >6 T	Specification met
Dual-aperture dipole magnet	Collider	2384	Field: 140 Gs-560 Gs aperture: 70 mm length: 28.7 m; harmonic< 5×10^{-4} relative field difference<0.5%	Specification met
Dual-aperture quadrupole magnet	Collider	2392	Gradient: 3.2-12.8 T/m length: 2 m; harmonic< 5×10^{-4} aperture: 76 mm relative field difference<0.5%	Specification met
Weak field dipole	Booster	16320	Field error $\leq 10^{-3}$ @60 Gs	Specification met
Electrostatic separator	Collider	32	Electric field: 2.0 MV/m field uniformity: 5×10^{-4} good field region: 46 mm*11 mm	Specification met by prototype
Cryogenic refrigerator	Collider/Booster	4	18 kW @ 4.5 K	Collaboration with IPC CAS, a refrigerator system of 2.5 kW @ 4.5 K has been developed
Ceramic vacuum chamber and coating	Transport lines	~ 20	$75\times 56\times 5\times 1200$ mm	Prototype in production
MDI SCQ	Collider	8	Gradient: 136T/m; length: 2m Aperture: 40mm; included angle: 33mrad	Prototype in manufacture
Visual instrument	All	11	Image accuracy: $5\mu\text{m}+(5\mu\text{m/m})$ horizontal angle: 1.8 arc-second vertical angle: 2.2 arc-second	Prototype completed

Table 5.2: Summary of key technologies in engineering applications essential for CEPC

Device type	Accelerator	Quantity	CEPC specifications
S-band copper accelerating tube	Linac	111	~30 MV/m
vacuum chamber and coating	Collider/Booster	Total length 200 km	Length: 6 m aperture: 56 mm vacuum: 3×10^{-10} Torr NEG coating pump speed for H_2 : 0.5 L/s·cm ²
BPM and electronics	All	~5000	Closed orbit resolution: 0.6 μm
kicker & fast pulser	Transport line	~25	Pulse width <10 ns (strip-line) trapezoidal pulse width <250 ns (slotted-pipe)
Lambertson septum	Transport line	~20	Septum thickness ≤ 3.5 mm (in-air) thickness ≤ 2 mm (in-vacuum)
Power supply	All	9294	Stability 100-1000 ppm
RF-shielded bellows	Collider/Booster	24000 /12000	Contact force 125 $\pm$ 25 g/finger





Figure 12.3: Cost breakdown of the CEPC accelerator technical systems.

5.1 关键技术预研现状与成熟度


CEPC 技术预研现状与成熟度

国际领先的关键部件


650MHz 超导射频腔




高效速调管



极弱场二极磁铁




100km 加速器准直与安装预研



控制点

骨干网

隧道控制网络



加速器预准直单元



多功能视觉跟踪仪

高效的准直方案 + 新型准直设备研发 → 保证加速器设备安装4年内完成.

5.2 技术的国际领先性

CEPC 技术预研现状与成熟度

- 团队在大装置上积累丰富经验
 - 漂移室、超导磁铁：（北京谱仪）
 - 硅微条探测器：（ATLAS升级）
- 关键技术研发
 - 硅像素探测器与时间投影室
 - 粒子流量能器




- 研发工作覆盖所有子探测器系统
- 进行深度的国际合作
 - 粒子流量能器：与CALICE 国际合作组联合研发
 - 时间投影室：与 LCTPC 国际合作组联合研发
 - 漂移室：与意大利INFN等单位联合研发
 - 硅径迹探测器：与英国/德国/意大利等单位联合研发
 - 硅像素探测器：与法国/西班牙等单位联合研发

粒子流量能器

已经研发出样机，正在测试

探测器	指标	CEPC 物理需求	国际水平	CEPC 样机状态
硅像素 探测器	空间分辨率	~3 微米	3-5 微米 [8-9]	3-5 微米 (小型样机) [10-12]
TPC 时间 投影室 /漂移室	dE/dx (dN/dx) 分辨率	~ 2%	~ 4% [13-14]	~ 4% [15]-[17] (小型样机)
塑料闪烁 体-钨的电 磁量能器	电磁能量分辨率 颗粒度	$< 15\%/\sqrt{E(\text{GeV})}$ $\sim 2 \times 2 \text{ cm}^2$	$12.5\%/\sqrt{E(\text{GeV})}$ [18]	已研制。 分辨率待测量 颗粒度 $0.5 \times 0.5 \text{ cm}^2$
4D 晶体 电磁 量能器	电磁能量分辨率 三维等效颗粒度	$\sim 3\%/\sqrt{E(\text{GeV})}$ $\sim 2 \times 2 \times 2 \text{ cm}^3$	$\sim 2\%/\sqrt{E(\text{GeV})}$ [19-20] N/A	研制中, 预期 $\sim 3\%/\sqrt{E(\text{GeV})}$ [21] 颗粒度满足要求
塑料闪烁 体-钢的强 子量能器	与粒子流算法匹配 单强子能量分辨率	$< 60\%/\sqrt{E(\text{GeV})}$	$57.6\%/\sqrt{E(\text{GeV})}$ [22]	样机研制中
闪烁玻璃 强子 量能器	与粒子流算法匹配 单强子能量分辨率	$\sim 40\%/\sqrt{E(\text{GeV})}$	N/A	研制中, 预期实现 $\sim 40\% \sqrt{E(\text{GeV})}$
超导螺线 管磁铁	磁场强度 径向厚度 物质量	2-3 T $< 150 \text{ mm}$ $< 1.5 X_0$	1-4 T $> 270 \text{ mm}$ [23]-[25]	样机研发中 研制出小尺寸高温超导样缆


硅顶点像素探测器（3-5微米位置分辨率）



粒子流导向的闪烁体-钨的电磁量能器



4维粒子流 晶体量能器



5. 关键技术预研现状，及技术成熟程度

核心团队、依托单位、已有条件及支持




Table 7.2: Team of Leading and core scientists of the CEPC

Name	Brief introduction	Role in the CEPC team
Yifang Wang	Academician of the CAS, director of IHEP	The leader of CEPC, chair of the SC
Xinchou Lou	Professor of IHEP	Project manager, member of the SC
Yuanning Gao	Academician of the CAS, head of physics school of PKU	Chair of the IB, member of the SC
Jie Gao	Professor of IHEP	Convener of accelerator group, vice chair of the IB, member of the SC
Haijun Yang	Professor of SJTU	Deputy project manager, member of the SC
Jianbei Liu	Professor of USTC	Convener of detector group, member of the SC
Hongjian He	Professor of IHEP	Convener of theory group, member of the SC
Shan Jin	Professor of NIT	Member of the SC
Nu Xu	Professor of IHEP	Member of the SC
Meng Wang	Professor of SJTU	Member of the SC
Qinghong Cao	Professor of PKU	Member of the SC
Wei Lu	Professor of THU	Member of the SC
Joao Guimaraes da Costa	Professor of IHEP	Convener of detector group
Jianchun Wang	Professor of IHEP	Convener of detector group
Yuhui Li	Professor of IHEP	Convener of accelerator group
Chenghui Yu	Professor of IHEP	Convener of accelerator group
Jingyu Tang	Professor of IHEP	Convener of accelerator group
Xiaogang He	Professor of SJTU	Convener of theory group
Jianping Ma	Professor of ITP	Convener of theory group

目前有117个加速器方面 + ~300个物理探测器方面科学家；CEPC被批准后预期有规模相当的来自世界领军科学家加入

Table 7.3: Team of the CEPC accelerator system

Number	Sub-system	Convener	Team (senior staff)
1	Accelerator physics	Chenghui Yu, Yuan Zhang	18
2	Magnets	Wen Kang, Fusan Chen	12
3	Cryogenic system	Rui Ge, Ruixiong Han	11
4	SC RF system	Jiyuan Zhai, Peng Sha	12
5	Beam Instrumentation	Yanfeng Sui, Junhui Yue	7
6	SC magnets	Qinjin Xu	10
7	Power supply	Bin Chen, Fengli Long	9
8	Injection & extraction	Junhui Chen	9
9	Mechanical system	Hanli Wang, Lan Dong	4
10	Vacuum system	Yanliang Zhang, Yuesheng Ma	5
11	Control system	Genlei, Gang Li	6
12	Linac injector	Jingyi Li, Jingru Zhang	13
13	Radiation protection	Zhongjian Ma	3
Sum			117



Table 7.4: Team of the CEPC detector system

Number	Sub-system	Conveners	Institutions	Team (senior staff)
1	Pixel Vertex Detector	Zhijun Liang, Qun Ouyang, Xiangming Sun, Wei Wei	CCNU, IFAE, IHEP, NJU, NWPU, SDU, Strasbourg, ...	~ 40
2	Silicon Tracker	Harald Fox, Meng Wang, Hongbo Zhu	IHEP, INFN, KIT, Lancaster, Oxford, Queen Mary, RAL, SDU, Tsinghua, Bristol, Edinburgh, Liverpool, USTC, Warwick, Sheffield, ZJU, ...	~ 60
3	Gaseous detector	Franco Bedeschi, Zhi Deng, Ming Wang, Hongbo Zhu	CEA-Saclay, DESY, IHEP, INFN, KIT, ...	~ 30
4	Magnet	Feipeng Ning	IHEP	~ 10
5	Calorimetry	Yanliang Zhang, Yuesheng Ma	CAEP, IHEP, ...	~ 40
6	Muon	Paolo Giacomelli, Liang Li, Xuefeng Wang	EDU, IHEP, INFN, SJTU ...	~ 20
7	Neutrino	Yanliang Zhang, Yuesheng Ma	IHEP, INFN, SJTU, ...	~ 80
8	Software	Liantao Wang, Mingshui Chen, Shengsen Sun, Weidong Li, Xingtiao Huang	IHEP, SDU, FDU, ...	~ 20
Sum				~ 300

6.1 核心人员队伍的完整性及竞争力

核心团队、依托单位、已有条件及支持

国际委员会



Name	Affiliation	Country
Tatsuya Nakada	EPFL	Japan
Steinar Stapnes	CERN	Norway
Rohini Godbole	CHEP, Bangalore	India
Michelangelo Mangano	CERN	Switzerland
Michael Davier	LAL	France
Lucie Linssen	CERN	Holland
Luciano Maiani	U. Rome	San Marino
Joe Lykken	Fermilab	U.S.
Ian Shipsey	Oxford/DESY	U.K.
Hitoshi Murayama	IPMU/UC Berkeley	Japan
Geoffrey Taylor	U. Melbourne	Australia
Eugene Levichev	BINP	Russia
David Gross	UC Santa Barbara	U.S.
Brian Foster	Oxford	U.K
Marcel Demarteau	ORNL	USA
Barry Barish	Caltech	USA
Maria Enrica Biagini	INFN Frascati	Italy
Yuan-Hann Chang	IPAS	Taiwan, China
Akira Yamamoto	KEK	Japan
Hongwei Zhao	Institute of Modern Physics, CAS	China
Andrew Cohen	University of Science and Technology	Hong Kong, China
Karl Jakobs	University of Freiburg/CERN	Germany
Beate Heinemann	DESY	Germany

International Accelerator Review Committee

- Phillip Bambade, LAL
- Marica Enrica Biagini (Chair), INFN
- Brian Foster, DESY/University of Hamburg & Oxford University
- In-Soo Ko, POSTECH
- Eugene Levichev, BINP
- Katsunobu Oide, CERN & KEK
- Anatolii Sidorin, JINR
- Steinar Stapnes, CERN
- Makoto Tobiyama, KEK
- Zhentang Zhao, SINAP
- Norihito Ohuchi, KEK
- Carlo Pagani, INFN-Milano

International Detector R&D Review Committee

- Jim Brau, USA, Oregon
- Valter Bonvicini, Italy, Trieste
- Ariella Cattai, CERN, CERN
- Cristinel Diaconu, France, Marseille
- Brian Foster, UK, Oxford
- Liang Han, China, USTC
- Dave Newbold, UK, RAL (chair)
- Andreas Schopper, CERN, CERN
- Abe Seiden, USA, UCSC
- Laurent Serin, France, LAL
- Steinar Stapnes, CERN, CERN
- Roberto Tenchini, Italy, INFN
- Ivan Villa Alvarez, Spain, Santader
- Hitoshi Yamamoto, Japan, Tohoku

国际顾问委员会: 全球著名专家组成, 大部分具有大科学装置组织、设计和管理经验, 2015年成立

国际加速器和探测器委员会: 领域内领军专家, 为项目预研工作提供指导

6.1 核心人员队伍的完整性及竞争力 + 6.3 国际合作程度

核心团队、**依托单位**、已有条件及支持



- 高能所是世界上少数拥有以下优势的机构之一：
 - 拥有**多个大型基础科学研究设施**的管理和成功建设经验
 - 拥有一个涵盖加速器和探测器**全部项目**的技术团队，特别是 BEPC/BES 团队
 - 拥有建设大型科研设备所需的全部基础设施
 - 运行多个国际大科学项目，如 BESIII, Daya Bay, JUNO, LHAASO 等。
- **高能所投入CEPC；CEPC战略规划得到科学院支持**


6.2 依托单位已有的条件及支持

核心团队、依托单位、已有条件及支持

国际合作

CEPC 已吸引大量国际合作参与

- 概念设计报告: 来自221所单位（包括140个国外单位）的1143名作者署名
- 已签署并执行超过20份合作备忘录
- 已开展深入的国际合作物理研究
- 海外科学家在各个子系统（特别是探测器系统）预研中做出了重要贡献
- 2014以来，每年召开CEPC国际会议
- 组织欧洲-美洲版CEPC国际会议: 下一次会议地点在马赛
- 2015年起，每年参加香港科技大学高能物理工作月



6.3 国际合作程度

核心团队、依托单位、已有条件及支持

工业界的参与



- CEPC产业促进会（CIPC）成立于2017年，目前包括约70个高科技企业。覆盖超导材料、超导腔、低温恒温器、大型液氦低温系统、速调管、电子学器件、功率源、真空系统、土木工程等。CIPC通过联合研制和攻关，共同推动核心技术预研，促进产业协同发展，**为量产作好准备**。
- CEPC研究团队也在积极寻求**国际产业界的合作和供货**。
- CEPC将极大提升相关技术的发展(经济效益显著)。

7.2 项目建设的性价比

项目预研和建设预算，项目时间线

表 8.1: CEPC 各系统建设预算 (CDR)

总计 (亿人民币)	358	
加速器	164	
对撞环		99.2
增强器		39.2
直线注入器与粒子源		9.1
阻尼环		0.44
Common: 低温系统		10.6
检视 & 准直系统		4
辐射防护		1.7
土建施工	102	
探测器	40	
γ 束流线	3	
项目管理 (1%)	3	
不可预见费用 (15%)	46	

CEPC Work Breakdown Structure (WBS) - Accelerator															
Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	WBS Element Title	Type	Unit	Number	Price (10,000 Yuan)	Total Price (10,000 Yuan)	WBS Element Description		
1	2						TOTAL (accelerator)					1641673			
1	2						Accelerator Physics					1000			
6	2	1					Analytic and simulation studies								
7	2	2					Code development								
8	2	3					Computing hardware								
9	2	4					Computing software								
10	2	5					Publication								
11	3						Collider (Ch 4) Collider ring					991757			
12	3	1					Superconducting RF System (Ch 4.3.1)					95200			
13	3	1	1				Cavity	650 MHz 2-cell niobium	one	240	180				
14	3	1	2				Gyromodule	2 K, for 6 cavities	one	40	200				
15	3	1	3				Input coupler	650 MHz, single window, wa	one	240	40				
16	3	1	4				HOM coupler	coaxial, detachable	one	480	15				
17	3	1	5				HOM absorber	room temperature	one	80	40				
18	3	1	6				Tuner	end lever with piezo	one	240					
19	3	1	7				Vacuum, valve, cables, tooling, assembly, etc.		one	40			16800		
20	3	1	8												
21	3	1	9												
22	3	2					RF Power Source (Ch 4.3.2)								
23	3	2	1				Klystron	650MHz/800kW	SET				36000		
24	3	2	2				PSM source	120kV/16A	SE				42000		
25	3	2	3				Circulator and dummy load	800kW			250		30000		
26	3	2	4				LLRF				25		3000		
27	3	2	5				Waveguide	800kW			100		12000		
28	3	2	6												
29	3	2	7												
30	3														
31	3	2	8												
32	3	2	9												
33	3	3					Magnets (Ch 4.3.3)						304986		
34	3	3	1				Dipoles						173192		
35	3	3	1	1			Dual aperture dipole		one	2384	69		164496		
36	3	3	1	1	1		Coils (main & trim)		m	28.7	0.1		2.87	Aluminum	
37	3	3	1	1	2		Lamination		m	28.7	0.6		17.22	Steel - J23	
38	3	3	1	1	3		Stainless steel		m	28.7	0.4		11.48	Support and structure	
39	3	3	1	1	4		Lead		m	28.7	0.2		5.74	Radiation shielding	
40	3	3	1	1	5		Other materials		m	28.7	0.1		2.87	Epoxy, paint, etc.	
41	3	3	1	1	6		Accessories		set	1	0.72		0.72	Water cooling, temperature swith, electric connectors, etc.	
42	3	3	1	1	7		Toolings		one	1	1.2		1.2	Minding former, casting mould, punching die, stacking tooling, etc.	
43	3	3	1	1	8		Machining & assembly		one	1	15		15		
44	3	3	1	1	9		Inspection & test		one	1	0.1		0.1		
45	3	3	1	1	10		Package & delivery		one	1	0.5		0.5		
46	3	3	1	1	11		Overhead		one	1	1.5		1.5		
47	3	3	1	1	12		Tax		one	1	7		7		

CDR 中的造价估算之一: ~1000 独立项相加


- CDR采取两种独立的方法估算造价：差别在10% 以内
- CEPC 设计基于成熟的技术和研究结果，减少造价估算的不确定性
- TDR阶段的建设预算正在进行：估价没有明显变化

7.1 项目预研和建设预算

项目预研及建设经费 - 性价比分析

- CEPC可带来**价值不可估量**的发现和知识。CEPC预期在2030年代产生Higgs数据，将人类的科研带到一个全新的时代。
- **CEPC进行了系统优化**，通过设计和技术上的创新大幅压低了造价。
- CEPC将吸引、支持上千名科研人员进行长达数十年的科研。相对其他大科学工程、其他学科、每人每年平均的科研经费并没有提升、甚至更低（规模效应）。
- CEPC升级潜力巨大，**大力推动技术发展**，是全球人才培养和**协同创新**的高地；有望在若干关键技术上带来革命性突破，应用前景巨大。
- CEPC将吸引显著的**国际合作**，促进国际交流、促进国际和平。
- CEPC及其附近的科学城将显著推动当地**经济发展**。

项目预研和建设预算，项目时间线



7.3 项目时间进度安排

总结

CEPC

- 将探索粒子物理领域最重要、最紧迫的科学问题。
- 战略价值巨大，比较优势明显、建成后将成为领域内旗舰设施。
- 设计技术趋于成熟、优异升级潜力、重大附加值和溢出效应。
- 人员队伍完整、经验丰富并具有国际竞争力；得到高能所全力支持和有效的国际合作，为实施项目打下了基础。
- 提议：在“十五五”期间开建、于“十六五”期间建成并开始运行。
- 将使中国获得粒子物理研究的国际引领地位，对人类科学探索作出重大贡献。

Back up

Budgets for R&D and construction

Cost and benefit analysis

- CEPC **is priceless** in revealing potential discoveries & knowledge. CEPC may provide the **Higgs data** in 2030s, thus brings upon mankind a new era in the science exploration.
- The **current CEPC design is optimized**. The cost is reduced through innovative design & new tech. development.
- CEPC will host **thousands of users and operates for decades**. The investment per researcher per year is comparable, or even smaller than that of other facilities & other disciplines.
- CEPC has the upgradable capability and provides **strong boost to the technologies**, is a highland for global talent training & **cooperative innovations**. It could revolutionize multiple key-tech. that has huge potential for application.
- CEPC attracts significant **International collaboration**, enhance the international communication, contribute to the World Peace.
- The science city of CEPC could strongly **promote** local **economic**.

7.2 Cost-benefit evaluation of the project

Summary


CEPC

- will address most pressing & critical science problems
- adds enormous strategic values; has many advantages; will be in a leading position if realized.
- design-technologies reaching maturity; offers great upgrade options and many added values and benefits
- has a strong-experienced team, IHEP support and international cooperation, which are keys to bring CEPC to fruition
- schedule follows China's 5-year planning; expects to complete R&D and preparation to build the facility and carry out the science program
- will position China to be a leading position in particle physics and contribute to the world in a major way.

Science


Scientific objective: Higgs field & Challenges to the SM

Gauge




Higgs

- Hierarchy: From neutrinos to the top mass, masses differs by 13 orders of magnitude
- Naturalness: Fine tuning of the Higgs mass
- Masses of Higgs and top quark: meta-stable of the vacuum
- Unification?
- Dark matter candidate?
- Not sufficient CP Violation for Matter & Antimatter asymmetry
- **Most issues related to Higgs**



关键科学和技术问题（路线）



2.1 关键科学问题 & 2.2 关键技术路线

CEPC Measurement Precision

Table 2.1: Precision of the main parameters of interests and observables at CEPC, from Ref. [1] and the references therein, where the results of Higgs are estimated with a data sample of 20 ab^{-1} . The HL-LHC projections of 3000 fb^{-1} data [2] are used for comparison

Higgs			W, Z, and top		
Observable	HL-LHC projections	CEPC precision	Observable	Current precision	CEPC precision
M_H	20 MeV	3 MeV	M_W	9 MeV	0.5 MeV
Γ_H	20%	1.7%	Γ_W	49 MeV	2 MeV
$\sigma(ZH)$	4.2%	0.26%	M_{top}	760 MeV	$\mathcal{O}(10)$ MeV
$B(H \rightarrow bb)$	4.4%	0.14%	M_Z	2.1 MeV	0.1 MeV
$B(H \rightarrow cc)$	-	2.0%	Γ_Z	2.3 MeV	0.025 MeV
$B(H \rightarrow gg)$	-	0.81%	R_b	3×10^{-3}	2×10^{-4}
$B(H \rightarrow WW^*)$	2.8%	0.53%	R_c	1.7×10^{-2}	1×10^{-3}
$B(H \rightarrow ZZ^*)$	2.9%	4.2%	R_μ	2×10^{-3}	1×10^{-4}
$B(H \rightarrow \tau^+\tau^-)$	2.9%	0.42%	R_τ	1.7×10^{-2}	1×10^{-4}
$B(H \rightarrow \gamma\gamma)$	2.6%	3.0%	A_μ	1.5×10^{-2}	3.5×10^{-5}
$B(H \rightarrow \mu^+\mu^-)$	8.2%	6.4%	A_τ	4.3×10^{-3}	7×10^{-5}
$B(H \rightarrow Z\gamma)$	20%	8.5%	A_b	2×10^{-2}	2×10^{-4}
$B_{\text{upper}}(H \rightarrow \text{inv.})$	2.5%	0.07%	N_ν	2.5×10^{-3}	2×10^{-4}

Accelerator Design, R&D & Maturity

Accelerator	Cost (billion CNY)	Ratio	CEPC R&D	BEPCII /HEPS
Magnets	4.47	27.3%	20.0%	7.0%
Vacuum	3.00	18.3%	10.0%	8.0%
RF power source	1.50	9.1%	5.0%	2.0%
Mechanics	1.24	7.6%	N.A	6.6%
Magnet power supplies	1.14	7.0%	0.5%	6.5%
SCRF	1.16	7.1%	5.1%	2.0%
Cryogenics	1.06	6.5%	3.0%	2.5%
Linac and sources	0.91	5.5%	2.0%	2.5%
Instrumentation	0.87	5.3%	2.3%	3.0%
Control	0.39	2.4%	0.1%	0.5%
Survey and alignment	0.40	2.4%	1.4%	1.0%
Radiation protection	0.17	1.0%	0.1%	0.2%
SC magnets	0.07	0.4%	0.2%	0.1%
Damping ring	0.04	0.2%	N.A.	N.A.
Total			49.7%	41.9%


Accelerator design: Compatible Operation

DESIGN GOAL


Compatible operation for Higgs, W, Z and Top runs

SOLUTIONS

- Partial/full partial double ring design with special RF station bypass scheme



RF station by pass scheme for Higgs, W, Z



4 IP design in progress...

Accelerator design: Environmental Friendly Design

DESIGN GOAL

Environmental friendly & economic operation



SOLUTIONS

- High efficiency Klystron
- High Q SRF cavity
- Dual Aperture Magnets




High Q SRF Cavity & Module



High Efficiency Klystron



Dual Aperture Magnets








Accelerator design: Pursing high Luminosity

DESIGN GOAL

Increase Luminosity


SOLUTIONS

- Lattice optimization for all energies
- Crab waist scheme with large cross angle and sextuples





Accelerator technology Maturity

- Intensive R&D covers systems with a high budget ratio:
 - magnet (27%), vacuum (18%), RF power source (9%), mechanical (8%), superconducting RF (7%), cryogenic(7%), beam source and linac (6%), instrumentation (5%), and alignment (2%)





State-of-the-art SRF cavities



650 MHz 2- & 1-cell SRF cavity test results







1.3GHz 9-cell SRF cavity test results



State-of-the-art **P-band Klystron**



70.5% @ 630kW efficiency in the present status
Goal: ~80% efficiency




State-of-the-art High Field Magnet

Iron based HTS coil


2021 . . .




Quench Current w.r.t. Background Field of the IBS Racetracks Coils



2022 . . .



After heat-treatment $\Phi 34$ DPC after heat-treatment $\Phi 34$ DPC after epoxy impregnating Six DPCs in series Coil after epoxy impregnating Ic measurement at 32 T





Comments from SUST reviewers :

- ...the new results that can have a **strong impact on the conductor and magnet community.**
- ...demonstrated the **great potential of Iron-Based Superconductor in the development of next-generation accelerators.**
- It is of **certain significance in the path of applications of Iron-Based Superconductor...**

Preparation for the future SPPC upgrade, and significant potential for multiple applications

Dual aperture SC dipole (NbTi+Nb3Sn) achieves 12.47 T at 4.2 K



Feasibility study: Polarized Beams


DESIGN GOAL

Resonant Depolarization for 10^{-6} -level precision beam energy calibration at Z, W


>50% longitudinal polarization for Z, W and even Higgs

SOLUTIONS


- Injection of polarized beams
 - Polarized beam generation from the source
 - Polarization maintenance with “Spin resonance free” booster design
- Solenoid-based spin rotators in the collider rings



Extension for polarized beams



Spin resonance free booster







Spin rotators in Collider rings

Novel Acceleration Principle: PWFA Wakefield

PWFA plasma acceleration as an alternative option for high performance Linac, promoting acceleration technology:

- Cascaded Acceleration
- Positron Acceleration
- High bunch charge



Key technologies validated by BEPC II & HEPS

Device type	Accelerator	Quantity	CEPC specifications
S-band copper accelerating tube	Linac	111	~30 MV/m
vacuum chamber and coating	Collider/ Booster	Total length 200 km	Length: 6 m aperture: 56 mm vacuum: 3×10^{-10} Torr NEG coating pump speed for H_2 : $0.5 \text{ L/s} \cdot \text{cm}^2$
BPM and electronics	All	~5000	Closed orbit resolution: $0.6 \mu\text{m}$
kicker & fast pulser	Transport line	~25	Pulse width <10 ns (strip-line) trapezoidal pulse width <250 ns (slotted-pipe)
Lambertson septum	Transport line	~20	Septum thickness $\leq 3.5 \text{ mm}$ (in-air) thickness $\leq 2 \text{ mm}$ (in-vacuum)
Power supply	All	9294	Stability 100-1000 ppm
RF-shielded bellows	Collider Booster	24000 /12000	Contact force $125 \pm 25 \text{ g/finger}$

- BEPC, BEPC II: 40 years experience of designing, constructing, and operating collider.
- HEPS: light source with highest brightness through advanced accelerator technology.



All the CEPC systems are well covered by currently accumulated technologies, the R&D, and validation projects.

Compared to New collider Designs




Figure 5: Possible location for a 3 km Israpur linear collider at Fermilab site considered for C3.





Figure 6: Possible location of the 200 GeV BEPCIII collider at Peking. The 200 GeV BEPCIII is shown. The map shows the location of the 200 GeV BEPCIII and the proposed circular collider ring.



Figure 7: Fermilab site showing the proposed 30 km site-dilator collider ring.

Twin LC with energy recovery



- Multiple new proposals in recent years, especially in the snowmass studies
 - Handful of new electron positron collider design (i.e., C3, HELEN, etc)
 - Colliders with different particles: Muon collider, Photon Collider, electron-photon collider
- Compared to the electron-positron Higgs factories, the luminosity and scientific potential of these new designs are relatively limited, and corresponding technologies are relatively immature.


Detector Design & R&D

Detector design


Well understood Physics Requirements.

Significant International Collaboration




PFA oriented design emphasizing the performance of ECAL & Pid to enhance the physics cases, especially flavor, etc.



(Baseline Design)
Particle Flow Approach



PFA approach with Full Silicon Tracking



Sub-detectors and Key techs


Table 3.2: All sub-detectors and the key technologies

Sub-detector	Key technology	Key Specifications
Silicon vertex detector	Spatial resolution and materials	$\sigma_{r\phi} \sim 3 \mu\text{m}, X/X_0 < 0.15\%$ (per layer)
Silicon tracker	Large-area silicon detector	$\sigma(\frac{1}{p_T}) \sim 2 \times 10^{-5} \oplus \frac{1 \times 10^{-3}}{p \times \sin^{3/2} \theta} (\text{GeV}^{-1})$
TPC/Drift Chamber	Precise dE/dx (dN/dx) measurement	Relative uncertainty 2%
Time of Flight detector	Large-area silicon timing detector	$\sigma(t) \sim 30 \text{ ps}$
Electromagnetic Calorimeter	High granularity 4D crystal calorimeter	EM energy resolution $\sim 3\%/\sqrt{E(\text{GeV})}$ Granularity $\sim 2 \times 2 \times 2 \text{ cm}^3$
Magnet system	Ultra-thin High temperature Superconducting magnet	Magnet field 2 – 3 T Material budget $< 1.5 X_0$ Thickness $< 150 \text{ mm}$
Hadron calorimeter	Scintillating glass Hadron calorimeter	Support PFA jet reconstruction Single hadron $\sigma_E^{had} \sim 40\%/\sqrt{E(\text{GeV})}$ Jet $\sigma_E^{jet} \sim 30\%/\sqrt{E(\text{GeV})}$

CEPC EM calorimeter


- PFA-oriented High granularity calorimeters were constructed based on mature technology
 - Scintillators + iron hadron calorimeter (AHCAL)
 - Scintillators + TungstenCAS EM calorimeter (Sci-W ECAL)

Sub-detector	Specification	Requirement	World-class level	CEPC prototype
Scintillator-W ECal	Energy Resolution	$< 3\%/\sqrt{E}$	12.5% [18]	to be measured
	Granularity	$\sim 2\text{cm} \times 2\text{cm}$		5mm $\times$ 5mm
Scintillator-Steel HCal	Single Hadron Energy Resolution	$< 60\%/\sqrt{E}$	57.6% [20]	Prototyping [19] Prototyping



CEPC Vertex detector R & D

- CEPC Vertex detector sensor R & D timeline
 - Based on Tower Jazz CIS 180nm process (Jadepix , TaichuPix)
 - Based SOI 200nm process (CPV chip)



CEPC TPC detector R & D



- Highlights of CEPC TPC detection technology R&D
 - Pad readout towards pixelated readout TPC to increased PID to 2-3%
 - Massive production and assemble MPGD lab has been setup at IHEP
 - Very activate international collaboration with LCTPC and RD51

Publications by TPC group:
<https://doi.org/10.1016/j.nima.2022.167241>
<https://doi.org/10.1109/NSS/MIC44867.2021.9875566>
<https://doi.org/10.1088/1748-0221/15/09/C09065>
<https://doi.org/10.1088/1748-0221/15/05/P05005>
<https://dx.doi.org/10.1142/S0217751X20410146>
<https://doi.org/10.1088/1674-1137/41/5/056003>
<https://doi.org/10.1088/1748-0221/15/02/T02001>

Prototype plan at IHEP

- Realization of pixelated technology collaborated with Tsinghua


Bump bond pixelated readout with Micromegas detector	Module size	To be addressed by R&D
• $\geq 300\text{ }\mu\text{m} \times 300\text{ }\mu\text{m}$ • Developed the readout chip by Tsinghua University • Developed the Micromegas detector sensor at IHEP • Development of the new module and prototype in the end of 2022	1-2 cm ²	• Research on pixelated readout technology realization • Optimization of cluster profile and pad size • Study of the '$dN_{cl}+dx$'
	100 cm ²	• Study the distortion using UV laser tracks and UV lamp to create ions disk • In-situ calibration with UV Laser system • Study of the '$dE/dx+dN_{cl}/dx$'




CEPC Team @ LHC upgrade

LHC upgrade Project	Contribution	IHEP member Leadership
ATLAS high granularity timing detector (HGTD)	~34% modules and sensors (~2700 modules, sensor by Chinese foundry)	Project leader Coordinators in Sensors/ modules
LHCb UT tracker upgrade	System design, test and integration	Deputy project leader
ATLAS ITK strip detector upgrade	~10% modules in Barrel (100 modules)	Coordinator in China/UK cluster
CMS HGcal	~ 20% modules (~100 m ² area) silicon module	
High luminosity LHC upgrade	Contributing 13 CCT magnetic	


ATLAS ITK strip upgrade
Module prototyping



ATLAS HGTD
Sensor developed by IHEP



CMS HGcal
module prototyping



HL-LHC accelerator CCT magnet

April 2020
Xi'an China

Team

Organization @ R&D stage

CEPC has a complete and competitive core team that is **well-positioned to realize and operate this project**


Institution Board composed of 32 institutions, including multiple top university/institutes

Management team with comprehensive experience in project initiation, design, construction, operation, maintenance, management, and upgrade.

IARC & IDRC composed of leading experts of this field, provide valuable guide

IAC composed of global renowned scientists and top laboratory or project leaders who have ample experience in project management, planning, and execution of strategies

Younger talents responsible for physics study and key technology R&D. The CEPC **accelerator & detector R&D team** composed of ~400 staffs, with equivalent number of postdocs and students.



.....

Core R&D team: young and active scientists





Table 7.3: Team of the CEPC accelerator system

Number	Sub-system	Convener	Team (senior staff)
1	Accelerator physics	Chenghui Yu, Yuan Zhang	18
2	Magnets	Wen Kang, Fusan Chen	12
3	Cryogenic system	Rui Ge, Ruixiong Han	11
4	SC RF system	Jiyuan Zhai, Peng Sha	12
5	Beam Instrumentation	Yanfeng Sui, Junhui Yue	7
6	SC magnets	Qingjin Xu	10
7	Power supply	Bin Chen, Fengli Long	9
8	Injection & extraction	Jinhui Chen	7
9	Mechanical system	Jianli Wang, Lan Dong	4
10	Vacuum system	Haiyi Dong, Yongsheng Ma	5
11	Control system	Ge lei, Gang Li	6
12	Linac injector	Jingyi Li, Jingru Zhang	13
13	Radiation protection	Zhongjian Ma	3
Total			117



Table 7.4: Team of the CEPC detector system

Number	Sub-system	Conveners	Institutions	Team (senior staff)
1	Pixel Vertex Detector	Zhijun Liang, Qun Ouyang, Xiangming Sun, Wei Wei	CCNU, IFAE, IHEP, NJU, NWPU, SDU, Strasbourg, ...	~ 40
2	Silicon Tracker	Harald Fox, Meng Wang, Hongbo Zhu	IHEP, INFN, KIT, Lancaster, Oxford, Queen Mary, RAL, SDU, Tsinghua, Bristol, Edinburgh, Liverpool, USTC, Warwick, Sheffield, ZJU, ...	~ 60
3	Gaseous detector	Franco Bedeschi, Zhi Deng, Mingyi Dong, Huirong Qi	CEA-Saclay, DESY, LCTPC Collab., IHEP, INFN, NIKHEF, THU ...	~ 30
4	Magnet	Feipeng Ning	IHEP	~ 10
5	Calorimetry	Roberto Ferrari, Jianbei Liu, Haijun Yang, Yong Liu	CALICE Collab., IHEP, INFN, SJTU, USTC..	~ 40
6	Muon	Paolo Giacomelli, Liang Li, Xiaolong Wang	FDU, IHEP, INFN, SJTU ...	~ 20
7	Physics	Manqi Ruan, Yaquan Fang, Liantao Wang, Mingshui Chen	IHEP, FDU, SJTU, ...	~ 80
8	Software	Shengsen Sun, Weidong Li, Xingtao Huang	IHEP, SDU, FDU, ...	~ 20
Total				~ 300

Younger talents responsible for physics study and key technology R&D. The CEPC accelerator & detector R&D team composed of ~400 staffs, with equivalent number of postdocs and students.

R&D team actively participate the LHC experiments & HL-LHC upgrade

International Advisory Committee (since 2015)




Name	Affiliation	Country
Tatsuya Nakada	EPFL	Japan
Steinar Stapnes	CERN	Norway
Rohini Godbole	CHEP, Bangalore	India
Michelangelo Mangano	CERN	Switzerland
Michael Davier	LAL	France
Lucie Linssen	CERN	Holland
Luciano Maiani	U. Rome	San Marino
Joe Lykken	Fermilab	U.S.
Ian Shipsey	Oxford/DESY	U.K.
Hitoshi Murayama	IPMU/UC Berkeley	Japan
Geoffrey Taylor	U. Melbourne	Australia
Eugene Levichev	BINP	Russia
David Gross	UC Santa Barbara	U.S.
Brian Foster	Oxford	U.K.
Marcel Demarteau	ORNL	USA
Barry Barish	Caltech	USA
Maria Enrica Biagini	INFN Frascati	Italy
Yuan-Hann Chang	IPAS	Taiwan, China
Akira Yamamoto	KEK	Japan
Hongwei Zhao	Institute of Modern Physics, CAS	China
Andrew Cohen	University of Science and Technology	Hong Kong, China
Karl Jakobs	University of Freiburg/CERN	Germany
Beate Heinemann	DESY	Germany

Global renowned scientists and top laboratory or project leaders who have ample experience in project management, planning, and execution of strategies

IARC & IDRC

International Accelerator Review Committee

- Phillip Bambade, LAL
- Marica Enrica Biagini (Chair), INFN
- Brian Foster, DESY/University of Hamburg & Oxford University
- In-Soo Ko, POSTECH
- Eugene Levichev, BINP
- Katsunobu Oide, CERN & KEK
- Anatolii Sidorin, JINR
- Steinar Stapnes, CERN
- Makoto Tobiya, KEK
- Zhentang Zhao, SINAP
- Norihito Ohuchi, KEK
- Carlo Pagani, INFN-Milano



Project guided by International Accelerator and Detector Review Committees composed of leading experts of this field

International Detector R&D Review Committee

- Jim Brau, USA, Oregon
- Valter Bonvicini, Italy, Trieste
- Ariella Cattai, CERN, CERN
- Cristinel Diaconu, France, Marseille
- Brian Foster, UK, Oxford
- Liang Han, China, USTC
- Dave Newbold, UK, RAL (chair)
- Andreas Schopper, CERN, CERN
- Abe Seiden, USA, UCSC
- Laurent Serin, France, LAL
- Steinar Stapnes, CERN, CERN
- Roberto Tenchini, Italy, INFN
- Ivan Villa Alvarez, Spain, Santader
- Hitoshi Yamamoto, Japan, Tohoku

The 2021 CEPC International Accelerator Review Committee

Review Report

May 19, 2021

Overview

The CEPC International Accelerator Review Committee was held remotely due to the Covid-19 pandemic on May 11th and 12th 2021. This is the second IARC meeting.

The Circular Electron Positron Collider (CEPC+SppC) Study Group, currently hosted by the Institute of High Energy Physics of the Chinese Academy of Sciences, completed the conceptual design of the CEPC accelerator in 2018. As recommended by the CEPC International Advisory Committee (IAC), the group began the Technical Design Report phase for the CEPC accelerator in 2019, with a completion target year of 2022. Meanwhile an International Accelerator Review Committee (IARC) has been established to advise on all matters related to CEPC accelerator design, the R&D program, the study of the machine-detector interface region, and the compatibility with an upgrade to the t-bar energy region, as well as with a future SppC. The first IARC meeting took place in Beijing during the CEPC international workshop on Nov. 18-21, 2019.

2021 Second CEPC IARC Meeting

IARC Committee


October 20th, 2021

The Circular Electron Positron Collider (CEPC) and Super Proton-Proton Collider (SppC) Study Group, currently hosted by the Institute of High Energy Physics of the Chinese Academy of Sciences, completed the conceptual design of the CEPC accelerator in 2018. As recommended by the CEPC International Advisory Committee (IAC), the group began the Technical Design Report (TDR) phase for the CEPC accelerator in 2019, with a completion target year of 2022. Meanwhile an International Accelerator Review Committee (IARC) has been established to advise on all matters related to CEPC accelerator design, the R&D program, the study of the machine-detector interface region, and the compatibility with an upgrade to the t-bar energy region, as well as with a future SppC.


The second 2021 CEPC International Accelerator Review Committee was held remotely due to the Covid-19 pandemic on October 11th to 14th 2021. A total of 22 talks were presented on a variety of topics.

1 General comments

The Committee congratulates the CEPC team for the work performed in the last months and presented at this meeting. In particular, the progress on the R&D of the hardware components looks very promising. The team has updated the table of parameters for the high-luminosity running, as well as the lattices and components for all accelerator systems: sources, Linac, Booster and Collider.




Organization: toward construction & operation



Embrace the International collaboration

Engaging with theory community



Support

Large-Scale Acc. Facilities: High Energy Photon Source



beam energy 6 GeV, 1.36KM, $\leq 0.06\text{nm}\cdot\text{rad}$, 14 beam lines

Carried out by IHEP, to be completed in 2025,
great training and preparation for CEPC: validate significant part
of CEPC technologies

Device type	Accelerator	Quantity	CEPC specifications
S-band copper accelerating tube	Linac	111	$\sim 30\text{ MV/m}$
vacuum chamber and coating	Collider/ Booster	Total length 200 km	Length: 6 m aperture: 56 mm vacuum: $3 \times 10^{-10}\text{ Torr}$ NEG coating pump speed for H_2 : $0.5\text{ L/s}\cdot\text{cm}^2$
BPM and electronics	All	~ 5000	Closed orbit resolution: $0.6\text{ }\mu\text{m}$
kicker & fast pulser	Transport line	~ 25	Pulse width $< 10\text{ ns}$ (strip-line) trapezoidal pulse width $< 250\text{ ns}$ (slotted-pipe)
Lambertson septum	Transport line	~ 20	Septum thickness $\leq 3.5\text{ mm}$ (in-air) thickness $\leq 2\text{ mm}$ (in-vacuum)
Power supply	All	9294	Stability 100-1000 ppm
RF-shielded bellows	Collider Booster	24000 /12000	Contact force $125\pm 25\text{ g/finger}$



Support by Platform of Advanced Photon Source


Support Key Technology R&D:

- SRF ➤ Magnet ➤ Vacuum ➤ Klystron ➤ Electric Power Source ➤ Cryogenic System
- Mechanical system & Alignment ➤ e- gun

Facility: CEPC SRF test facility (lab) is located in IHEP Huairong Area of 4500m²



New SC Lab Design (4500m²)




New SC Lab will be fully functional in 2021



Cryogenic system hall in Jan. 16, 2020




Large-Scale Acc. Facilities: China Spallation Neutron Source



- One of the four pulsed Spallation Neutron Sources in the world
- Construction completed in 2018



快循环同步加速器 (RCS)



靶站



Budget and timeline

Budget of R&D & Construction

Table 8.2: Two funding models of the CEPC

	Funding model I (100 M CNY)	Funding model II (100 M CNY)
Central government	250	100
Local government	50	200
International contribution	60	60
Donations	0-35	0-35

Funding model: iteration and interaction with relevant entities, especially Local Governments. (Leading contributor)

International contribution: 20% according to convention.

7.1 Budget for the project design, R&D and construction



CEPC Accelerator TDR

- Consistent TDR high luminosity parameter design as a Higgs factory
- Key components with prototyping, technical feasibility demonstrated, no technical show stopper
- Design and R&D technical documentation (data, drawings, etc.)
- CEPC accelerator TDR document release planned for 2023

CEPC Accelerator EDR Plan; ~Jan. 2023-Dec. 2025 preliminary

- CEPC site study will converge to one or two with feasibility studies (tunnel and infrastructures, environment)
- Engineering design of CEPC accelerator systems and components
- Site dependent civil engineering design implementation preparation
- EDR document completed for government's approval of starting construction in 2026 (the starting of the "15th five year plan")
- There will be more discussions on the planning

Site Selection

CEPC Site Selection
(Red are actively progressing forward)


- 1) Qinhuangdao, Hebei Province
- 2) Huangling, Shanxi Province
- 3) Shenshan, Guangdong Province
- 4) Huzhou, Zhejiang Province
- 5) Chuangchun, Jilin Province
- 6) Changsha, Hunan Province

Multiple candidate sites & strong supports from Local Government

Site Selection



Factors: geology, electricity supply, transportation, international-friendly, local supports ...



July 5, 2021: Changsha Bureau of S&T entrusted Hunan U. to conduct a feasibility study.

Sept 4, 2021: Hunan U. organized a review by a committee of experts from multiple disciplines. The committee evaluated scientific potential of CEPC, feasibility of a new science city based on CEPC, and overall impact on Changsha. The overall conclusion is very positive. The local government is interested and very supportive to the CEPC project.

Cost Benefit performance

- The Higgs boson is probably the most promising portal to the new physics. The CEPC is capable to provide the **Higgs data** in 2030s, which can reveal potential discoveries & knowledges that **are priceless** to mankind. (...)
- The **current CEPC design is optimized**. Taking into account the balance of scientific requirements, technological maturity, and advancement, cost-effectiveness, and other aspects, the CEPC accelerator is designed to have a circumference of 100 kilometers and the compatibility of partial double-ring (Higgs) and double-ring (W/Z).
- Compared to the FCC-ee proposed by CERN, CEPC reaches the similar performance with a much lower cost.
- The CEPC not only perform excellent scientific exploration, but also provide **strong boost to the technologies**, and serves as a highland for global talent training & cooperative innovations. It is of great strategics value with optimized construction and operation cost.
- Because of the excellent scientific program, the CEPC could attract significant **International collaboration**, which further increases its cost-efficient.
- The CEPC project is huge with **lifetime of 40-50 years**, and the city where it is located will build a science city based on the CEPC, attracting thousands, if not tens of thousands, of scientists, engineers, and support personnel to live there, considerably **boosting local economic and technological growth**. Multiple local governments shows strong interests to host CEPC.

Summary

CEPC will address most pressing & critical science problems

- **Science Merit:** The CEPC enables exploration to the most important questions of contemporary particle physics. Though large amount of Higgs, Z, W bosons produced in an extremely clean environment, CEPC can search for new physics in an energy scale higher than HL-LHC and current boundaries by one order of magnitude or more.

CEPC adds enormous strategic values, has many advantages, will be in a leading position if realized

- **Strategical Value & Comparative advantages in International Competition:** The scientific importance and strategical value of CEPC, or in general electron positron Higgs factories are well identified by Global Particle Physics community. Among multiple Higgs factory proposals, the CEPC has strong comparative advantages, and can be the first to deliver data in 2030s.

CEPC design-technologies reaching maturity, great upgrade options offered, plus many added values and benefits

- **Maturity, Upgradability & Added value:** The CEPC performs intensive R&D, pushing multiple critical technologies to the state-of-art level. Its anticipated performances is among the best of future proposals. The CEPC can be upgraded in several highly valuable ways that further strengthen its discovery power, providing high-impact science program spans for decades. The CEPC will bring series of technological innovations, and has strong synergies with scientific research at other disciplines, especially through high energy gamma synchrotron light source.

Summary

Strong-experienced team, IHEP support and international cooperation are there or to be implemented to bring CEPC to fruition

- **Team, Current Support & International Collaboration** The CEPC is well support by the international community, the host lab, and relevant projects. The CEPC study group completes the Design of CEPC accerlerate and detectors, assembled a team of highly professional scientific & engineering staff, and will soon complete the R&D. The CEPC study group is well-positioned to realize and operate this project, and is capable to establish International collaborations to achive its scientific goals.

CEPC schedule follows China's 5-year planning; expects to complete R&D and preparation to build CEPC and carry out the science program

- **Timeline:** We propose to commence the construction of the CEPC during China's 15th Five-year plan (2026 - 2031), and complete, commission, and operate the CEPC during the 16th Five Year plan (2031 - 2036). The maturity of CEPC R&D meets this proposed timeline. Firm connections has been established to the indusrial, facilate the future mass production and construciton of CEPC.

CEPC will position China to be a leading position in particle physics and contribute to the world in a major way

- The CEPC meets the natioanl positioning on basic science, and **will significantly promotes China** in the international community of Paritcle Physics research.