



中国科学院高能物理研究所
Institute of High Energy Physics
Chinese Academy of Sciences

SRF Activities in China

Jiyuan Zhai (IHEP)

14th Workshop of France China Particle Physics Laboratory (FCPPL2023)
SYSU Zhuhai Campus, November 9, 2023


Acknowledgement

- **CAS IHEP:** Prof. Pei Zhang (HEPS and BEPCII-U), Prof. Xiao Li (SAPS), Prof. Rui Ge, Prof. Huachang Liu, Dr. Yun Wang and Dr. Wenzhong Zhou (CSNS-II)
- **CAS IMP** (CiDAS and HIAF): Prof. Yuan He, Prof. Teng Tan
- **CAS SARI** (SSRF & SHINE): Prof. Hongtao Hou, Prof. Jinfang Chen
- **CAS DICP** (DALIS) & **Shenzhen IASF** (S³FEL): Prof. Xilong Wang, Prof. Han Li
- **USTC** (HALF): Prof. Yelong Wei
- **PKU:** Prof. Jiankui Hao, Prof. Fang Wang

Content

1. Introduction
2. SRF accelerator projects, R&D and infrastructures in China
3. Summary

Introduction: SRF Accelerator Research Institutes, Infrastructures, Projects and Industry in China



Teng Tan, TTC2020



SRF Accelerator Projects in China

	Operation	Construction	Design & R&D	Sum
Collider	BEPCII (1.89 GeV, 2 CAV, since 2006)	BEPCII upgrade (2.35 GeV, 4 CAV, complete in 2024)	CEPC (45.5-180 GeV, 288 ~ 980 CAV) ...	2 circular colliders tau-charm, Z, W, Higgs, ttbar
Synchrotron Light Source	BSRF (2.5 GeV, 2 CAV, since 2006) SSRF (3.5 GeV, 3 CAV, since 2009)	HEPS (6 GeV, 10 CAV, complete in 2025) HALF (2.2 GeV, 1 CAV, complete in 2028)	SAPS (3.5 GeV, 4 CAV) ...	5+ light sources 3 rd & 4 th generations 2.2 ~ 6 GeV
FEL	PKU FEL & DC-SRF Gun (30 MeV, 3 CAV) CTFEL (10 MeV, 2 CAV, since 2017)	SHINE (8 GeV, 616 CAV, complete in 2027) S3FEL (2.5 GeV, 224 CAV, complete in 2031) CTFEL upgrade (50 MeV)	DALS (1 GeV, 96 CAV) Pulsed XFEL (15 GeV) ...	7+ FELs 2 hard X-ray 1 soft X-ray 1 EUV, 1 IR, 2 THz
Proton & Heavy Ion	ADS injector I (10 MeV, 14 CAV, since 2016) CAFe (25 MeV, 23 CAV, since 2017)	CiADS (0.5 GeV, 151 CAV, complete in 2025) HIAF (4.25 GeV/u, 96 CAV) CSNS-II (300 MeV, 54 CAV, complete in 2028)	CSNS-III (1 GeV) ADS (1 GeV) Pulsed proton linac (1 GeV) ...	6+ proton & heavy ion SRF accelerators
Sum	Operating 6 facilities ~ 50 cavities	Constructing 9 projects ~ 1200 cavities by 2028 ~ 40 billion CNY	Proposing 6+ projects 2000+ cavities	

Superconducting RF Systems at IHEP

Light Sources & FELs

BSRF, HEPS, CW FEL, ERL



166 MHz (HEPS)

World's first very low freq
 $\beta=1$ module



1.3 GHz (FEL, CEPC, ILC)

World's first mid-T high Q module

HEP Colliders

BEPCII&U, CEPC, ILC



500 MHz (BEPC-II&U, HEPS)

In-house-made, long-term operation
in large scientific facility



650 MHz (CEPC, ADS, CSNS)

World's first 650 MHz cryomodule

High Intensity Proton Linacs

ADS, CSNS-II, ν factory



325 MHz (ADS)


World's first spoke cavity linac



324 MHz (CSNS-II)

China's first double-spoke module

IHEP BEPCII and Upgrade




 北京正负电子对撞机 BEPC

BEPCII SRF System

- BEPCII SRF system stable operation since 2006 with two imported cavities from Japan and in collaboration with KEK, reached design luminosity of $1 \times 10^{33} \text{ cm}^{-2}\text{s}^{-1}$ (910 mA @ 1.89 GeV) in 2016.
- In 2017, east cavity replaced with in-house-made cavity and module, stable operation till now.
- Three imported sub-systems (SRF cavity and module, LLRF, RF power source) have been replaced with in-house-made ones.



In-house-made 500 MHz cavity and module
made in 2011, stable operation since 2017



Digital LLRF system
Stable operation since 2019



200 kW SSA
Operation since Oct. 2023



BEPCL-Upgrade SRF System

Table 1: Main parameters of BEPCL and BEPCL-U.







Parameter	Symbol	BEPCL	BEPCL-U	Unit
Circumference	C	237.53	237.53	m
Beam energy	E_0	1.89	2.35	GeV
Beam current	I_0	910	900	mA
Bunch number	N_b	120	120	-
Total energy loss per turn	U_{tot}	0.116	0.277	MeV
Total power loss to SR	P_{SR}	106	250	kW
Parasitic loss	P_{HOM}	7.7	30	kW
Total beam power	P_b	114	290	kW
Revolution frequency	f_{rev}	1262.1	1262.1	kHz
Synchrotron tune	ν_s	0.03	0.04	-
Bunch length	σ_z	14	12	mm
Momentum compaction factor	α_p	0.018	0.017	-
RF frequency	f_{rf}	499.8	499.8	MHz
Total RF voltage	V_{rf}	1.6	3.3	MV
Radiation damping time (x)	τ_x	24.2	12.6	ms
Radiation damping time (y)	τ_y	25.8	13.4	ms
Radiation damping time (z)	τ_z	13.4	6.9	ms
β function at straight section	β_x	15	20	m
β function at straight section	β_y	15	20	m

Table 3: RF parameters for BEPCL-U (breakdown).

Parameter	Existing	To be added	Unit
RF frequency	499.8	499.8	MHz
Number of cavities	2(+1)	1	-
RF voltage per cavity (V_c^{op})	1.65	1.75	MV
Cavity unloaded Q at V_c^{op}	$\geq 5e8$	$\geq 1e9$	-
Operating temperature	4.2	4.2	K
Nominal RF power per cavity	145	145	kW
Loaded Q	$2e5$	$2e5$	-
Cavity loaded bandwidth	2.5	2.5	kHz
Number of RF stations	2	2	-
Number of transmitters	2	2	-
Transmitter type	Klystron	SSA	-
Nominal power per transmitter	250	200	kW
Min. output power per transmitter (including 15% transmission loss)	165	165	kW
FPC designed power (CW)	200	200	kW
Number of LLRF	2	4	-
Specified amplitude noise (pk-pk)	± 1	± 0.5	%
Specified phase noise (pk-pk)	± 1	± 0.5	$^\circ$

BEPCII-Upgrade SRF System

- BEPCII-U: Add two cavities and SSAs in 2024.
- Further R&D in 500 MHz cavity, LLRF and SSA.



(a) West RF hall (BEPCII)

(b) West RF hall (BEPCII-U)

(c) East RF hall (BEPCII)

(d) East RF hall (BEPCII-U)

BEPCII-U and HEPS 500 MHz Cavity and Cryomodule

- One 500 MHz cavities for BEPCII-U and two 500 MHz third harmonic cavities for HEPS.
- Prevent cavity buckling by thicker Nb sheet (2.5 mm to 3.7 mm), deep drawing instead of spinning, adding stiffening rings.
- First CM assembly complete soon.







TABLE V
BUCKLING PERFORMANCE OF THE CAVITY UNDER TWO DIFFERENT BOUNDARIES


	Conditions	Φ	Φ	Φ_{cr}
		(Bare)	(Stiff.)	
Cell (LBP side)	BPs fixed	29.3	83.7	16.1
	LBP LF	10.5	30.2	
Cell (SBP side)	BPs fixed	29.4	85.1	16.1
	LBP LF	12.8	36.9	
LBP tube	BPs fixed	33.2	33.2	2.5
	LBP LF	17.2	31.0	

“BPs fixed” stands for both beam pipes are fixed, “LBP LF” stands for the cavity LBP side is free to move longitudinally while the SBP side is fixed, “Bare” stands for bare cavity without any stiffening rings, and “Stiff.” stands for cavities with one pair of stiffening rings added on the cell.





500 MHz KEKB-type single-cell SC cavity module

IHEP CEPC



IHEP CEPC


- 100 km circular collider, Higgs (Z / W / ttbar) factory, in China. Run at $\sqrt{s} \sim 90, 160, 240, 360$ GeV. Possible pp collider (SppC) of $\sqrt{s} \sim 50 - 100$ TeV in the far future.
- CEPC CDR published in 2018, TDR will publish in late 2023. Will propose to the government to begin construction around 2028 during the 15th 5-year-plan period.
- CEPC SRF system has unprecedented challenges in high RF voltage (20 GV) , high current (1.4 A), high power (100 MW RF power, Z-pole 1 MW per cavity) , high HOM power and beam-cavity interaction issues, with requirement of mode switching. State-of-the-art technology in high gradient, high Q and high power.






CEPC 650 MHz SRF System R&D



650 MHz test cryomodule with 2x2-cell cavities. Beam test soon.



High G High Q 650 MHz 1-cell Cavity
 EP treated: **2.3E10@41.6 MV/m@2 K**
 Mid-T treated: **6.3E10@31 MV/m@2 K**



IHEP 1.3 GHz SRF R&D

2003-2015

Early research
Technology R&D




1-cell and 9-cell cavities

ILC test cryomodule

Important collaboration
with PKU, KEK, INFN-
LASA, FNAL, JLAB,
DESY ...

2016-2020

Technology transfer
Performance breakthrough



HERT 11 TESLA 9-cell cavities

EP 36 MV/m (reach ILC spec)

Mid-T 5E10@21 MV/m (world record)

4 BCP + 4 mid-T high Q cavities
delivered to SHINE

2021-2025

Cavity mass production
Cryomodule prototyping

SHINE

88 9-cell cavities
by HERT



DALS 1.3 GHz high Q cryomodule

2026-2035

Cavity and cryomodule
mass production

Engage in these projects:

SHINE (600 CAV, 75 CM)

S³FEL (208 CAV, 26 CM)

Other CW FELs



CEPC booster (352 cavities)

ILC (8000+8000 cavities)

...

**High Q high gradient and new
material R&D**

IHEP 1.3 GHz SRF R&D




IOP Publishing
Superconductor Science and Technology
Supercond. Sci. Technol. 34 (2021) 095005 (7pp)
<https://doi.org/10.1088/1361-6668/ac1657>

Medium-temperature furnace baking of 1.3 GHz 9-cell superconducting cavities at IHEP

Feisi He^{1,2,3,4}, Weimin Pan^{1,2,3,4,*}, Peng Sha^{1,2,3,4,*}, Jiyuan Zhai^{1,2,3,4}, Zhenghui Mi^{1,2,3,4}, Xuwen Dai^{1,3}, Song Jin^{1,2,3,4}, Zhanjun Zhang^{1,3}, Chao Dong^{1,2,3}, Baiqi Liu^{1,2,3}, Hui Zhao^{1,3}, Rui Ge^{1,2,3,4}, Jianbing Zhao^{1,3}, Zhihui Mu^{1,3}, Lei Du^{1,2,3}, Liangrui Sun^{1,2,3}, Liang Zhang^{1,3}, Conglai Yang^{1,3} and Xiaobing Zheng^{1,3}

¹ Institute of High Energy Physics, Chinese Academy of Sciences, Beijing 100049, People's Republic of China
² Key Laboratory of Particle Acceleration Physics & Technology, Institute of High Energy Physics, Chinese Academy of Sciences, Beijing 100049, People's Republic of China
³ Center for Superconducting RF and Cryogenics, Institute of High Energy Physics, Chinese Academy of Sciences, Beijing 100049, People's Republic of China
⁴ University of Chinese Academy of Sciences, Beijing 100049, People's Republic of China




World's first Mid-T 1.3 GHz Cryomodule with Record High Q_0



IHEP 1.3 GHz SRF team with Acceptance Test Review Committee members and DALSS/S3FEL colleagues.

World's first Mid-T 1.3 GHz Cryomodule with Record High Q_0



Module RF voltage > 191 MV
Avg. Q_0 @ 16 MV/m: 3.8×10^{10}
Avg. Q_0 @ 21 MV/m: 3.6×10^{10}


Parameters	IHEP Mid-T CM	LCLS-II (SHINE, S ³ FEL) Spec	LCLS-II-HE Spec	CEPC Booster Higgs mode Spec
Avg. usable CW E_{acc}	> 23 MV/m	2.7×10^{10} @ 16 MV/m	$2.7E10$ @ 20.8 MV/m	3.0×10^{10} @ 21.8 MV/m
Avg. Q_0 @ 21 MV/m	3.6×10^{10}			

IHEP 1.3 GHz SRF team with Acceptance Test Review Committee members and DALIS/S3FEL colleagues.




IHEP HEPS



HEPS RF System






Parameter	Value	Unit
Beam energy	6	GeV
Circumference	1360.4	m
Beam current	200	mA
Lattice type	7BA	-
Number of sectors	48	-
Natural emittance	34.2	pm·rad
Natural bunch length	5.06	mm
Energy loss (bare lattice)	2.64	MeV
Total no. of IDs (Phase I)	14	-
Total beam power	850	kW
Radiation damping time (x/y/z)	10.85/20.62/18.76	ms
RF frequency (main, 3 rd harm.)	166.6, 499.8	MHz
Main RF voltage (w/ harm. cav.)	5.16	MV






Parameter	Value	Unit
Circumference	1360.4	m
RF frequency (f_0)	166.6	MHz
Total energy loss per turn (U_0)	4.14	MeV
Total beam power (P_b)	850	kW
Total RF voltage (V_{RF})	5.16	MV
Number of main RF cavities	5	-
RF power per main cavity	170	kW
Cavity type	SRF cavity	-
HOM control	Heavy damping	-
Harmonic RF frequency (f_{HC})	499.8	MHz
Number of RF stations	5 + 2	-
Transmitter power per RF station	260	kW
Field noise (pk-pk)	$\pm 0.1\%$, $\pm 0.1^\circ$	-

IHEP HEPS 166 MHz Cavity and Cryomodule



- Low frequency: 166.6 MHz, $\beta=1$
- High RF power: 180 kW per cavity
- High current: 200 mA \rightarrow heavy HOM damping: $Q_L < 1000$
- Compactness: limited space of the straight section (6 m for 2 cavs)
- Stable operation (user facility): large margin in RF parameters



IHEP HEPS 166 MHz Cavity and Cryomodule



IHEP ADS Injector SRF System



14 spoke012 cavities accelerate 2 mA CW proton beam to 10 MeV in Injector-I at IHEP.

6 spoke021 cavities increase CW proton beam to 25 MeV in Injector-II at IMP.

ADS Injector SRF System

- Batch production of Spoke012 and Spoke021, meet spec
- SSR024/040, HWR325, MB082 prototypes



Spoke012 cavity string



650 MHz 5-cell cavity (beta 0.82)





325 MHz Spoke cavity (beta 0.21)



325 MHz Spoke cavity (beta 0.40)




325 MHz HWR cavity (beta 0.14)







IHEP CSNS





 中国散裂中子源
China Spallation Neutron Source

CSNS-II and Future Plan




Beam parameters	I	II
Beam Power on target [kW]	100	500
Proton energy [GeV]	1.6	1.6
Average beam current [μA]	62.5	312.5
Pulse repetition rate [Hz]	25	25
Linac energy [MeV]	80	300
Macropulse. ave current [mA]	15	40
Linac RF frequency (MHz)	324	324/648
Linac beam width(μs)	400	600

CSNS-II SRF System





- **CSNS-II upgrade (2023-2028)**
 - Linac energy: 80 MeV → 300 MeV
 - Linac beam current: 15 mA → 40 mA
 - Linac beam pulse length: 400 μs → 600 μs
- **20 324 MHz $\beta=0.5$ double-spoke cavities**
 - Prototype cavities meet design spec
 - Prototype cryomodule under assembly at PAPS
- **24 648 MHz $\beta=0.62$ 6-cell cavities**
 - Prototype cavity in fabrication, module in design




Parameter	Value
f (MHz)	324
TTF	0.79
β_0	0.5
Eacc (MV/m)	7.3 (9)
Ep/Eacc	3.44
Bp/Eacc mT/(MV/m)	8.86
R/Q (Ω)	401.8
G (Ω)	118.6

Parameter	Value
f (MHz)	648
TTF@ β_g	0.7
β_g	0.62
Eacc (MV/m)	14
Ep/Eacc	2.53
Bp/Eacc mT/(MV/m)	5.45
R/Q (Ω)	309
G (Ω)	177
Beam tube diameter (mm)	105/120
Cell-cell coupling (%)	1.35

CSNS-II Double-Spoke Cavities



CSNS-II Double-Spoke Module Prototype Assembly



IHEP SAPS

- **Southern Advanced Photon Source (SAPS)**

- SAPS, a mid-energy fourth generation storage ring photon source, is planned to be built adjacent to the China Spallation Neutron Source (CSNS)
- Modified H-7BA magnetic focusing structure
- 350 mA high brightness mode
- 500 mA high-throughput mode



Parameters	Value	Unit
Beam energy E_0	3.5	GeV
Current	500	mA
Circumference	810	m
Nature emittance	26.3	pm·rad
Cell number	32	-
Long straight section	6	m


IHEP SAPS RF System

- **RF system**


- 500 MHz/5-cell Normal conducting cavities for booster RF
- Superconducting cavities for storage ring RF
- 166.6 MHz SC cavity + 499.8 MHz SC cavity

Parameters of the storage-ring rf system for SAPS

Parameter	Fundamental RF	HHC	Unit
RF frequency	166.6	499.8	MHz
Total energy loss (w/ IDs)	1.55	-	MeV
Total power loss to radiation	800	-	kW
Total RF voltage	2	0.36	MV
Number of cavities	4	1	-
Cavity type	SCC	SCC (active)	-
RF voltage per cavity	>0.5	>0.36	MV
Max. power per cavity	200	120	kW
Nominal transmitter power per RF station	260	150	kW



166.6 MHz SC cavity



499.8 MHz SC cavity

[1] P. Zhang et al., Radio-frequency system of the high energy photon source, Radiation Detection Technology and Methods (2023) 7:159–170.



IHEP High Power Input Couplers and HOM Damper

Input power: BEPC 100 kW, HEPS 200 kW, CEPC Higgs 300 kW, CEPC Z-pole 500 kW (1 MW)

500MHz-CW 420kW 166.6MHz-CW 200kW 650MHz-CW 300kW 1.3GHz-CW,70kW




1.3GHz-Pulse 1MW



162.5MHZ-CW,20kW



325MHZ-CW,25kW






650MHZ-CW,150kW




162.5MHZ-CW,80kW



325MHZ-CW,100kW




IHEP BEPCII LLRF



(a) Analog LLRF (since 2005)



(b) Digital LLRF (2017)




(c) Digital LLRF (2019)





(d) Digital LLRF (2021)



IHEP HEPS LLRF



1st-gen LLRF
(166.6 MHz cavity horizontal test,
 $V_c = 1.2$ MV, 4.2 K)








2nd-gen LLRF
(lab test, self closed-loop)



3rd-gen LLRF
(lab test, self closed-loop)

IHEP Thin Film Cavity R&D (Nb/Cu sputtering, Nb₃Sn, Iron-based)



IHEP PAPS SRF Infrastructure in Huairou, Beijing




Beam test hall

- Magnet R&D
- Mechanical & alignment
- Klystron Test

- SRF test hall
- Vacuum assembly & coating

Cryogenic System



SRF facility



Magnet and Undulator



Vacuum

Accelerator key technology R&D and Testing platform:

- SRF cavity and module
- High precision magnet
- Vacuum assembly & coating
- High efficiency Klystron
- Mechanics and alignment
- Beam test facility



Beam test



Alignment






Klystron R&D

IHEP PAPS SRF Infrastructure Fully Operational

二层, ~ 500m²
Second floor


一层, 78.6m x 49.8m, ~ 4000m²
First floor

30 吨天车
30t crane



IHEP Cavity Electro-Polishing System at OTIC Ningxia


China's first 9-cell cavity EP system, key tool for high gradient and high Q cavity.



IHEP PAPS SRF Infrastructure Operation Status

Facilities (capability per year)	Devices	Tests since 2021	Related Projects
VT stand (400 cavities)	166 MHz / 325 MHz / 500 MHz / 650 MHz / 1.3 GHz CAV	~ 160	HEPS/BEPCII-U/CEPC/CSNS-II/SHINE/DALS/HALF/(CiADS)
HT stand (20 modules, including assembly)	1.3 GHz CAV	~ 20	CEPC/SHINE/DALS/HEPS/(BEPCII-U/CSNS-II)
High power test stand (200 couplers)	Coupler / Circulator / RF load / Copper cavity	~ 20	HEPS/SHINE/DALS/CSNS-II/(HALF)
Clean assembly and HPR	166MHz / 325MHz / 500MHz / 650MHz / 1.3 GHz CAV	~ 160	HEPS/CEPC/CSNS-II/SHINE/DALS/BEPCII-U/(HALF)
Vacuum furnace	650 MHz / 1.3 GHz CAV	~ 50	CEPC/CSNS-II/SHINE/DALS

IHEP Dongguan SRF Infrastructure



IMP HIAF and CiADS



IMP HIAF and CiADS




- **HIAF:** High Intensity heavy ion Accelerator Facility
- **CiADS:** China Initiative Accelerator Driven System
- Being built by IMP in Huizhou of Guangdong Prov.
- Two large-scale scientific infrastructure facilities approved by China Government hosted by IMP

- **HIAF:** Nuclear physics research
- **Total budget:** 2.8 B CNY ¥ (424 M USD \$)
- **Schedule:** 2018-2025
- Construction started officially Dec. 2018



- **CiADS:** Nuclear waste transmutation
- **Total budget:** 4.0 B CNY ¥ (606 M USD \$)
- **Schedule:** 2021-2027
- Construction started officially July. 2021



IMP HIAF SRF Cavities



from p to $^{238}\text{U}^{35+}$





81.25 MHz QWR007
(30 in 6 CMs)

162.5 MHz HWR015
(66 in 11 CMs)

IMP CiADS SRF Cavities

CiADS Linac Design




Sections	Frequency(MHz)	beta	Cryomodules	Cavities	Solenoids
HWR010	162.5	0.1	1	9	9
HWR019	162.5	0.19	4	24	24
HWR040	325	0.4	10	60	20
Ellipt062	650	0.62	10	30	0
Ellipt082	650	0.82	7	28	0
Totals			32	151	53



HWR010

HWR040



Ellip-062


Particle	proton	
Energy	500	MeV
current	5/10	mA
Beam power	2.5	MW
RF freq	162.5/325/650	MHz
Epeak	26/28/29/29/29	MV/m
Num of CM	32	-
Num of cavity	151	-

The strongest *p* machine for spent fuel processing and other nuclear technologies.


Featured with Cu/Nb technology.

IMP Cu/Nb Casting and Coating Cavities


- Batch production of Cu/Nb cavities of HWR type.
- First all-Cu/Nb-cavity cold mass was successfully assembled and will be installed in CiADS linac.
- Performance is improving with verified high-stability



IMP Nb₃Sn Cavity and LHe-Free Linac



- Systematic study about Nb₃Sn thin film growth mechanism and cavity optimization.
- Maximum E_{acc} reaches 18 MV/m



Applied Surface Science 643 (2024) 158708

Contents lists available at ScienceDirect

Applied Surface Science

journal homepage: www.elsevier.com/locate/apsusc

ELSEVIER

Full Length Article


Understanding and optimization of the coating process of the radio-frequency Nb₃Sn thin film superconducting cavities using tin vapor diffusion method

Guangze Jiang^{a,b,#}, Shuai Wu^{a,b,#}, Ziqin Yang^{a,b,d,*}, Yuan He^{a,b,*}, Yang Ye^{a,b}, Hao Guo^{a,c}, Chunlong Li^a, Pingran Xiong^a, Lu Li^a, Shichun Huang^{a,b}, Andong Wu^{a,b}, Feng Qiu^{a,b}, Junhui Zhang^{a,b}, Xiaofei Niu^{a,b}, Qinggang Huang^a, Zhi Qin^{a,b}, Teng Tan^{a,b}, Zhijun Wang^{a,b}, Shenghu Zhang^a, Hongwei Zhao^{a,b}, Wenlong Zhan^{a,b}

^a Institute of Modern Physics, Chinese Academy of Sciences, Lanzhou 730000, China
^b School of Nuclear Science and Technology, University of Chinese Academy of Sciences, Beijing 100049, China
^c School of Nuclear Science and Technology, Lanzhou University, Lanzhou 730000, China
^d Advanced Energy Science and Technology Guangdong Laboratory, Huizhou 516007, China

<https://doi.org/10.1016/j.apsusc.2023.158708>

IMP Nb₃Sn Cavity and LHe-Free Linac








- The first cryocooler-driven SRF e-machine for various industrial applications will be commissioned in this Dec.
- One optimized Nb₃Sn cavity with 10 cryocoolers produce 5 MeV 10 mA e-beam, suitable for clean-water project, e-beam manufacturing, etc.



IMP Reactive Plasma Cleaning

- Reaction mechanism between reactive oxygen plasma and hydrocarbon was studied.
- Test platform and commercialized machine were developed for plasma cleaning technique.





Shanghai SARI SSRF



Spare 500 MHz Cryomodule for SSRF


One 500 MHz cryomodule has been horizontal tested successfully in April 2021:

- New design: fluted beam pipe and coaxial input coupler are combined
- $Q_0=1.0e9$ @ 1.5 MV and $Q_0 = 7.7e8$ @ 2.1 MV;
- Helium pressure stability $< +/- 1.5$ mbar and helium level stability $< +/- 1.0\%$
- Input coupling is adjustable: $(1.5 +/- 0.3)e5$



SARI Superconducting Harmonic Cryomodule for SSRF


- **Function:** bunch size lengthen, improve beam quality and lifetime, increase single bunch beam current threshold.....
- **Key components:** In-house developed, including Nb Cavity, cryostat, HOM absorber, Tuner, Monitor & Interlock controller, Digital LLRF controller
- **Operation** with 200 mA top-up beam: lengthen factor is 2.24 at four bunch train filling pattern, 2.98 at hybrid filling pattern with current in single bunch is higher than 24 mA. Lifetime increased factor is about 2.



3HC cryomodule in tunnel



Monitor & Interlock and LLRF




Beam Operation

Shanghai SARI SHINE

SHINE: Shanghai High repetition rate XFEL and Extreme light facility (600 9-cell cavities, 75 modules)



■ Launched in April 2017, groundbreaking in April 2018, aiming at the first lasing in 2025.



- 8 GeV SRF linac, total length: 3110 m -29.0 m underground
- 3 undulator lines, photons from 0.4-25 keV
- 3 X-ray beamlines, delivering up to 1MHz photon pulse
- 10 experimental stations
- A 100 PW laser facility

Superconducting Cryomodule for SHINE


- **Key components:** Nb Cavity, high power coupler, cryostat, HOM absorber, Tuner, BPM,
 - Both N-doping and midT-baking recipes **reached SHINE specs: $Q_0 > 2.7 \times 10^{10}$ @ 16 MV/m, $E_{acc_max} > 19$ MV/m, FE free**
- **Infrastructure:** Wuxi SRF Cavity post-processing platform (BCP, EP, Pre-tuning, HPR, Furnace, Cleanroom); Cryomodule HT & Cavity VT platform at Shanghai (Cleanroom, Assembly, Vertical test, Horizontal test)
- **Research:** high-Q & G study; high average coupler; cold BPM; tuner; Solid-State Power Source; Digital LLRF...




Status of small-batch high-Q cavities

- International cavities (RI and ZANON): N-doping, 3/60 recipe applied
- Domestic cavities (~half half): N-doping and mid-T baking
- So far, **two production lines have been qualified** by small batch cavities: One international and one domestic.
- Cavities of the other two lines are underway (surface treatment and waiting for VT)

All the 8 N-doped dressed cavities (Line 1)



All the mid-T baked bare cavities tested so far (Line 2, domestic)




Shanghai SARI SHINE

Infrastructure for CM assembly and test


S. Sun

- Two 3000 m² for CM Assembly and Test Halls (ATH1 & ATH2)
- Commissioning and gradually put into operation since 2021
- 3 rounds of standard CM assembled and tested



Infrastructure for cavity surface treatment


- **Cavity surface-treatment platform** (co-built): SHINE facilities at Wuxi Creative
- **Goal: R&D and mass production** for cavity surface-treatment
- **Design:** Dealing with all the procedures after cavity fabrication, and before vertical test
- **Status:** Commissioning and gradually put into operation since 2021, undertaking the **surface-treatment of SHINE cavities from domestic companies**



Test Stands for cavities and CMs

S.J. Zhao

- ◆ 4 vertical test stands and 4 horizontal test stands are designed in the two halls
- ◆ In ATH1(Assembly and Test Hall), 2 vertical test stands and 2 horizontal test stands, have been constructed and **put into operation**;
- ◆ The test stands in ATH2 are expected to be completed this year;
- ◆ The Cryo distribution will be optimized to allow more effective operation of multi-stands;
- ◆ The mass flow meters will be equipped to make the Q_0 test easier than the delta liquid level method used now.




Shenzhen IASF S³FEL

Worldwide FELs

Facility	Wavelength	Country	LINAC	Beam energy /GeV	Photon energy	Rep. rate/Hz	Status
FLASH	Soft X-ray	DE	SRF	1.25	14 - 300 eV	5000	operation
European XFEL	Hard X-ray	EU	SRF	17.5	8.4 - 30 keV	27,000	operation
LCLS-II	Hard X-ray	US	SRF	4	0.2 - 5 keV	1,000,000	commissioning
SHINE	Hard X-ray	CN	SRF	8	0.4 - 25 keV	1,000,000	Under construction
S ³ FEL	Soft X-ray	CN	SRF	2.5	0.04 - 1 keV	1,000,000	Approved

Shenzhen IASF S³FEL



Location and Layout



Shenzhen IASF S³FEL

LINAC design

Function: accelerate the electron beam, compress the beam length and increase the peak current intensity



1.3 GHz cryomodule:
26 sets, energy acceleration



3.9 GHz cryomodule:
2 sets, linear compression compensation

Parameter	Design	Range	Unit
energy	2.5	1.0-2.5	GeV
charge	100	10-300	pC
bunch length (rms)	50	10-100	fs
current	800	200-1000	A
emittance	0.5	0.2-1.0	mm·mrad
energy spread	400	250-500	keV
rep. rate	1	0-1	MHz

Shenzhen IASF S³FEL


SRF Module Test Facility (SMTF)

- 2 × Vertical Test Cryostats (VTC)
- 3 × Cryomodule Test Benches (CMTB)
- 1 × Magnet test bench
- 1 × Clean room infrastructure
- 1 × Multipurpose cryo-test Facility
- Cryomodule assembly and integration bench
- Dedicated RF test bench



Shenzhen IASF S³FEL


S³FEL Project Schedule



Dalian DICP DALS

DALS Project overview

Dalian advanced light source layout




Parameter	design
beam energy/ GeV	1
charge/ pC	100
emittance/ mm-mrad	0.5
rep. rate/ MHz	1

CM type	Frequency [GHz]	Number of Cavities	Number of CM
9-cell cavity CM	1.3	80	10
9-cell cavity CM	3.9	16	2

Dalian DICP DALS

Current situation of injector test facility for DALS



Parameter	design
Beam energy/ MeV	90
Charge/ pC	100
Emittance/ mm-mrad	0.5-1.5
Rep. rate/ MHz	0.1-1
RMS pulse length/ps	4
Cooling capacity@ 2 K/W	370

Dalian DICP DALS

1.3 GHz prototype CM development collaborate with HIPE



Cooperation with IHEP



- IHEP made a 1.3 GHz cryomodule with 8 mid-T (medium-temperature furnace baking) 9-cell cavities for our project.
- Average usable gradient and Q_0 exceeds CW FEL projects and CEPC specs, and demonstrates excellent performance of mid-T cavities in a cryomodule for the first time.

Parameters	IHEP Mid-T CM	LCLS-II (SHINE, S ³ FEL, DALS) Spec	LCLS-II-HE Spec	CEPC Booster Higgs mode Spec
Avg. usable CW E_{acc} (MV/m)	> 22	2.7×10^{10} @ 16 MV/m	2.7E10 @ 20.8 MV/m	3.0×10^{10} @ 21.8 MV/m
Avg. Q_0 @ 16 & 21 MV/m	3.6×10^{10}			




Current situation of SMTF for DALS

- 1 × Vertical Test Cryostats(VTC)
- 1 × Cryomodule Test Benche (CMTB)
- 1 × Clean room infrastructure
- Cryomodule assembly and integration bench




PKU SRF Linac



DC-SRF-II gun and beam line

1.3 The 2 × 9-cell cryomodule

It can accelerate the electron beam to 10 ~ 30 MeV



Huang S L, Liu K X, Zhao K, et al. DC-SRF photocathode gun (in Chinese). Chin Sci Bull, 2023, 68: 1036–1046




PKU Large grain cavities

Large grain 9-cell cavities for XFEL

- 6 large grain 9-cell cavities were fabricated by PKU/OSTEC
- BCP 180 μ m + 800 $^{\circ}$ C 3h + BCP 30 μ m
- Eacc > 25 MV/m
- $Q_0 \sim 1.6-2.4E10$ @ 16 MV/m @ 2.0 K




Q vs E of PKU 9-cell cavities (2.0 K)




PKU High Q: N-doping

Light doping



Treatment	Q ₀ (2K,16MV/m)	E _{acc} (MV/m)
Baseline(BCP200+800C+EP6)	2.0e10	26.3
BCP30+N2/A6+ EP5	3.2e10	19.8
+ EP2(totally EP7)	4.1e10	20.0
+ EP2(totally EP9)	3.6e10	20.7

Medium doping




- BCP 200 μm + EP 50 μm + 900°C
3 h

Treatment	Q ₀ (2K,16MV/m)	E _{acc} (MV/m)
NMFG02, EP5	2.5e10	20.7
NMFG03, EP10	4.2e10	18.9
NMFG04, EP15	4.4e10	21.8


PKU High Q: N-infusion

1.3 GHz 1-cell cavities



Q improvement: 165°C > 150 °C > 180 °C

650 MHz 2-cell CEPC cavity N-infusion, 165°C




Baseline, BCP200+800C+BCP30

$$Q_0 \sim 3.8 \times 10^{10} \text{ (2.0 K, 20 MV/m)}$$

BCP30+N-infusion

$$Q_0 \sim 6.7 \times 10^{10} \text{ (2.0 K, 20 MV/m)}$$

162.5 MHz HWR N-infusion, 160°C



Before infusion

$$Q_0 \sim 7.9 \times 10^9 \text{ (2.0K, 10 MV/m)}$$

$$1.3 \times 10^9 \text{ (4.2K, 10 MV/m)}$$


After infusion

$$Q_0 \sim 1.4 \times 10^{10} \text{ (2.0 K, 10 MV/m)}$$

$$1.6 \times 10^9 \text{ (4.2 K, 10 MV/m)}$$


PKU High Q: Medium temperature baking

1-cell cavities




800°C3h+AirExposure48h+300°C
3h
 Q_0 : 2.8-3.4E10@16MV/m

9-cell cavities



- 800°C 3 h
- Air Exposure 48 h
- 450 °C 3 h
- $Q_0 \sim 2.7 \times 10^{10}$ @ 16 MV /m





9-cell cavities (EP)



- Q_0 @ 16 MV/m
- $\sim 2.7 \times 10^{10}$ (BCP)
- $\sim 2.3 \times 10^{10}$ (EP)



PKU Nb₃Sn cavities and conduction cooling accelerator

Tin vapor diffusion for Nb₃Sn coating



$Q_0 \sim 4.8 \times 10^9$ @4.2K @ low field
max. $E_{acc} \sim 17.3 \text{ MV/m}$

Conduction cooling for Nb₃Sn cavity




- CW running of Nb₃Sn cavity with conduction cooling

$$Q_0 = 6.7 \times 10^8$$


$$@ E_{acc, max} = 1.75 \text{ MV/m}$$

- Cavity heat loss: 0.58W
- Ave. T of cavity ~ 7K

Hefei USTC HALF




Hefei Advanced Light Facility (HALF)
4th generation synchrotron radiation source



~366 million Euros
2023.09-2028.12

参数	储存环要求	验收指标
能量 [GeV]	2.2	2.2
电荷量 [pC]	300	300
束流几何发射度 [nm·rad]	12	12
能量分散 (rms)	≤0.2%	≤0.2%
能量稳定性 (rms)	≤0.1%	≤0.1%
注入点位置偏差 (rms) (dx, dy)	0.1 mm	---
注入点角度偏差 (rms) (dx _p , dy _p)	0.1 mrad	---




Hefei USTC HALF

499.8 MHz SRF cryomodule (in collaboration with IHEP)

- ① SRF cavity ($V_a = 1.5 \text{ MV}$)
- ② Solid-state RF transmitter
- ③ HOM absorbers
- ④ High-power input coupler ($P_{in} = 140 \text{ kW}$)





SRF cavity





Vertical tests show that $Q_0 \geq 1 \times 10^9$ for an accelerating voltage = **3.84 MV**

High-power input coupler



High-power input coupler has been cold-tested and waiting for high-power tests.

HOM absorbers



HOM absorbers has been fabricated and cold-tested.

Solid-state RF transmitter






500 MHz / 250 kW solid-state RF transmitter has been manufactured and successfully tested.




Hefei USTC HALF

1499.4 MHz SRF cryomodule (in collaboration with SARI)

- ① SRF cavity ($V_a = 0.5 \text{ MV}$)
- ② SiC HOM Absorbers



Parameters	Value
Mechanical tuning range	[-200 +500] kHz
Mechanical tuning sensitivity	3.153 MHz/mm
Mechanical tuning accuracy	20 Hz
Piezo tuning range	20 kHz
Piezo tuning accuracy	10 Hz



Summary

- 20 years blooming SRF R&D at IHEP and in China. We are in a golden era of large SRF accelerator facilities design and construction in China (2010-2035).
- Many challenges in the design, development, construction and operation of SRF systems for the colliders, light sources & FELs and proton linacs, as well as SRF application in industry.
- Domestic and international communications, exchanges and collaborations are always very important and will benefit to all.



矢志创新铸国之重器 攻坚克难谱时代华章

立足国内 放眼世界 坚持

系“国家事”

Merci

高品质因数1.3 GHz超导加速模组取得世界领先成果

