

Progress in mechanical design of CEPC detector TDR

Ji Quan

June 27, 2024

Content:

1. Overall layout and Size distribution
2. Installation and Connection Concept design
of Sub detectors
3. Summary


1. Overall layout and Size distribution

Overall layout



ACC MDI Component


Others are detector components



1. Overall layout and Size distribution



Overall layout

Total weight :
 $\approx 6000 \text{ t}$



1. Overall layout and Size distribution

Size distribution --- Detector boundary



1. Overall layout and Size distribution

Size distribution --- MDI boundary

consists of 4 segments of channels:

Detection angle : 8.1° ($\arccos 0.99$)


(Before ECAL)

(After ECAL)

ECAL : 700 mm


HCAL : 800 mm

Yoke : $\varnothing 1300$ mm




8.1°

$\varnothing 1300$



1. Overall layout and Size distribution

Size distribution --- Gap between sub detectors



Example for GAP between the Yoke and Magnet

Minimum gap principle:

Designed installation gap: 10mm
Factors: Guide rail accuracy
Collimation accuracy


Dimensional tolerance: (example)
Barrel yoke : 4245 Tolerance: +5
0
Magnet: R4235 Tolerance: -5

Actual installation gap:
10~20 mm


2. Installation and Connection Concept of Sub detectors

Installation sequence:

1. Install **the barrel sub-detector** first, in the following order:
Yoke, Magnet, HCAL, ECAL, TPC+OTK, ITK, Beampipe(Vertex)
2. Then install **the end sub-detector**, in the following order:
ECAL+OTK, HACL
3. Then install the **ACC component**
4. End-Cap Yoke



2.Installation and Connection Concept of Sub detectors



Step 1:
Install Yoke iron

Realized the installation design
of zero-assist Tools



(说明：没有探测器及超导以及电子学等干扰情况下的机械设计)

Total weight :
 $\approx 3900+700(\text{base}) \text{ t}$


洛矿的工程设计图
(3月8日-6月6日)

2. Installation and Connection Concept of Sub detectors

Collaboration with 洛矿 will be the best choice for the High Energy Institute




2. Installation and Connection Concept of Sub detectors



Installation:
Mandrel method

2. Installation and Connection Concept of Sub detectors




Connection design:
Principle of proximity

Barrel Yoke : Fixed on the base
Magnet : Fixed on the Barrel Yoke
Barrel HCAL : Fixed on the Barrel Yoke
Barrel ECAL : Fixed on the Barrel HCAL
TPC+OTK : Fixed on the Barrel ECAL
ITK(ST) : Fixed on the TPC
Beampipe(Vertex) : Fixed on the ITK
End-cap ECAL+OTK : Fixed on the Barrel HCAL
End-cap HCAL : Fixed on the Barrel HCAL
(Auxiliary cylinder)

Auxiliary cylinder



Step 2: Installation and connection of magnet



Connection :
Fixed on the Yoke

Weight :
≈ 265 t


Connection of the magnet: (裴亚田)





Step 3: Installation and connection of Barrel HCAL

Install the Barrel HCAL :

Auxiliary cylinder



A: Static Structural
Total Deformation
类型: 总变形
单位: mm
时间: 1
2024/4/29 16:15




Thickness of cylinder:
60 mm

Max deformation:
~ 0.25


Weight :
≈ 1000 t

Step 3: Installation and connection of Barrel HCAL


Connection of the barrel HCAL:



Cable channel





Connection flange



Connection:
Fixed on the Yoke
by connection flange

Step 4: Installation and connection of [Barrel ECAL](#)


Install the Barrel ECAL :




Connection:

[Fixed on the Barrel HCAL](#)

Step 5: Installation and connection of TPC(OTK)





Connection:
Fixed on the Barrel ECAL




Weight :
 $\approx 1.2 \text{ t}$

Step 6: Installation and connection of ITK



Connection:
Fixed on the TPC

Step 7: Installation and connection of Beampipe(Vertex)




Connection :
[Fixed on the ITK](#)



Weight :
 $\approx 10 \text{ kg}$

Step 7: Installation and connection of Beampipe(Vertex)

2023年7月, ST的安装模拟图:




Step 8: Installation and connection of End ECAL(OTK)




Connection:
Fixed on the Barrel HCAL

Step 9: Installation and connection of End HCAL




Weight :
 $\approx 380 \times 2$ t

Connection :
Fixed on the auxiliary cylinder




Step 10 : Installation and connection of ACC Component

ACC Component 与 Beampipe 的连接：
Pillow Seal



Pillow Seal密封原理：
表面粗糙度高的金属膜片与刚性金属面
在一定气压预应力作用下紧密贴合，实现
密封功能，如下图所示。



优点：
◎ 实现远程密封
◎ 对配合面的平行度和
相对距离要求低

3. Summary

- 1) 大部分子探测器机械设计停滞在初始阶段
- 2) 探测器、电子学和机械等硬件三方需要加强沟通
- 3) 抓大放小，求大同存小异，尽快给机械工程师明确任务和设计要求等

现状：

机械总图仍处在第0版阶段，远没有达到多方自治的程度！

Thanks