




北京大學

CMS MTD BTL Sensor R&D and Assembly in Phase2 Upgrade

Xiaohu Sun, Mingtao Zhang, Licheng Zhang, Jin Wang, Leyan Li, Mingxian Zhang, Zhiyuan Li
Peking University

第十届中国LHC物理会议 (CLHCP2024 青島), 11/14/2024






- CMS MTD BTL Detector for HL-LHC
- BTL Sensor R&D and Test Beam
- BTL Assembly and Local Lab Setups at PKU
- Summary



北京大學



01 CMS MTD BTL detector for HL-LHC

Physics motivation of MTD





北京大學

High luminosity → High pileup

The MTD is a new CMS Phase-II detector for the HL-LHC.
It will be added to CMS to help meet the challenge of high luminosity.

- HL-LHC, 3000 fb^{-1} at the cost of **140-200** simultaneous collisions (PU)
- **MTD** + upgraded tracker = Run2-esque **PU** mitigation



Physics motivation of MTD



北京大學

MTD can effectively suppress pileup, improving the overall accuracy of physical measurements.

- It improves the precision of single Higgs measurements by **20-30%**.
- It increases the acceptance of Di-Higgs signals by **20%**.

MTD provides TOF information.

- It reduces reducible background by **40%** in the search for SUSY particles.
- It significantly enhances sensitivity to long-lived particles.


Composition and Highlights of MTD



北京大學

BTL and ETL

- Choice of sensor technologies for barrel and endcap timing layers driven by technology maturity, radiation hardness, power consumption, and cost and schedule considerations.



Highlights

- ✓ The MTD BTL is the first time that CMS barrel has achieved a **time resolution of tens of picoseconds**
- ✓ CMS will be the **only large-scale universal detector** on the LHC that measures tens of picoseconds of time in the barrel section

What is MTD BTL ?






北京大學

BTL is a **single-layer** MIP detector located in-between the outer tracker (OT) and the inner wall of the BTL-Tracker Support Tube (BTST).


It will measure time with **~30-60ps resolution.**

- Thin (**< 4 cm**), large area (**38 m²**) detector covering $|\eta| < 1.5$
- **~10k** Sensor Modules, each containing **16 LYSO crystal bars** and **two 16-channel SiPM** arrays
- Read out with custom TOFHIR2 ASIC
- Mounted on CO₂ **cooled trays** and installed on **inner surface of BTL Tracker Support Tube (BTST)**





北京大學



02 BTL Sensor R&D and Test Beam

Test Beam for BTL Sensor R&D




北京大学

Analysis of the time resolution of BTL module using minimum ionizing particles.

Setup:

- Conducted on CERN (180 GeV pion) and FNAL (120 GeV proton) beams



The time resolution is well modeled as a function of few SiPM parameters:


- gain, PDE and DCR

The optimal choice of SiPM and LYSO:

- 25 μm SiPM cell size from HPK SiPM and 3.75 mm thick LYSO

Such a sensor module configuration achieves a time resolution of about

- 25 ps with non-irradiated SiPMs
- 60 ps under the irradiation, annealing and temperature conditions representative of the end of the BTL detector operation



>> [Optimization of LYSO and SiPM paper submitted to JINST](#)






Test Beam Study by PKU : SiPM R&D



北京大學

SiPM

- Main optimization and research parameters: **Cell size of SiPM**
 - The time resolution for modules with non-irradiated SiPMs of different cell-sizes (15, 20, 25 μm)
 - 25 μm has the **best** time resolution
- More tests were conducted, such as comparing the time resolution of **SiPM from different manufacturers**
- Optimization of SiPM parameters has been **completed**






Test Beam Study by PKU : LYSO R&D



北京大學

LYSO

- Preliminary comparative tests were conducted on the quality of LYSO (size, yield, etc.) from various manufacturers
- Finally, perform time resolution testing on high-performance manufacturers using beam current
- The time resolution of **manufacturers Prod1 and Prod5** was compared as follows
- LYSO optimization has been **completed**




Results are measured at the optimal threshold

LYSO	Vov/V	angle/deg	t _{Res} /ps	error/%
prod1	1.50	32	38.2	6.9
		52	32.2	3.1
		64	30.9	9.0
	3.50	32	25.7	2.1
		52	23.5	1.2
		64	23.6	7.2
prod5	1.50	52	35.1	4.3
	3.50		24.6	4.0



北京大學



03 BTL Assembly and Local Lab Setups at PKU

Schedule of MTD BTL




北京大學

Assembly timeline

- Testbeam of sensor in 2023
- Improved the assembly and QA/QC in 2023 & 2024
- Assembly Center Certification in 2024
- Start batch assembly in the Autumn of 2024
- End assembly in 2025






382	Module production batch 4	January 7, 2025	Feb 7, 2025	2.76 weeks
383	Module production batch 5	Feb 7, 2025	Mar 11, 2025	3.1w
384	Module production batch 6	March 11, 2025	April 11, 2025	3.38 weeks
385	Module production batch 7	April 11, 2025	May 13, 2025	3.7 weeks
386	Module production batch 8	May 13, 2025	June 12, 2025	1m
387	Module production batch 9	June 12, 2025	July 15, 2025	1.1m
388	B.A. 3.2 Finish of module production	July 15, 2025	July 15, 2025	1.1m
389	Tray production & assembly	Nov 18, 2024	Sep 16, 2025	0 days
390	B.A.4.0 Tray production starts	Nov 18, 2024	Nov 18, 2024	2w
391	Tray production batch 1 - module mounting	Nov 18, 2024	Dec 6, 2024	2w
392	Tray production batch 1 - CC, cabling, testing	Dec 27, 2024	Jan 9, 2025	0 days
393	Tray production batch 2 - module mounting	Dec 6, 2024	Dec 26, 2024	2.02 weeks
394	Tray production batch 2 - CC, cabling, testing	Jan 10, 2025	Jan 23, 2025	0 days
395	B.A.4 Tray production 25% done	Jan 23, 2025	Jan 23, 2025	0 days
396	Tray production batch 3 - module mounting	Jan 24, 2025	Feb 12, 2025	0 days
397	Tray production batch 3 - CC, cabling, testing	Feb 13, 2025	Feb 26, 2025	0 days
398	Tray production batch 4 - module mounting	Feb 27, 2025	Mar 18, 2025	0 days
399	Tray production batch 4 - CC, cabling, testing	March 19, 2025	April 1, 2025	0 days
400	B.A.5 Tray production 50% done	April 1, 2025	April 1, 2025	0 days
401	Tray production batch 5 - module mounting	April 2, 2025	April 21, 2025	0 days
402	Tray production batch 5 - CC, cabling, testing	April 22, 2025	May 5, 2025	0 days
403	Tray production batch 6 - module mounting	May 6, 2025	May 23, 2025	0 days
404	Tray production batch 6 - CC, cabling, testing	May 26, 2025	June 6, 2025	0 days
405	Tray production batch 7 - module mounting	June 9, 2025	June 26, 2025	0 days
406	Tray production batch 7 - CC, cabling, testing	June 27, 2025	July 10, 2025	0 days
407	Tray production batch 8 - module mounting	July 11, 2025	July 30, 2025	0 days
408	Tray production batch 8 - CC, cabling, testing	July 31, 2025	Aug 13, 2025	0 days
409	Tray production batch 9 - module mounting	Aug 14, 2025	Sep 2, 2025	0 days
410	Tray production batch 9 - CC, cabling, testing	Sep 3, 2025	Sep 16, 2025	0 days
411	B.A.6 Tray production 100% finished	Sep 16, 2025	Sep 16, 2025	0 days
412	BTL Integration	Nov 18, 2024	Mar 8, 2028	0 days
413	TIF preparation for integration	Nov 18, 2024	May 1, 2025	-4.2h
414	TIF preparation for integration	Jan 30, 2025	Mar 27, 2025	-4.2h
415	BE prototype installed in TIF	Nov 18, 2024	Jan 13, 2025	2.6m
416	Tray test insertion	Mar 27, 2025	May 1, 2025	-4.2h
417	B.A.7.0 TIF ready for BTL integration	May 1, 2025	May 1, 2025	-4.2h
418	TST integration	May 1, 2025	July 29, 2027	0 days
419	B.A.7 Start of TST integration	May 1, 2025	May 1, 2025	-4.2h
420	TST+ integration	May 1, 2025	July 29, 2025	-4.2h
421	Insert batch 1 of 6 trays	May 1, 2025	May 14, 2025	-4.2h
422	Connecting batch 1 of 6 trays	May 14, 2025	May 27, 2025	-4.2h
423	Insert batch 2	May 14, 2025	May 27, 2025	-4.2h
424	Connect batch 2	May 27, 2025	June 9, 2025	-4.2h
425	Insert batch 3	May 27, 2025	June 9, 2025	-4.2h
426	Connect batch 3	June 9, 2025	June 20, 2025	-4.2h
427	Insert batch 4	June 9, 2025	June 20, 2025	-4.2h
428	Connect batch 4	June 20, 2025	July 3, 2025	-4.2h





Assembly of MTD BTL



北京大學



	Module	RU	Tray	Total
Channels (SiPMs)	32	768	4608	331776
Crystals	16	384	2304	165888
ASICs	1	24	144	10368
Modules	-	24	144	10368
Readout units (RU)	-	-	6	432
Trays	-	-	-	72



Cooling plate assembly and QC is ongoing at CERN

All components are assembled and validated at 4 global BTL Assembly Centers (BACs)


- Virginia
- Caltech
- Milan
- Beijing

Trays will be shipped to CERN, integrated into the BTST


PKU Lab Setups for BTL Assembly and QAQC



北京大学



SM Assembly



SM glued and tools



Tray shelf for Tray assembly and QAQC

Assembly and QA/QC of Sensor Module



北京大学

Assembly of Sensor Module

Assembly materials

- **RTV** with a high refractive index close to that of LYSO

Assembly tool : GAMBIT

- **Control RTV thickness, SiPM/LYSO alignment, and others**


Standardization of Assembly flow

- **The humidity, time,** and other ranges for placing the module

QA/QC of Sensor Module

- measure the light yield of each channel to show the assembly quality
- Components: Electronic module, **constant temperature dark box**, data collection system, and source movement system

In Leyan's talk






Assembly and QA/QC of Sensor Module



北京大学


QA/QC at PKU



QAQC result of the first batch SMs



Batch production of QAQC boards



Assembly and QA/QC of Detector Module






北京大學

Detector Module : Sensor module, FE front-end electronic board, and copper shell for heat exchange

Assembly process of DM: **Thermal contact**

- Good contact between **the outer end of TEC on SiPM** and the **copper**
- Coverage of **thermal pads** on important chip surfaces on FE board
- **Avoid contact** between LYSO crystals and other components

QA/QC of the DM mainly involves thermal coupling testing



JIAMU DESIGN

JIAMU DESIGN

Assembly and QA/QC of BTL Tray



北京大學

MTD BTL Tray



- A BTL Tray will cover a detector range of **10 degrees** and **2.5 meters at η**
- A total of **72 Trays** cover the entire barrel of the MTD time detector

Assembly of BTL Tray

- 6 RUs, each includes a cooling plate, CC board, PCC board, and 12 DMs.

The **tray QA/QC system** based on Serenity board and custom tray powering board is currently being established.

Powering board



Research and Workshop on BTL assembly



北京大學




The first complete **detector module** was produced at **CERN** by the end of 2023

for the **manufacturing process** of detector modules



In March 2024 at CERN, Complete the assembly of **the whole RU** for the first time




In July 2024, at CERN,

Completed the **assembly of the entire Tray** for the first time, **QA/QC** was carried out, and **the assembly process** was basically determined

- BTL production is moving ahead according to the latest schedule!
- For the latest progress on BTL work, please refer to [Karlis](#) .



北京大學



04 Summary

Summary




北京大學

- MTD, a new CMS Phase-II detector for the HL-LHC will be added to CMS to help meet the challenge of high luminosity.
 - ✓ BTL is a single-layer MIP detector which will measure time with $\sim 30\text{-}60$ ps resolution.
- For PKU, We actively participate in the comprehensive work of MTD BTL , and, as one of the assembly centers, undertake 1/4 of the assembly work.
 - ✓ In terms of BTL Sensor R&D, we mainly conducted research on the cell size, manufacturers of SiPM and manufacturers of LYSO.
 - ✓ Assembly and QAQC work is currently underway at PKU !
- THU and BUAA also started learning up the assembly !
- BTL is not “moving to production”, BTL is “in production”.
 - ✓ We are confident that BTL will be the first fully completed CMS Phase-2 sub-detector come 4th November 2025.


Thanks for your attention!



北京大學



Back up



$$T_{ave} = 1/2(T_L + T_R) \quad \sigma_{ave} = 1/2\sqrt{\sigma_L^2 + \sigma_R^2}$$

$$\sigma_{diff} = 2 \times \sigma_{ave}$$

$$T_{diff} = T_L - T_R \quad \sigma_{diff} = \sqrt{\sigma_L^2 + \sigma_R^2}$$




Table 1.3: Nominal radiation doses and fluences at various locations of the timing layers after 3000 fb^{-1} . The last two columns show the radiation levels providing a safety margin of a factor 1.5. The fluence is normalized to 1 MeV neutron equivalent in silicon.

Experiment	r (m)	σ_T (ps)	$r/\sigma_T (\times 100)$ (m \times ps $^{-1}$)
STAR-TOF	2.2	80	2.75
ALICE-TOF	3.7	56	6.6
CMS-MTD	1.16	30	3.87

Region	$ \eta $	r (cm)	z (cm)	3000 fb^{-1}		$1.5 \times 3000 \text{ fb}^{-1}$	
				$n_{\text{eq}}/\text{cm}^2$	Dose (kGy)	$n_{\text{eq}}/\text{cm}^2$	Dose (kGy)
Barrel	0.0	116	0	1.65×10^{14}	18	2.48×10^{14}	27
Barrel	1.15	116	170	1.80×10^{14}	25	2.70×10^{14}	38
Barrel	1.45	116	240	1.90×10^{14}	32	2.85×10^{14}	48
Endcap	1.6	127	303	1.5×10^{14}	19	2.3×10^{14}	29
Endcap	2.0	84	303	3.0×10^{14}	50	4.5×10^{14}	75
Endcap	2.5	50	303	7.5×10^{14}	170	1.1×10^{15}	255
Endcap	3.0	31.5	303	1.6×10^{15}	450	2.4×10^{15}	675

Table 1.1: Expected scientific impact of the MIP Timing Detector, taken from Ref. [8].

Signal	Physics measurement	MTD impact
H $\rightarrow \gamma\gamma$ and H $\rightarrow 4$ leptons	+15–25% (statistical) precision on the cross section \rightarrow Improve coupling measurements	Isolation and Vertex identification
VBF \rightarrow H $\rightarrow \tau\tau$	+30% (statistical) precision on cross section \rightarrow Improve coupling measurements	Isolation VBF tagging, p_T^{miss}
HH	+20% gain in signal yield \rightarrow Consolidate searches	Isolation b-tagging
EWK SUSY	+40% background reduction \rightarrow 150 GeV increase in mass reach	MET b-tagging
Long-lived particles (LLP)	Peaking mass reconstruction \rightarrow Unique discovery potential	β_{LLP} from timing of displaced vertices