




Progress of CEPC ref-TDR TDAQ

Fei Li

On behalf of CEPC TDAQ Group



中國科學院高能物理研究所
Institute of High Energy Physics
Chinese Academy of Sciences

Progress of TDAQ

■ TDR draft v0.2

- First draft: Intro/requirements
- Partial draft: overview/simulation/trigger/DAQ

■ Elec. & TDAQ meeting

- Nov. 14th (Thu. morning)
- Discussed trigger and clock distribution schema

■ TDAQ meeting

- Nov. 14th (Thu. afternoon)
- <https://indico.ihep.ac.cn/event/24194/>
- Trigger rate discussion
- New physics trigger requirements(single photon)
- Trigger simulation progress
- TDAQ overview architecture discussion


Chapter 12 Trigger and Data Acquisition	1
12.1 Introduction	1
12.2 Requirements	1
12.2.1 Requirements	1
12.2.2 Event rate & background rate estimation	1
12.3 Overview Design	1
12.3.1 Design consideration	1
12.3.2 TDAQ design structure	1
12.4 Trigger Simulation and Algorithms	1
12.4.1 Physics Signatures and primitives with sub-detectors	2
12.4.2 Sub-detectors trigger algorithms	2
12.4.3 Global trigger algorithms	4
12.5 Hardware Trigger	5
12.5.1 Previous experience on large facilities	5
12.5.2 System architecture	5
12.5.3 Common Trigger Board	5
12.5.4 Trigger Control and Distribution	5
12.5.5 Resource cost estimation	5
12.6 Software and High Level Trigger	5
12.6.1 Previous experience on large facilities	5
12.6.2 HLT software	5
12.6.3 Study of GPU usage in the HLT	5
12.6.4 Study of FPGA usage in the HLT	5
12.6.5 Model for CPU estimation	5
12.7 Data Acquisition System	5
12.7.1 Previous experience on large facilities	5
12.7.2 Overview of System Functionality	5
12.7.3 Detector Readout	5
12.7.4 Dataflow	5
12.7.5 Online Software	5
12.7.6 Hardware Deployment	5
12.8 Detector Control System	5
12.8.1 Control and monitoring requirements	5
12.8.2 Experience in detector control system	5
12.8.3 Detector control system software architecture design	5
12.9 Experiment Control System	5
12.9.1 Requirements	5
12.9.2 Experience in experiment control system	5
12.9.3 Software framework design	5
12.9.4 Online Data Center	5
12.9.5 Infrastructure and services	5
12.10 Summary	5

TCDS-Trigger Clock Distribution System

■ TCDS/TTC

- Clock, BC0, Trigger, orbit start signal distribution
- Full, ERR signal feed back to TCDS/TTC and mask or stop L1A

- TCDS-Trigger Clock Distribution System
- TTC- Trigger, Timing and Control
- DCTD-Data Concentrator and Timing Distribution
- BEE-Backend board Electronic



TDAQ are only responsible for system-level distribution, each system is then responsible for its own internal distribution.

Trigger & Data Rate

- Compress background -> 1% @ L1
- Compress background -> 0.1% @ HLT
- Data size per bunch cross
 - 300Kbytes @ Higgs
 - Unknown @Z
- Event size < 2 Mbyte
 - Occupancy and read out window
- L1 trigger rate
 - 13~120 kHz @ Higgs&low lum. Z
- DAQ data rate
 - Read out: 26~240 GB/s
 - @ Higgs & low lum. Z
 - Storage: 0.3~7.5 GB/s

	Higgs	Z(10MW)	Z(50MW)	W	tt
Luminosity(10E34/cm2/s)	8.3	38	192	26.7	0.8
Bunch space(ns)	346.2	69.3	23.1	253.8	4523.1
Bunch cross rate(MHz)	1.34	12	39.4	6.5	0.18
Raw data rate before trigger (TBytes/s)	0.4	3.6	11.82	1.95	0.048
Physical event rate(kHz)	0.008	13.2	66	0.1	0.002
L1 trigger rate(kHz)	13	120	400	65	2
DAQ readout rate(Gbyte/s)	26	240	800	130	4
High level trigger rate(kHz)	1	25	100	6	1
DAQ storage rate(Gbytes/s)	0.3	7.5	30	1.8	0.3

Backup

Working Plan for TDR

- 先根据河南技术方案修改一个版本，一周。后面三周扩充内容。
- 模拟：
 - 第一周：事例率 (Cal+Muon), muon tracking
 - 双gamma光子应对策略
 - 第二周：L1算法(Cal+Muon)算法，TDR editing
 - 第三周：TPC、OTK tracking，low lum. Z background.
 - 第四周：Global trigger start，TDR draft 0.1
 - 12月，TDR draft 1.0
 - HLT algorithm 结果
 - Global trigger
 - trigger efficiency

Chapter 12 TDAQ and online

12.1	Introduction	
12.2	Requirements and Design Considerations	
12.2.1	Requirements	
12.2.2	Event rate & background rate estimation	
12.2.3	Technology survey	
12.2.4	TDAQ policy consideration	
12.2.5	TDAQ Interface with electronics	
12.3	Trigger Simulation and Algorithms	
12.4	Hardware Trigger	
12.4.1	Previous experience on large facilities	
12.4.2	System architecture	
12.4.3	Common Trigger Board	
12.4.4	Trigger Control and Distribution	
12.4.5	Resource cost estimation	
12.5	Software and High Level Trigger	
12.6	Data Acquisition System	
12.6.1	Previous experience on large facilities	
12.6.2	Overview of System Functionality	
12.6.3	Detector Readout	
12.6.4	Dataflow	
12.6.5	Network	
12.6.6	Online Software	
12.7	Detector Control System	
12.8	Experiment Control System	
12.9	Summary	6

Working Plan for TDR

■ 硬件触发

– 11月

- Hardware trigger structure design for TDR
- trigger board/ TTC detailing
- BEE interface
- basic trigger primitives

– 12月 :

- trigger primitives for each L1 detectors
- common trigger board structure finalize
- L1 algorithm deployment design, boards num

Working Plan for TDR

■ HLT

- 11月
 - 编辑一页的FPGA加速
 - GPU, 概念性描述
 - 离线软件状况

■ DAQ

- 11月
 - system architecture
 - software layer data flow
 - RDMA/GPU/FPGA/Mem buffer
- 12月
 - Network/hardware
 - Online software

■ DCS

- 11月
 - DCS requirement from each detectors
 - framework design

■ ECS

- 11月
 - framework design
 - control network
- 12月
 - IT infrastructure
 - hardware
 - control/computing room
 - monitoring

Findings--revised

- The baseline plan is to transmit the full raw data to the **front-end** electronics and connect the trigger to the back-end electronics.
 - Transmit the full raw data from front-end electronics(on-detector) to **back-end** electronics(off-detector)
- A hierarchical trigger scheme is foreseen to bring event data rates down from **~3MHz** to **~1kHz** in ZH running and **~40MHz** to **~100kHz** at the Z pole.
 - The bunch cross rate in ZH running is about **1.34 MHz** when bunch space is 346.2 ns (2.9 MHz) and there is 54% bunch train gap.

Comments

- The detailed (bottom-up) design of the TDAQ must await further details on the sub detector design.
 - We will closely follow the design of each sub detector. Especially background study and data rate estimation from each sub detectors.
- Work on the trigger primitives is needed to bring the rate down to an acceptable input for the second-level trigger, and to inform further planning for the processing farms in the DAQ design. Should it be needed, a track trigger could provide a powerful additional primitive.
 - More simulation works on trigger primitive and more discussion with physics and detector experts are needed. Track trigger simulation will be next main work.
- High-level triggering will also need to weigh the physics-versus-bandwidth tradeoff for lower-energy events, e.g. from gamma-gamma collisions.
 - We need more study for low-energy events of beam induced background. And few gamma-gamma collisions are included in the available background sample data.

Recommendations

- A simple simulation of sub detector-based trigger inputs using simple, robust algorithms should be prioritized to allow more detailed specification of the requirements for TDAQ hardware and identify areas that need further attention. This should include an appropriate safety factor for beam-related backgrounds.
 - Basic trigger simulation study for each sub detectors are in progress.
 - And the safety factor needs to be discussed carefully.
- Further work should include an evaluation of benefits of implementing a track trigger as a complement to the calorimeter and muon primitives, and to clarify the bandwidth foreseen for gamma-gamma events.
 - We will move forward this after finish simple trigger simulation.

Physical Event Rate

■ Higgs 240GeV(30MW/50MW)

- BX rate: 0.8(1.74)/1.34(2.9) MHz
- Physical event rate: **5Hz/8Hz** (Higgs: 0.02Hz)


■ Z pole 91GeV(10MW/50MW)

- BX rate: 12(14.5)/39.4(43.3) MHz
- Physical event rate: **13.2kHz/66kHz**

	Higgs	Z		W	$t\bar{t}$
SR power per beam (MW)	30	30	10	30	30
Bunch number	268	11934	3978	1297	35
Bunch spacing (ns)	576.9 (×25)	23.1(×1)	69.2(×3)	253.8(×11)	4523.1(×196)
Train gap (%)	54	17	17	1	53
Luminosity per IP ($10^{34} \text{ cm}^{-2} \text{ s}^{-1}$)	5.0	115	38	16	0.5

	Higgs	Z	W	$t\bar{t}$
SR power per beam (MW)	50			
Bunch number	446	13104	2162	58
Bunch spacing (ns)	346.2 (×15)	23.1 (×1)	138.5 (×6)	2700.0 (×117)
Train gap (%)	54	9	10	53
Luminosity per IP ($10^{34} \text{ cm}^{-2} \text{ s}^{-1}$)	8.3	192	26.7	0.8

过程	xsection(nb)	百分比	事例率kHz
Bhabha	0.0586	0.001371951	0.068597543
muon	1.5361	0.035963374	1.798168703
tau	1.5249	0.035701158	1.78505791
qq	30.6522	0.717633315	35.88166573
电子中微子	2.9607	0.069316296	3.465814777
muon中微子	2.9896	0.06992906	3.499645306
tau中微子	2.9909	0.070023342	3.501167095
中微子总	8.9411	0.209330202	10.46651012
总共	42.7129	1	50
		亮度	
30MW		1.15E+36	4.91E+01
50MW		1.92E+36	8.20E+01



Z pole, ref: [MC /cifs/data/stdhep/CEPC91/2fermions/wi_ISR_20220618_50M/2fermions/](https://mc.cern.ch/data/stdhep/CEPC91/2fermions/wi_ISR_20220618_50M/2fermions/)

Raw Data Rate

Data rate before trigger

- <1 TB/s @ Higgs
- Several TB/s @ Z

L1 trigger rate

- O(1k) Hz @ Higgs
- O(100k) Hz @ Z

Event size < 2 MB

- Related to occupancy and read out window

Storage rate after HLT

- <100 Hz(200 MB/s) @ Higgs
- 100 kHz (200 GB/s) @ Z

	Vertex	Pix(ITKB)	Strip (ITKE)	OTKB	OTKE	TPC	ECAL-B	ECAL-E	HCAL-B	HCAL-E	Muon
Channels per chip	512*1024	512*128	1024	128		128	8~16				
Data Width /hit	32bit	42bit	32bit	48bit		48bit	48bit				
Avg. data rate / chip	0.18Gbps/chip, 1Gbps/chip inner	3.53Mbps/chip	21.5Mbps/chip	2.9Mbps/chip	38.8Mbps/chip	~70Mbps/module Inmost	10kHz/ch	10kHz/ch	5kHz/channel	5kHz/channel	10kHz/channel
Detector Channel/module	1882 chips @Stch &Ladder	30,856 chips 2204 modules	23008 chips 1696 modules	83160 chips 3780 modules	11520 chips 720 modules	492 Module	0.96M chn ~60000 chips 480 modules	0.39 M chn	3.38M chn 5536 aggregation board	2.24M chn 1536 Aggregation board	43,176 chn, 288 modules
Avg Data Vol before trigger	474.2 Gbps	101.7 Gbps	298.8 Gbps	249.1 Gbps	27.9 Gbps	34.4 Gbps	460.8 Gbps	187 Gbps	811.2 Gbps	537.6 Gbps	24 Gbps
Occupancy(%)	0.022	0.025(Strip)		0.35(Strip)		0.0028	0.58		0.002		0.038
Sum	3.2 Tbps = 400GB/s										

Collected from each detectors @Higgs

Trigger simulation

■ Trigger simulation study

- BDT: energy + Centre of gravity for Ecal&Hcal
 - Higgs: 1.34MHz->3.4kHz
 - Trigger efficiency 95%->99.9%, background 5%->0.25%
- Tracking @ Muon detector
- gamma-gamma collisions

