



CEPC Ref-TDR ECAL Updates

Yong Liu (IHEP) for the CEPC Ref-TDR ECAL team
CEPC Reference Detector TDR Weekly Meeting
February 11, 2025




Overview on updates

- Crystal ECAL transverse granularity at CEPC Day: [talk in Jan. 24](#)
- CEPC Ref-TDR ECAL Weekly Meetings
 - Jan. 24, 2025: <https://indico.ihep.ac.cn/event/24786/>
 - Feb. 7, 2025: <https://indico.ihep.ac.cn/event/25006/>




Overview on updates

- Crystal ECAL transverse granularity at CEPC Day ([Jan. 24, 2025](#))
- CEPC Ref-TDR ECAL Weekly Meetings
 - Jan. 24, 2025: <https://indico.ihep.ac.cn/event/24786/>
 - Feb. 7, 2025: <https://indico.ihep.ac.cn/event/25006/>
- Summary of talks and discussions
 - Crystal ECAL transverse granularity of 15x15 mm (new)
 - Promising reduction in cost and power; similar jet performance (BMR<4%)
 - γ/π^0 discrimination technique using EM shower profiles
 - [SiPM testing and discussions](#) on SiPM-ASIC design
 - Cs-137 tests with BGO and NDL-SiPMs: typical waveforms of 662 keV gamma
 - [Updated results](#): impacts to ECAL with new MC samples of beam-induced backgrounds
 - BIB hit rate in endcap ECAL: max. 2MHz/cell in Low-Lumi Z (previously 1MHz/cell)




Preparations for Ref-TDR ECAL cost review

- Considerations on planning: [slides](#) (Feb. 7, 2025)
 - Context: CEPC Ref-TDR cost review in March - April
 - ECAL needs to start preparations of internal discussions/reviews in February asap
- ECAL: key cost drivers
 - (1) SiPM (major domestic vendor); (2) Crystals (BGO/BSO); (3) Carbon-fiber
- NDL-SiPM
 - First meeting in Feb. 6; second meeting in Feb. 12 with detector + electronics teams
- Scintillating crystal
 - Visit SIC-CAS in Feb. 12: crystal transverse size (production yield), BGO and BSO (costs)
- Carbon-fiber reinforced materials
 - Visit [Harbin FRP Institute Co.](#): further detailed planning and coordination with Q. Ji
 - FEA results, feasibility, mass production, QC




Backup Slides



SiPM and electronics: linearity specification

- SiPM response linearity to BGO scintillation light: simulation studies done
 - Need to quantify more details from existing studies
- Front-end electronics linearity
 - Work plan: to be modelled in the ECAL digitisation
 - Target: ASIC non-linearity effect should be smaller than SiPM non-linearity
 - “HGCROC”: a state-of-art chip for CMS HGCal, considered as a first reference



Including BGO scintillation and pixel recovery effects






Figure 2. ADC characterisation. Top: charge conversion in ADC units versus injected charge. Middle: noise in ADC units for each charge. Bottom: integral non linearity (INL).



Work plan on TDRrd ECAL chapter (updated)

- A first draft in late Nov. or early Dec. would include
 - General ECAL requirements
 - ECAL technical options: SiW-ECAL, ScW-ECAL, crystal
 - Performance: single-particle EM performance, two-particle separation power
 - Crystal calorimeter prototyping and beamtests
 - SiPM and readout electronics specifications
 - Beam-induced backgrounds: hit rates and impacts to performance
 - Mechanics and cooling: preliminary designs and FEA results, CF prototypes
- Studies to address technical challenges: to be continued after TDRrd draft
 - Impacts to ECAL performance: temperature variations and radiation damages
 - Calibration schemes: Bhabha/di-muon events with colliding beams; in-situ calibration system



SiPM and readout electronics: a first set of specs


SiPM parameters

Parameters	NDL-SiPM (EQR06)	NDL-SiPM (EQR10)	HPK S14160-3010PS
Pixel pitch	6um	10um	10um
Num. of pixels in 3x3mm	244,719	90,000	89,984
Gain	8E4	1.7E5	1.8E5
Operational Voltage	Vb + 8V (Vb=24.5V)	Vb + 12V (Vb=24.5V)	Vb + 5V (Vb=38V +/- 3V)
Peak PDE	30% (at 420nm)	36% (at 420nm)	18% (at 460nm)
Typical DCR	2.5 MHz	3.6 MHz	700 kHz
Inter-pixel Crosstalk	12%	Not specified in data sheet	<1%
Terminal Capacitance	45.9pF	31.5 pF	530pF

Blue: data sheet
 Green: measurement
 Red: no information


SiPM-readout electronics: first specs

Parameters	NDL-SiPM (EQR06)	NDL-SiPM (EQR10)	HPK S14160-3010PS
Charge per 1 p.e.	12.8 fC	27.2 fC	28.8 fC
Threshold (10 p.e.)	128 fC	272 fC	288 fC
1 MIP (200 p.e.)	2.56 pC	5.44 pC	5.76 pC
Max. charge: 3000 MIPs	7.68 nC	16.32 nC	17.28 nC




IDRC recommendations to calorimetry (1)

- *“The innovative technologies selected for the baseline ECal and HCal present both opportunities and challenges. It is essential to maintain steady progress in prototyping and simulation to demonstrate their feasibility and readiness, along with finalizing specifications. One aspect that must be monitored and perfected is the reproducibility of glass scintillators.”*
- **Work Plan**
 - Continue data analysis of crystal calorimeter prototype beamtests
 - Aim for publications as journal papers (CERN, DESY) in Nov. – Dec.
 - Specifications on SiPM and readout electronics
 - Dedicated discussions with electronics colleagues started in Nov. 1
 - Aim for finalising a set of specs in coming 2-3 weeks after discussions and iterations




IDRC recommendations to calorimetry (2)

- “Design choices should be thoroughly justified by physics goals achieved with simulation of a full detector model. **Alternative parameter choices** should be considered and evaluated for physics outcomes. For example, ECal crystals of 1 cm (transverse) x 2 cm (depth) would reduce channel count and cost. Does it impact physics performance? ”
- “Some specific performance issues that would be interesting to more fully understand. These include **higher energy π^0 reconstruction**, which may benefit, for example, from a staggered bar arrangement or finer granularity in the first few layers. Also **electron ECal resolution** when the bending of electrons match the 12 degree incline angle. Does this impact electron measurements?”
- **Work Plan**
 - Calorimetry software team first focuses on performance comparison with crystal transverse granularities: 10x10 mm versus 15x15 mm (ongoing studies)
 - Other recommendations remain to be discussed to come up with a more detailed plan for the given constrained timeline



Suggestions from IDRC members

- Tommaso Tabarelli de Fatis (Università di Milano Bicocca)
 - Following up on our discussion after your talk yesterday, I would like to suggest that you try to simulate the response of a a detector with
 - 0.5 (side) x 1 (depth) x ~40 cm in the first 4 layers (~4 X0)
 - 1.0 (side) x 1 (depth) x ~40 cm in the next 16 layers
 - 2.0 (side) x 1 (depth) x ~40 cm in the last 8 layers
 - This would give the same total number of SiPMs, but improve the granularity for pi0/gamma separation.
 - Another option would be to stick to 1x1 cm² bars, to ease production, but stagger them by 0.5 cm in each second layer. This might require 0.5 cm side bars at the two ends.
- James Brau (U. Oregon)
 - Different longitudinal granularity for long bars: e.g. cross section of 1x2 cm² with coarser longitudinal segmentation (a factor of 2 less)




Preliminary report of IDRC Review: ECAL part (1)

- General remarks

- *Findings: The electromagnetic calorimeter (ECal) and hadronic calorimeter (HCal) teams are strong and productive. They are generally making good progress on their technologies.*


- Comments

- *The ECal team recognizes that they have several challenges in front of them to bring their chosen technology to maturity. They should sustain steady progress addressing these including:*
 - *Developing and perfecting the Particle-flow algorithms including the effective pattern recognition and minimization of ambiguity issue;*
 - *Dealing technical issues (ASICs, hermiticity, minimized power, mass production) with the very large number of channels in the very finely grained concept;*
 - *Successfully overcoming beam-induced backgrounds and radiation damage;*
 - *Understanding the impact of design choices on the performance to define specifications for the SiPMs linearity, crystal granularity and uniformity, readout threshold and noise, calibration needs;*
 - *Developing and optimizing the in-situ calibration system.*




To address technical challenges (1)

- *“Developing and perfecting the Particle-flow algorithms including the effective pattern recognition and minimization of ambiguity issue”*
- **Work Plan: joint efforts with software team**
 - This suggestion is related to further optimisations of the particle-flow algorithm CyberPFA.
 - The work plan include the performance evaluation with the full detector geometry (including both barrel and endcaps) and also the tracking performance, especially its matching with calorimeter clusters.
 - Besides, the calorimeter calibration for the jet energy scale needs in-depth studies, to ensure correct reconstruction of the Z and H boson masses in a consistent way.




To address technical challenges (2)

- *“Dealing technical issues (ASICs, hermiticity, minimized power, mass production) with the very large number of channels in the very finely grained concept.”*
- Work plan: joint efforts with electronics, software, mechanics teams
 - This is related to the general detector design for ECAL, optimisation and validation, including mechanics, cooling, embedded electronics and their integration.
 - ASIC development requires joint efforts of CEPC electronics team, while keeping an eye on DRD6/7 collaborations on new calorimetry-specific ASIC developments.
 - Modularity is a major prerequisite to demonstrate mass production capability. We plan to further optimize and validate modular designs for barrel and endcaps, and would also need to propose protocols on Quality Assurance and Quality Control (QA/QC) for key components, including crystals, SiPMs, ASICs, mechanics, cooling, etc.
 - Further studies on integration of modules and cooling (in barrel and endcaps) is planned.




To address technical challenges (3)

- *“Successfully overcoming beam-induced backgrounds and radiation damage.”*
- Work plan: joint efforts with software and MDI teams
 - This is related to simulation studies of beam-induced backgrounds and modelling of radiation damages to crystals and SiPMs.
 - Key information is needed from the MDI team: mappings of **TID (Total Ionisation Dose)** and **NIEL (Non-ionisation Energy Loss)** in ECAL (esp. in ECAL endcaps), which is a crucial input for study radiation damages to crystals and SiPMs
 - Based on ongoing developments of modelling (including TID vs crystal transparency, NIEL vs SiPM noises), we plan to quantify the impacts of radiation damage to the EM performance and also to the cooling system design (e.g. SiPM operational temperature)
 - We also plan to further study extra hits from beam-induced backgrounds and evaluate their impacts to EM performance by mixing calorimetric signals and backgrounds. This would also be related to the optimization of ECAL time window for signal readout.




To address technical challenges (4)

- *“Understanding the impact of design choices on the performance to define specifications for the SiPMs linearity, crystal granularity and uniformity, readout threshold and noise, calibration needs.”*
- Work plan: joint efforts with software and electronics teams
 - SiPM noise, linearity, readout threshold and crystal uniformity have been extensively studied in the lab and in simulation. We would need to prepare a comprehensive summary of these results and thus define specifications, which would be also an input to the SiPM-readout chip design.
 - Crystal granularity: longer crystal bars (60cm) and coarser transverse granularity (15x15mm) were already tested in beams. Granularity would also impact the PFA performance, which is being investigated by the software team. Other granularity designs were suggested by some IDRC members via separate messages, which require further discussions with the software team.
 - Calibration needs: we plan to study calibration precision to meet the specifications.



To address technical challenges (5)


- *“Developing and optimizing the in-situ calibration system.”*
- Work plan: joint efforts with electronics and software teams
 - In-situ calibration system in general would be indispensable to the success of ECAL that can finally achieve optimal EM performance
 - Bhabha and di-muon events at CEPC would be ideal for ECAL calibration. We would need to estimate typical numbers of events and running times that are required to achieve the calibration precision
 - The calibration system needs to “remove” beam-induced backgrounds that could be mixed in the events in the pile-up way.
 - We may need to monitor and correct the crystal transparency and SiPM noises due to radiation damages. Furthermore, the instantaneous radiation damage to crystals and SiPMs during beam injection may also need to be monitored and corrected by the in-situ calibration system.
 - A detailed design would need to be discussed with the electronics team.



Preliminary report of IDRC Review: ECAL part (2)

- Comments

- *There are ECal issues that need clarification such as*
 - *The 0.1 MIP ECal threshold is chosen based on a balance between S/N and dynamic range - a more quantitative explanation of this is missing from presentation;*
 - *SiPM dynamic range and linearity needs specification;*
 - *The noise levels of the ECal including SiPMs and readout electronics;*
 - *Anticipated level of crystal degradation with time, and its impact on physics performance;*
 - *Homogeneity of MIP detection efficiency.*



Feedback

- *“The 0.1 MIP ECal threshold is chosen based on a balance between S/N and dynamic range - a more quantitative explanation of this is missing from presentation.”*
 - There have been many extensive studies (simulation, measurements). Need to summarise results.
- *“SiPM dynamic range and linearity needs specification.”*
 - There have been many extensive studies (simulation, measurements). Need to summarise results.
- *“The noise levels of the ECal including SiPMs and readout electronics.”*
 - Tested in the lab and beamtests.
- *“Anticipated level of crystal degradation with time, and its impact on physics performance”*
- *“Homogeneity of MIP detection efficiency”*