



FCPPN/L 2025

B_c studies and upgrade of ECAL for LHCb

Xiaofan Pan, Ming Zeng, Liming Zhang (**Tsinghua**)

Liupan An, Yiheng Luo, Zhenwei Yang, Zhiyang Yuan, Yanxi Zhang (**PKU**)

Weisong Duan, Hengne Li (**SCNU**)

Jiale Fei, Jike Wang (**Wuhan**)

Sergey Barsuk, Fabian Glaser, Chiara Mancuso, Patrick Robbe (**IJCLab Orsay**)

Jul. 21 – 25, 2025 Haitian Grand Theatre Hotel Qingdao, China

Outline


1. Introduction
2. B_c studies
3. Ongoing R&D for ECAL upgrade
 - 1) Absorber and large-scale production
 - 2) SpaCal-W with plastic fibers for LS3
 - 3) SpaCal-W with crystal fibers for LS4
 - 4) Electronics for PicoCal
4. Summary and conclusion

Outline


1. Introduction
2. B_c studies
3. Ongoing R&D for ECAL upgrade
 - 1) Absorber and large-scale production
 - 2) SpaCal-W with plastic fibers for LS3
 - 3) SpaCal-W with crystal fibers for LS4
 - 4) Electronics for PicoCal
4. Summary and conclusion

The Current LHCb ECAL

- ECAL is essential to all measurements involving neutrals and electrons
- Optimized for π_0 and γ identification in the few GeV to 100 GeV region at $2 \times 10^{32} \text{ cm}^{-2} \text{ s}^{-1}$




- Shashlik technology used
- Scintillator: Polystyrene - p-terphenyl - POPOP
- WLS fibres: Kuraray Y-11



- Radiation hard up to 40 kGy
- Energy resolution:

$$\sigma(E)/E \approx 10\%/\sqrt{E(\text{GeV})} \oplus 1\%$$



View from the back

- Large array of $\approx 50 \text{ m}^2$ with 3312 modules and 6016 channels



Motivation to upgrade

- To fully use the opportunities provided by the HL-LHC for heavy flavor physics

Run 3			LS3			Run 4			LS4			Run 5					
2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041

- Upgrade II to be installed at LS4: $1.5 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$
Original design: $2 \times 10^{32} \text{ cm}^{-2} \text{ s}^{-1}$
Run 3: $2 \times 10^{33} \text{ cm}^{-2} \text{ s}^{-1}$

Vertex Locator (VELO)



Run 3: pile-up ~ 6

Upgrade II: pile-up ~ 40

High pile-up
Radiation hardness

...

New ECAL technology R&D needed

Motivation to upgrade




Requirements for the Upgrade II:

- Radiation doses up to **1 MGy** and $\leq 6 \times 10^{15}$ 1 MeV neq/cm² in the centre for 300 fb⁻¹
 - New technologies required for the center

- Pile-up mitigation crucial
 - Timing $\mathcal{O}(10 \text{ ps})$ precision
 - Increased granularity
 - longitudinal segmentation

Scintillators R&D needed

- Keep current energy resolution of $\sigma(E)/E \approx 10\%/\sqrt{E} \oplus 1\%$



Technologies for ECAL Upgrade II


SPACAL technology for inner region.

- **1.5×1.5 cm² cell - W absorber and crystal fibres**
 - Development of radiation-hard crystal fibres
 - Polystyrene fibres for Run 4, then replaced by crystals
- **3×3, 4×4 cm² cell - Pb absorber and plastic fibres:**
 - Need radiation-tolerant plastic fibres



Shashlik technology for outer region

- **4×4, 6×6, 12×12 cm² cell**
 - Timing improved with faster WLS fibres and double-sided readout

PicoCal 2024 - baseline




Side view



Y. Guz, IHEP

ECAL configuration to be installed during LS3

- **176 new SpaCal modules in the inner region**
→ This region covers about 35% of photons and neutral pions from B-hadron decays over the ECAL acceptance
- **The existing modules will be rearranged in rhombic areas (32 Shashlik modules with 4×4 cm² cell size will be replaced)**




Cell size:	Modules:	Number of cells:
2×2 cm ²	16 new SpaCal-W modules with plastic fibres	576
2×2 cm ²	16 new SpaCal-W modules with plastic fibres - special shape	480
3×3 cm ²	104 new SpaCal-Pb modules with plastic fibres	1664
3×3 cm ²	40 new SpaCal-Pb modules with plastic fibres - special shape	480
4×4 cm ²	176 existing Shashlik modules	1584
6×6 cm ²	448 existing Shashlik modules	1792
12×12 cm ²	2'512 existing Shashlik modules	2512

Outline

1. Introduction
2. B_c studies
3. Ongoing R&D for ECAL upgrade
 - 1) Absorber and large-scale production
 - 2) SpaCal-W with plastic fibers for LS3
 - 3) SpaCal-W with crystal fibers for LS4
 - 4) Electronics for PicoCal
4. Summary and conclusion

Observation of the orbitally excited B_c^+ states

- The B_c^+ meson family is the only mesons composed of two different heavy quarks ($\bar{b}c$) [\[arXiv:2507.02149\]](#)
- Despite its ground state, **only the 2S excitations** have been observed at the LHC [\[arXiv:2507.02142\]](#)
- The **1P excited states** are predicted to decay solely **via radiative transitions**
 - ✓ most likely to be the next excitations to be observed, with predicted masses in the range of **(340, 520) MeV**
 - ✓ **four states** are expected, leading to **six peaks** due to unreconstructed photons from B_c^* decays



$$(L = 1) \otimes (S = 0, 1) \begin{cases} S = 0 \rightarrow 1^1P_1 \\ S = 1 \rightarrow 1^3P_0, 1^3P_1, 1^3P_2 \end{cases}$$

Four physical states

$$1^3P_0, 1^3P_2 \begin{pmatrix} 1P'_1 \\ 1P_1 \end{pmatrix} = \begin{pmatrix} \cos \theta & \sin \theta \\ -\sin \theta & \cos \theta \end{pmatrix} \begin{pmatrix} 1^1P_1 \\ 1^3P_1 \end{pmatrix}$$



mixing \downarrow

States	1^3P_0	$1P_1$	$1P'_1$	1^3P_2
Decays	$B_c^{*+}(\rightarrow B_c^+\gamma)\gamma$	$B_c^+\gamma$	$B_c^+\gamma$	$B_c^{*+}(\rightarrow B_c^+\gamma)\gamma$
		$B_c^{*+}(\rightarrow B_c^+\gamma)\gamma$	$B_c^{*+}(\rightarrow B_c^+\gamma)\gamma$	
#peaks	1	2	2	1

Observation of the orbitally excited B_c^+ states

- $B_c(1P)^+ \rightarrow B_c^+ \gamma$, where $B_c^+ \rightarrow J/\psi (\rightarrow \mu^+ \mu^-) \pi^+$ and photon reconstructed from calorimeter [\[arXiv:2507.02149\]](#)
- A pronounced wide peaking structure is seen within the predicted mass range (significance $> 7 \sigma$) [\[arXiv:2507.02142\]](#)
- The visible width exceed the expectation of single-peak interpretation \Rightarrow a minimal effective two-peak model used
- By fixing the peak positions and relative yields to theory, different theoretical models were investigated \Rightarrow all generally good
- The relative production rate, representing the fraction of B_c^+ comes from $B_c(1P)^+$ is determined using the LQCD model

$$R = 0.20 \pm 0.03 \pm 0.02 \pm 0.03$$



Outline

1. Introduction
2. B_c studies
3. Ongoing R&D for ECAL upgrade
 - 1) Absorber and large-scale production
 - 2) SpaCal-W with plastic fibers for LS3
 - 3) SpaCal-W with crystal fibers for LS4
 - 4) Electronics for PicoCal
4. Summary and conclusion

Ongoing R&D: Absorber and large-scale production

➤ Requirements

- High density: close to $\rho_W = 19.3 \text{ g/cm}^3$
- Geometry: $120 \times 120 \times 50 \text{ mm}^3$
- 5180 square holes of $1.20 \times 1.20 \text{ mm}^2$
- Roughness $R_a < 5 \text{ }\mu\text{m}$


➤ LaserAdd (雷佳) gradually improved the W absorbers

- $\rho \approx 19.0 \text{ g/cm}^3$, $R_a \approx 5 \text{ }\mu\text{m}$
- Young's module measured at THU, WHU, CERN



➤ We are finalizing all tests and QA system for PRR in June



Density measurement at WHU



Young's module measurement at THU






Perpendicularity measurement at WHU

Plane	Angle (°)	
	5# at top	6# at top
112	89.9	90.1
213	90.0	90.0
314	90.0	90.1
411	90.1	89.9
511 or 611	90.1	90.0
512 or 612	90.0	90.0
513 or 613	90.1	90.0
514 or 614	90.1	90.0

Outline

1. Introduction
2. B_c studies
3. Ongoing R&D for ECAL upgrade
 - 1) Absorber and large-scale production
 - 2) SpaCal-W with plastic fibers for LS3
 - 3) SpaCal-W with crystal fibers for LS4
 - 4) Electronics for PicoCal
4. Summary and conclusion


Ongoing R&D: Assembly for LS3



Test beam in May 2025 at CERN SPS:


➤ **First test of full Run 4 chain with new prototypes:**

- W absorbers
- 3HF green plastic fibres (square fibres $1 \times 1 \text{ mm}^2$)
- Optics assembly with bundlers and long “hollow” light guides
- R9880U PMTs



- Cable clipping circuits
- 10-meter signal cables
- Read-out with Run 3 & 4 front-end boards electronics

Ongoing R&D: Assembly for LS3



- **One more iteration of prototypes needed in Q3/2025:**
- SpaCal-W: optimised dimension of fibres ($0.98 \times 0.98 \text{ mm}^2$) and holes ($1.22 \times 1.22 \text{ mm}^2$)
- Compatible with performance requirements

Test beam in May 2025 at CERN SPS:

➤ First test of full Run 4 chain with new prototypes:

- W absorbers
- 3HF green plastic fibres (square fibres $1 \times 1 \text{ mm}^2$)
- Optics assembly with bundlers and long “hollow” light guides
- R9880U PMTs



- Cable clipping circuits
- 10-meter signal cables
- Read-out with Run 3 & 4 front-end boards electronics



Outline

1. Introduction
2. B_c studies
3. Ongoing R&D for ECAL upgrade
 - 1) Absorber and large-scale production
 - 2) SpaCal-W with plastic fibers for LS3
 - 3) SpaCal-W with crystal fibers for LS4
 - 4) Electronics for PicoCal
4. Summary and conclusion


Milestone: GAGG test systems at PKU

- Test systems finished in Mar. 2024
- The test results from PKU are consistent with those from CERN, providing a basis for effective cooperation on GAGG testing.


Decay time (TCSPC with X-ray)




Light output




Absorbance



Photoluminescence spectrum



Ongoing R&D: Accelerating Scintillation



➤ **The issue:** current commercial GAGG has scintillation decay time > 40 ns

- Mitigate spill-over effect on time resolution

➤ **Novel GAGG compositions developed to quench scintillation**

- Light yield reduced
- Decay time accelerated
- Time resolution kept competitive



➤ **R&D to produce large-size and homogeneous Czochralski ingots**

➤ **Collaboration with:**


- SIPAT(电科芯片), China
- FZU and Crytur, Czech Republic
- European project TWISMA including CERN, ILM & UCB, and ISMA

➤ **The Second prototype in June 2024**

- SiPAT GAGG with decay time ~ 20 ns
- 3D-printed absorber with LaserAdd (雷佳), China
- Under characterization in testbeam




Testbeam: SpaCal - W Absorber - Crystal Fibres



➤ **Energy resolution at $3^\circ+3^\circ$:**

- Sampling term: $10.6 \pm 0.2 \%$
- Constant term: $\sim 2 \%$

**First measurements performed with non-optimal configuration
degradation of energy and time resolution expected**



➤ **Time resolution SIPAT GAGG at $3^\circ+3^\circ$:**


- R11187 (Direct contact) and R9880U have similar performance (< 20 ps when > 20 GeV)
- MAPMT and R11187 (square LG and only front part) much worse in time resolution

Outline

1. Introduction
2. B_c studies
3. Ongoing R&D for ECAL upgrade
 - 1) Absorber and large-scale production
 - 2) SpaCal-W with plastic fibers for LS3
 - 3) SpaCal-W with crystal fibers for LS4
 - 4) Electronics for PicoCal
4. Summary and conclusion

Electronics for PicoCal

➤ Architecture:





➤ Readout with PMTs

- Two separate paths with dedicated ASIC developed in parallel, with the same technology (TSMC 65 nm), running at 40 MHz:
 - Time ASIC (SPIDER): waveform TDC in analog memories (R&T IN2P3, Orsay/Clermont-Ferrand/Lyon/Caen/Nantes) (dynamic range of ET = 50 MeV to 5 GeV, resolution 15 ps RMS)
 - Energy ASIC (Barcelona, Valence), measurement of the integrated charge at 40 MHz over 12 bits with two gains (dynamic range between ET = 0 and 40 GeV)

Measurement of Time: Waveform Digitizing

- Time measurement is done by sampling the signal shape using analog memories and a FPGA: development of a dedicated ASIC called SPIDER
- Time is computing using:
 - A counter (~ 1 ns step), DLL2
 - A DLL to define the region of interest (~ 100 ps step) DLL1
 - Samples on the signal shape: Cell banks
- The interpolation in a FPGA allows to measure the time with a precision of a few ps RMS with a precise calibration even with signals with small amplitudes.
- The main disadvantages that must be addressed in the new SPIDER chip:
 - Large deadtime (~ 100 μ s) limiting usage at high rate (goal = 40 MHz) \Rightarrow ADC massively parallel to reach at least 50% occupancy
 - Need of a trigger: every channel is self triggered



Technologie: TSMC CMOS 65 nm

- 10-bit Wilkinson ADC at 5 GHz
- Memory cells (switches/capacitors) with ~ 0.8 V dynamic range and noise level ~ 0.5 mV RMS
- DLL between 40 and 640 MHz

First prototype Automne 2024 (final version end 2029)

Outline

1. Introduction
2. B_c studies
3. Ongoing R&D for ECAL upgrade
 - 1) Absorber and large-scale production
 - 2) SpaCal-W with plastic fibers for LS3
 - 3) SpaCal-W with crystal fibers for LS4
 - 4) Electronics for PicoCal
4. Summary and conclusion

Summary and conclusion

➤ **Common activities in Chinese and French groups about LHCb ECAL Upgrade :**

- Observation of the orbitally excited B_c^+ states
- R&D for modules assembly with plastic fibers for LS3
- R&D for new modules with GAGG fibers for LS4
- The first SPIDER ASIC prototype (v0) was produced and delivered in early July 2025
- A test board for SPIDER(v0) was built, with testing set to start in late July 2025

➤ **In the near future:**

- Test beams at DESY and SPS to measure module characteristics(One more iteration in Q3/2025)
- The SPIDER ASIC v1 features 8 channels instead of 2 and will be produced by mid-2026

➤ **On the longer term:**

- Full production of innermost ECAL modules
- Full production of Front-End electronics
- Implementation of algorithms in FPGA to improve calorimeter reconstruction

Thanks for your attention!

博士后招聘 Postdoc position

Peking University's LHCb group



Job description:

Core R&D tasks for a next-generation electromagnetic calorimeter in the upgraded LHCb detector (ECAL development, construction, installation, and commissioning):

- Development of ultrafast, highly radiation-resistant novel scintillation crystals
- Mass production of high density, high precision tungsten absorber
- Test beam for ECAL prototype

工作描述:

面向LHCb升级后的下一代新型电磁量能器的核心研发任务（包括ECAL的研制、建造、安装与调试）：


- 开发超快、高抗辐射性能的新型闪烁晶体
- 量产高密度、高精度钨吸收体
- ECAL原型机的束流测试任务

Contact: yangluping@pku.edu.cn
yangzw@pku.edu.cn

Back up

Updated CERN accelerator schedule

Long Term Schedule for CERN Accelerator complex



- Run 3 extended till end of June 2026
- LHC restart for Run 4 in 2030
- LHC LS4 moved by one year to 2034-35
- LS5 becomes EYTES
- Also impact on SPS test beams!