

Workshop on Accelerator R&D for Ultimate Storage Rings

Tuesday, 30 October 2012 - Thursday, 1 November 2012

Book of Abstracts

Contents

Pulsed Sextupole Injection for BAPS	1
SOLEIL orbit feedback systems and photon BPMs	1
Anticipated limits on machine stability and consequences on machine and beamline designs	1
A 5BA low emittance lattice with superbends for Sirius	2
Some engineering considerations for USR light sources	2
Experience with Damping Wigglers at PETRA III	2
Compact low emittance lattice including superbends	3
Welcome	3
Workshop charge	3
Scientific cases for USR	3
Highlights of science of USR	3
Overview of USR design and performance requirements	3
PEP-X design	3
MAX-IV project and MBA with higher multipoles	4
Tevatron USR and other topics of USR	4
Latest development of ESRF and future plan	4
Overview of optics correction at Diamond and plan for DLS-II	4
Round beam experience at BINP	4
Discussion	4
Lattice design for Spring-8 II	4
USR upgrade for ALS	5
Optimization of dynamic aperture for the ESRF upgrade	5
Study of lower emittance lattice at SOLEIL	5

BAPS lattice design	5
Coupling correction at SLS, minimum vertical emittance	5
2-frequency RF system for short bunches at SPring-8	5
Discussion	6
Collective effects in USRs	6
Single and multiple Touschek scattering in low emittance rings	6
BAPS CSR, impedance and IBS	6
Propagation of ultra-short bunches in USRs and potential lasing	6
Optimal RF frequency	6
Top –up injection	6
Injection into low-lifetime USRs	7
Pulsed sextupole injection for MAX-IV	7
Some engineering challenges for a USR machine	7
MAX-IV magnet design	7
Pulsed sextupole injection for BAPS	7
Injection scheme for the SPring-8 upgrade	7
On-axis swap-out injection	7
High Gradient Magnet Design	8
Discussion	8
Design and fabrication of NSLS-II sextupole	8
Design for high precision small aperture magnets for BAPS	8
Discussion	8
Discussion	8
MAX-IV vacuum chamber design	8
Single non-linear injection kicker magnet	8
Fast pulsed power supply for ILC damping ring kicker	9
SOLEIL orbit feedback systems and photon BPMs	9
Multi-Bunch Feedback System in USR	9
Feedback system for USRs	9
Discussion	9

IDs for the ESRF upgrade	9
Ground vibration for BAPS	9
Superconducting IDs at BINP	10
IDs for Shanghai Synchrotron Radiation Facility	10
Discussion	10
PETRA-III damping wiggler experience	10
Undulator technology for USR	10
Cryogenic permanent magnet and superconducting small period undulators	10
Discussion	10
Report writing	11
Summary	11
Discussion	11
Anticipated limits on machine stability and consequences on machine and beamline designs	11
Development and Commissioning of a Single Non-linear Kicker Magnet System for the BESSY II Storage Ring Injection	11
Single and Multiple Touschek scattering in low emittance rings	12
Superconducting IDs at BINP	12
MAX IV vacuum System design	12
Undulator Technology for Ultimate Storage Rings (USRs)*	13
Lattice design for Spring-8 II	13
Two-frequency RF system for short bunches for SPring-8 II	14
Multi-bunch feedback system in USR	14
BAPS Lattice Design	14

7

Pulsed Sextupole Injection for BAPS

Author: yi jiao¹

¹ *IHEP*

Corresponding Author: jiaoyi@ihep.ac.cn

We will introduce the design of the pulsed sextupole injection for BAPS.

8

SOLEIL orbit feedback systems and photon BPMs

Author: Jean-Claude DENARD¹

Co-authors: Lodovico CASSINARI ²; Marie Labat ²; Nicolas HUBERT ³

¹ *Synchrotron SOLEIL*

² *Synchrotron Soleil*

³ *synchrotron Soleil*

Corresponding Author: denard@synchrotron-soleil.fr

A global orbit correction system based on two feedback loops, slow and fast, stabilizes the photon beam to the submicron level at the SOLEIL light source. Having two systems, each one using a different set of correctors is advantageous for performance and cost. The recent addition of dipole frontend XBPMs into the fast loop improves the stability of the bending magnet beamlines. A similar approach is planned for improving the stability of the in-vacuum undulator beamlines. An X-BPM just in front of the first BL critical element seems the most promising if it is sufficiently insensitive to the gap aperture. It is not the case of all our Blade X-BPMs. The issue of the X-BPM readings sensitivity to the gap size is even more critical for the Apple II undulators because the blade X-BPM cannot work for all gap and phase configurations. There is a strong need for XBPMs insensitive to undulator configuration changes.

9

Anticipated limits on machine stability and consequences on machine and beamline designs

Author: Jean-Claude DENARD¹

¹ *Synchrotron SOLEIL*

Corresponding Author: denard@synchrotron-soleil.fr

With the small emittance the future USRs will provide, the beam stability is going to be more and more a critical issue. I will compare a $\pm\sigma/10$ position stability tolerance for a 30 keV diffraction limited photon beam to the actual beam stability of an existing light source. The future USRs might or not achieve a better stability. We will see that for acquisition times from 10 ms to about 10 s a ± 100 nm stability requirement can be met. For shorter or longer acquisition times, photon beam position and angle feedback systems will likely be necessary. I briefly report on a state of the art BPM and orbit feedback system; on stable supports made of INVAR for BPM; and of a high performance hydrostatic leveling system (HLS).

10

A 5BA low emittance lattice with superbends for Sirius

Author: Lin Liu¹

Co-authors: Fernando Henrique de Sa ¹; Ricardo Rodrigues ¹; Ximenes Resende ¹

¹ *Brazilian Synchrotron Light Laboratory*

Corresponding Author: liu@lnls.br

We present the lattice design issues of the new Brazilian synchrotron light source (Sirius) currently under construction at the Brazilian Synchrotron Light Laboratory (LNLS) in Campinas. The Sirius lattice was recently revised to achieve a lower emittance. The new design is based on a 3 GeV, 5BA achromatic lattice with 0.28 nm.rad natural emittance without wigglers. The circumference is 518 m with 20 straight sections of alternating 6 and 7 meters in length. The dipoles will be based on the use of permanent magnet technology and will combine low field magnets (0.6 T) for the main beam deflection with a short 2 Tesla high field slice magnet (superbend) integrated in the center dipole. This will produce a longitudinal dipole gradient that is used to lower the emittance as well as to provide hard x-ray sources with a modest total energy loss.

11

Some engineering considerations for USR light sources

Author: Lin ZHANG¹

¹ *ESRF*

Corresponding Author: zhang@esrf.fr

Various projects of storage ring based light source under construction, and upgrade program of existing 3rd generation light sources are pushing the emittance lower and lower. Diffraction limited emittance in vertical direction is achieving in a number of light sources. Diffraction limited emittance in horizontal direction is ultimate performance for storage ring based light source –USR. There are many challenges in lattice design and optimization, in magnet design and manufacturing. Diffraction limited emittance means very small beam size. What should be the beam stability requirement for the USR? Some engineering issues are addressed in this presentation:

- Vacuum chamber and thermal absorber
- Beam stability requirement
- How to reach beam stability
- Heat load issues for beamline optics

12

Experience with Damping Wigglers at PETRA III

Author: Alexander Kling¹

¹ *DESY Hamburg*

Corresponding Author: alexander.kling@desy.de

PETRA III is a third generation light source which started operation in 2009. Twenty damping wigglers are installed in dispersion free straight sections in order to achieve a horizontal emittance of 1nmrad. We give a short overview of design considerations and beam

dynamics issues and report on experience from commissioning and user operation.

Session 1: Lattice Design (part 3) / 13

Compact low emittance lattice including superbends

Corresponding Author: liu@lnls.br

Welcome and Introduction Session / 14

Welcome

Welcome and Introduction Session / 15

Workshop charge

Corresponding Author: qinq@ihep.ac.cn

Welcome and Introduction Session / 16

Scientific cases for USR

Corresponding Author: dingh@iphy.ac.cn

Welcome and Introduction Session / 17

Highlights of science of USR

Corresponding Author: dongyh@ihep.ac.cn

Welcome and Introduction Session / 18

Overview of USR design and performance requirements

Corresponding Author: hettel@slac.stanford.edu

Session 1: Lattice Design (part 3) / 19

PEP-X design

Corresponding Author: borland@aps.anl.gov

Session 1: Lattice Design (part 1) / 20

MAX-IV project and MBA with higher multipoles

Corresponding Author: simon.leemann@maxlab.lu.se

Session 1: Lattice Design (part 3) / 21

Tevatron USR and other topics of USR

Corresponding Author: borland@aps.anl.gov

Session 1: Lattice Design (part 1) / 22

Latest development of ESRF and future plan

Corresponding Author: pantaleo.raimondi@esrf.fr

Session 1: Lattice Design (part 3) / 23

Overview of optics correction at Diamond and plan for DLS-II

Corresponding Author: riccardo.bartolini@diamond.ac.uk

Session 1: Lattice Design (part 3) / 24

Round beam experience at BINP

Corresponding Author: e.b.levichev@inp.nsk.su

Session 1: Lattice Design (part 3) / 25

Discussion

Session 1: Lattice Design (part 1) / 26

Lattice design for Spring-8 II

Corresponding Author: shimosaki@sp8sun.spring8.or.jp

Session 2: Lattice Design (part 2) / 27

USR upgrade for ALS

Corresponding Author: csteier@lbl.gov

Session 2: Accelerator Physics (part 2) / 28

Optimization of dynamic aperture for the ESRF upgrade

Corresponding Author: andrea.franchi@esrf.fr

Session 2: Lattice Design (part 2) / 29

Study of lower emittance lattice at SOLEIL

Corresponding Author: amor.nadji@synchrotron-soleil.fr

Session 2: Lattice Design (part 2) / 30

BAPS lattice design

Corresponding Author: xug@ihep.ac.cn

Session 2: Accelerator Physics (part 2) / 31

Coupling correction at SLS, minimum vertical emittance

Corresponding Author: leonid.rivkin@psi.ch

Session 2: Accelerator Physics (part 2) / 32

2-frequency RF system for short bunches at SPring-8

Corresponding Author: tfujita@spring8.or.jp

Session 2: Accelerator Physics (part 2) / 33

Discussion

Session 3: Accelerator Physics (part 1) / 34

Collective effects in USRs

Corresponding Author: kbane@slac.stanford.edu

Session 3: Accelerator Physics (part 1) / 35

Single and multiple Touschek scattering in low emittance rings

Corresponding Author: manuela.boscolo@lnf.infn.it

Session 3: Accelerator Physics (part 1) / 36

BAPS CSR, impedance and IBS

Corresponding Authors: wangna@ihep.ac.cn, tiansk@ihep.ac.cn

Session 3: Accelerator Physics (part 1) / 37

Propagation of ultra-short bunches in USRs and potential lasing

Corresponding Author: hettel@slac.stanford.edu

Session 3: Accelerator Physics (part 1) / 38

Optimal RF frequency

Corresponding Author: mikael.eriksson@maxlab.lu.se

Session 3: Injection (part 1) / 39

Top –up injection

Corresponding Author: leonid.rivkin@psi.ch

Session 3: Injection (part 1) / 40

Injection into low-lifetime USRs

Corresponding Author: hettel@slac.stanford.edu

Session 3: Injection (part 1) / 41

Pulsed sextupole injection for MAX-IV

Corresponding Author: simon.leemann@maxlab.lu.se

Session 4: Accelerator Engineering (part 1) / 42

Some engineering challenges for a USR machine

Corresponding Author: zhang@esrf.fr

Session 4: Accelerator Engineering (part 1) / 43

MAX-IV magnet design

Corresponding Author: martin.johansson@maxlab.lu.se

Session 4: Injection (part 2) / 44

Pulsed sextupole injection for BAPS

Corresponding Author: jiaoyi@ihep.ac.cn

Session 4: Injection (part 2) / 45

Injection scheme for the SPring-8 upgrade

Corresponding Author: soutome@spring8.or.jp

Session 4: Injection (part 2) / 46

On-axis swap-out injection

Corresponding Author: borland@aps.anl.gov

Session 4: Accelerator Engineering (part 1) / 47

High Gradient Magnet Design

Corresponding Author: soutome@spring8.or.jp

Session 4: Injection (part 2) / 48

Discussion

Session 4: Accelerator Engineering (part 1) / 49

Design and fabrication of NSLS-II sextupole

Corresponding Author: kangw@ihep.ac.cn

Session 4: Accelerator Engineering (part 1) / 50

Design for high precision small aperture magnets for BAPS

Corresponding Author: chenfs@ihep.ac.cn

Session 4: Accelerator Engineering (part 1) / 51

Discussion

Session 3: Accelerator Physics (part 1) / 52

Discussion

Session 5: Accelerator Engineering (part 2) / 53

MAX-IV vacuum chamber design

Corresponding Author: eshraq.al-dmour@maxlab.lu.se

Session 5: Accelerator Engineering (part 2) / 54

Single non-linear injection kicker magnet

Corresponding Author: olaf.dressler@helmholtz-berlin.de

Session 5: Accelerator Engineering (part 2) / 55

Fast pulsed power supply for ILC damping ring kicker

Corresponding Author: chenjh@ihep.ac.cn

Session 1: Instrumentation and Feedback / 56

SOLEIL orbit feedback systems and photon BPMs

Corresponding Author: denard@synchrotron-soleil.fr

Session 1: Instrumentation and Feedback / 57

Multi-Bunch Feedback System in USR

Corresponding Author: tfujita@spring8.or.jp

Session 1: Instrumentation and Feedback / 58

Feedback system for USRs

Corresponding Author: csteier@lbl.gov

Session 1: Instrumentation and Feedback / 59

Discussion

Session 2: Insertion Devices / 60

IDs for the ESRF upgrade

Corresponding Author: chavanne@esrf.fr

Session 5: Accelerator Engineering (part 2) / 61

Ground vibration for BAPS

Corresponding Author: jidh@ihep.ac.cn

Session 2: Insertion Devices / 62

Superconducting IDs at BINP

Corresponding Author: zolotarev@inp.nsk.su

Session 2: Insertion Devices / 63

IDs for Shanghai Synchrotron Radiation Facility

Corresponding Author: zhouqiaogen@sinap.ac.cn

Session 5: Accelerator Engineering (part 2) / 64

Discussion

Session 2: Insertion Devices / 65

PETRA-III damping wiggler experience

Corresponding Author: alexander.kling@desy.de

Session 2: Insertion Devices / 66

Undulator technology for USR

Corresponding Author: jaski@aps.anl.gov

Session 2: Insertion Devices / 67

Cryogenic permanent magnet and superconducting small period undulators

Corresponding Author: johannes.bahrtdt@helmholtz-berlin.de

Session 2: Insertion Devices / 68

Discussion

Closing Session / 69

Report writing

Closing Session / 70

Summary

Session 2: Lattice Design (part 2) / 71

Discussion

Session 4: Accelerator Engineering (part 1) / 72

Anticipated limits on machine stability and consequences on machine and beamline designs

Corresponding Author: denard@synchrotron-soleil.fr

73

Development and Commissioning of a Single Non-linear Kicker Magnet System for the BESSY II Storage Ring Injection

Author: Olaf Dressler¹

Co-author: Peter Kuske ¹

¹ Helmholtz-Zentrum Berlin

Corresponding Author: olaf.dressler@helmholtz-berlin.de

Top-Up injections without noticeable motion of the stored beam is a challenge. The common method of beam accumulation with a local bump formed by four independent pulsed dipole kicker magnets usually causes beam oscillations. The matching of the four independent kicker systems regarding pulse jitters and shapes is technologically limited. Powering neighboring kicker magnets in pairs reduces the excitation of the beam. An even more promising approach is to deploy a single non-linear kicker magnet with zero $B_{x,y}$ -field in the center and an off-axis maximum, B_y , which is horizontally displaced by 10-12 mm. There the injected beam gets kicked and loses half of its transverse momentum. Such a magnet was designed and built as a short in-vacuum magnet with a small vertical gap height. For first beam tests the kicker was placed in the second straight section after the injection point, and the 1.5 μ s pulse was designed to deflect the 1.72 GeV beam by 1 mrad. In this talk, the calculation and measurement of the magnetic fields, the mechanical design as well as the electrical

pulser circuit are described. The experiences with the commissioning of this kicker magnet system are discussed.

75

Single and Multiple Touschek scattering in low emittance rings

Author: Manuela Boscolo¹

¹ INFN

Corresponding Author: manuela.boscolo@lnf.infn.it

A quick overview on the intra-beam scattering theory and conventional computations will be presented, as well as for the Touschek effect. A parallelized tracking code for the IBS has been recently developed in view of the SuperB project; benchmarking with measurements (at SLS), with theory and with other codes (SIRE-CLIC-DR) have been done. Touschek lifetime is evaluated in most 3rd generation light sources, high intensity machines and damping wigglers for linear colliders, being one of the major limits of the beam lifetime. The STAR code developed to study their effect in DAFNE and SuperB will be described. To conclude, some remarks on the IBS and Touschek effect for the USRs.

76

Superconducting IDs at BINP

Author: Konstantin Zolotarev¹

¹ BINP

Corresponding Author: zolotarev@inp.nsk.su

Superconducting wigglers are very popular devices for generation of synchrotron radiation (SR) in the hard X-ray spectral range. Moreover, recently superconductive wigglers have also been used for emittance reduction in a few projects of light sources and damping rings of linear colliders. Budker Institute of Nuclear Physics (BINP) has great experience in the design and fabrication of superconducting wigglers. In the past thirty years, the Institute developed and fabricated more than twenty devices, which are now used at many SR centers over the world. A detailed analysis of this activity shows many interesting trends in the demand for superconductive IDs and their development in the past and at present and can be helpful in predicting the future tendency in this field.

This report reviews the BINP activity for developing and fabrication of superconductive IDs, tries to reveal the main trends, and presents some new ideas for future improvement of their design.

77

MAX IV vacuum System design

Author: Eshraq Al-Dmour¹

¹ Vacuum group coordinator

Corresponding Author: eshraq.al-dmour@maxlab.lu.se

The fact that the 3 GeV storage ring of MAX IV has a compact lattice and small aperture for the magnets makes the vacuum system a challenge in all stages, from design to installation and commissioning. The talk will cover the considerations for the vacuum system together with the layout. The design of the copper vacuum chambers, NEG coating and production issues are presented.

78

Undulator Technology for Ultimate Storage Rings (USRs)*

Author: Mark Jaski¹

¹ *Argonne National Laboratory*

Corresponding Author: jaski@aps.anl.gov

M. Jaski, R. Dejus, C. Doose, J. Grimmer, Y. Ivanyushenkov, Y. Jaski, M. Kasa, S. Kim, E. Moog, I. Vasserman, J. Wang, M. Borland, E. Gluskin, Advanced Photon Source, Argonne, IL 60439, U.S.A.

Abstract

One of the limitations on tuning range, brightness, and flux from undulators in storage rings is the extreme x-ray power and power density. It is difficult to engineer photon shutters and other components that can withstand these high heat loads. An alternative is to turn off the heat load when the photon shutter is closed by, for example, turning off the current in an electromagnetic undulator. To remove the heat load produced by a hybrid permanent magnet (HPM) undulator, the gap must be opened mechanically.

Electromagnetic undulator technology has progressed at the APS with the recent development of three new devices: a normal-conducting electromagnetic variably polarizing undulator with quasi-periodic capabilities has been installed at the APS, a superconducting undulator is scheduled to be installed at the APS, and a test model of a normal-conducting variably polarizing undulator with the added capability of rapid switching (10 Hz) between left- and right-circular polarizations is being built. A review of these devices along with the application of electromagnetic devices used with USRs will be discussed. The application of helical superconducting undulators to take advantage of the narrower horizontal emittance of the beam in a USR is also discussed.

*Work supported By U.S. Department of Energy, Office of Science, Office of Basic Energy Sciences, under contract number DE-AC02-06CH11357.

79

Lattice design for Spring-8 II

Author: Yoshito Shimosaki¹

¹ *JASRI / SPring-8*

Corresponding Author: shimosaki@sp8sun.spring8.or.jp

A feasibility of a very low-emittance storage ring has been studied for an upgrade project of the SPring-8, SPring-8 II. Its ultimate goal is to provide a superior brilliance for 0.5 ~ 100 keV photons. A sextuple bend achromat lattice with the natural emittance of 70 pmrad at 6 GeV has been examined as the first candidate. In order to increase the brilliance and to enlarge the dynamic aperture until the required values, the step-by-step optimization has been performed in designing linear optics, in selecting the betatron tune, and in designing nonlinear optics. The latest design for the coming upgrade of SPring-8 will be presented.

80

Two-frequency RF system for short bunches for SPring-8 II

Author: takahiro fujita¹

¹ SPring-8

Corresponding Author: tfujita@spring8.or.jp

Harmonic RF system for SPring-8 II will be presented. The frequency of the harmonic would be half-integer multiple of fundamental RF. This RF system lengthen most of bunches in order to suppress emittance growth and lifetime decrease due to Intra-beam scattering. With this harmonic RF system, short-bunch is also available.

81

Multi-bunch feedback system in USR

Author: takahiro fujita¹

¹ SPring-8

Corresponding Author: tfujita@spring8.or.jp

In ultra-low emittance ring for light source, hybrid filling of bunches and narrow gap undulators would contribute transverse instability. Under the hybrid filling, isolated bunch with high current and bunch train with high average current would be stored simultaneously. Mode coupling single bunch instability and multi-bunch instability due to resistive wall impedance must be suppressed by bunch-by-bunch feedback system in transverse plane. Since bunch current ratio in the hybrid filling would reach 2 orders of magnitude, an automatic attenuator which is sensitive to bunch current is developed at SPring-8 in order to avoid saturation in feedback processor. We will discuss effect of noise at BPM signal and signal processor of feedback system on effective beam size.

82

BAPS Lattice Design

Author: gang xu¹

¹ ihep

Corresponding Author: xug@ihep.ac.cn

The USR is one of the choices for Beijing Advanced Photonic Source(BAPS). The goal of the lattice design is approaching diffraction limit for 10keV X-ray. In the talk we will show several results of lattice design, parameters of damping wiggler, method of making round beam, process of chromaticity correction and tracking results of dynamic aperture.